

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Non-Woven Diagonal
FACE FIBER:	100% Polypropylene
WEB THICKNESS:	.140 Inches
WEB WEIGHT:	35.39 ounces per square yard
DENSITY:	Average Density = 9,100; Weight Density = 150,000
BACKING:	Bitumen / Polyflex
STANDARD SIZE:	23.63" x 23.63" (60 cm x 60 cm)
INSTALLATION METHOD:	Quarter-Turn

WARRANTIES:

WARRANTY:	10 Year Limited Warranty, Including Face Wear, Moisture Barrier, Wick-Back, Delamination, Tuft Bind, Unraveling, and Static Protection
-----------	--

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):	Class II (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.