

901 Island Light

RLM Reflectors

Job Information:

Project:

Prepared by:

Comments:

Approved by:

Features:

Reflector: Spun from heavy gauge aluminum with an rolled in bead.

Lamp Types:

Incandescent: 150W max. Medium base porcelain socket.

LED: Requires External Driver Enclosure.

LED(850/1250): Cree LMH2 Module with Osram Driver

LVE01: Cree CXA COB with Osram Driver, Requires Glass Jar

CFL: Requires External Driver Enclosure.

HPS: Requires External Driver Enclosure.

MH: 150W Max Requires External Driver Enclosure.

Mounting: Sturdy cast aluminum housing fits over 2 3/8" O.D. tenon locked with 3 set screws. Includes prismatic glass globe. Aluminum reflector, Powder coated. Medium base only.

Finish: Powder Coat Finish for Outdoor use. Complete color selection found at [bocklighting/colors](http://www.bocklighting.com/colors).

Certification: Built to UL 1598 and UL Certified for Damp and Wet Locations.



Size	Diameter	Height	Max Wattage
901	20"	18"	150W

Note: This isn't a complete spec to order from. Bock offers more than what is shown on a single page. Use the RLM Catalog or RLM Configurator to make a valid part number and submittal.

<http://www.bocklighting.com/sales/rlm-configurator>

Ordering Guide:

Example: 901-G0 / MED5

Series	Lamp Type
901 = Island Light	MED = Incandescent Base LED(850/1250) = LMH2 Module LVE01-(27/35/40K) @ (850/1250/1400/1800) = Cree CXA COB, Universal PSMH(50/70/100/150) = Pulse Start Metal Halide HPS(50/70/100/150) = High Pressure Sodium

BockLighting

Phone: (216) 912-7050 Fax: (216) 912-7051
sales@bocklighting.com
www.bocklighting.com

20150527