

## DESCRIPTION

Corelite's latest addition to its line of shallow recessed fixtures, the Class R3, is the ultimate complement to the R1 and R2, offering the ideal combination of performance and aesthetics. The fully luminous housing of the R3 creates a high sense of style and superior brightness management, all while providing low watts per square foot to satisfy the most stringent energy requirements. To further realize the Class R series' design potential, the Class R3 is available with a complete palette of lamp options - including T8 and compact fluorescent - and maintains the series' dedication to shallow plenum applications with a minimal 3-3/4" deep housing.

Catalog #		Type
Project		
Comments		Date
Prepared by		

## SPECIFICATION FEATURES

### A ... Construction

Low profile housing constructed of die-formed 20 gauge cold rolled steel with integral 20 gauge gear tray.

### B ... Reflectors

Micro prismatic acrylic lens composed of frosted and clear blend.

### C ... Shielding

Extruded acrylic center optic with frosted acrylic side lenses. Perf pattern is silkscreened onto the surface of the inlay. Lens is secured to housing via injection molded inserts for easy lamp access.

### D ... Electrical

T8 fixtures use UL listed Class P, 265ma T8 instant start universal voltage electronic ballasts. Power factor of 95% with less than 10% THD. Fixtures and electrical components certified to UL and CUL standards.

### E ... Finish


Fixture housings are high reflectance white using electrostatically applied polyester powder coat paint.

### Mounting



Standard flange design works with most lay-in ceiling types. Integral pryout tabs secure luminaire to ceiling grid from above. Fixture offers tie-in locations for tie-wire on all corners, consult local code for appropriate tie-wire recommendations. Cannot mount more than four (4) fixtures continuously in one direction, or eight (8) fixtures total.

### NOTE: Concealed Ceiling

Class R may be installed into inaccessible ceilings (sheet rock, wood panel, etc.). This is achieved with the Metalux DFW series drywall frame-in kit, ordered separately from Metalux. Specify "CC" for the Corelite Ceiling Type. Specify the following part numbers separately, from Metalux: For 1x4, order Metalux part # DF-14W-U



Alternate Dimensions - 1x4



## CLASS R3 Rectangular Perf Inlay Round Perf Inlay

1T8

1'x4' Recessed  
3-3/4" Depth



## ORDERING INFORMATION

Sample Number: R3-WG-1T8-1C-UNV-14-T1

<b>Series</b> R3- Class R3	<b>Shielding</b> D- Round Perf Inlay G- Rectangular Perf Inlay	<b>Lamp Type</b> T8- T8 Normal Output	<b>Wiring 1</b> B- Battery Pack C- Standard Circuit D- Dimming / Step Dimming E- Emergency T- Nightlight Y- Daylight	<b>Voltage 1</b> 120- 120V 277- 277V 347- 347V UNV- Universal (120V-277V)	<b>Ceiling Type</b> T1- 1" Grid, Slot-Grid, 9/16" Tegular T9- 9/16" Grid CC- Concealed Ceiling SU- Surface Mount	<b>Options 1</b> AR- Air Return CP- Chicago Plenum SD- Step Dimming WG- 6' Whip Flex W12- 12' Whip Flex
<b>Reflector</b> W- White	<b>Number of Lamps</b> 1- 1 Lamp	<b>Number of Circuits</b> 1- 1 Circuit		<b>Size</b> 14- 1' x 4'		

Notes: 1 Not all options available. Please consult your Cooper Lighting Representative for availability.