

DESCRIPTION

The Corelite Z3 recessed luminaire meets the demands of the new energy culture with superior lighting and energy performance. Its engineered optical system delivers luminaire efficiencies greater than 85% while maintaining a soft luminous glow for high visual comfort. Its unique light distribution fills the volume of space to ensure that vertical surfaces glow to create the perception of spaciousness. To further realize the design potential of the Z3 series, it is available with a complete palette of shielding options, and lamp options, including T5,T8,LED and compact fluorescent, and maintains the series dedication to shallow plenum applications with a minimal 3-3/4 inch deep housing.

Catalog #		Type
Project		
Comments		Date
Prepared by		

SPECIFICATION FEATURES

A ... Construction

Low profile housing die-formed 20 gauge cold rolled steel with integral 20 gauge gear tray.

B ... Reflectors

Precision tooled, high reflectance sheet metal, which allows for easy access to ballast compartment.

C ... Shielding

Center shielding consists of UV-stable co-extruded external acrylic lens with internal high light transmission Nano-Prismatic inlay material. The Nano-Prismatic film mitigates lamp image brightness with organized microscopic acrylic particles. Lens is secured to housing via injection molded inserts for easy lamp access.

D ... Electrical

T8 fixtures use UL listed Class P, 265ma T8 instant start universal voltage electronic ballasts. Power factor of 95% with less than 10% THD. Fixtures and electrical components certified to UL and CUL standards.

E ... Finish

Fixture housings are standard white using electrostatically applied polyester powder coat paint.

Mounting



Standard flange design works with most lay-in ceiling types. Integral pryout tabs secure luminaire to ceiling grid from above. Fixture offers tie-in locations for tie-wire on all corners, consult local code for appropriate tie-wire recommendations. Cannot mount more than four (4) fixtures continuously in one direction, or eight (8) fixtures total.



CLASS Z3
Nano Prism Lens

1T8

2'x2' Recessed
3-3/4" Depth



ORDERING INFORMATION

Sample Number: Z3-WN-1T8-1C-UNV-22-T1

Series Z3: Class Z3	Shielding N: Nano Prism Lens	Lamp Type T8: T8 Normal Output	Wiring ¹ B: Battery Pack C: Standard Circuit D: Dimming / Step Dimming E: Emergency T: Nightlight Y: Daylight	Voltage ¹ 120: 120V 277: 277V 347: 347V UNV: Universal (120V-277V)	Ceiling Type T1: 1" Grid, Slot-Grid, 9/16" Tegular T9: 9/16" Grid CC: Concealed Ceiling SU: Surface Mount	Options ¹ AR: Air Return CP: Chicago Plenum SD: Step Dimming W6: 6' Whip Flex W12: 12' Whip Flex
Reflector W: White	Number of Lamps 1: 1 Lamp	Number of Circuits 1: 1 Circuit		Size 22: 2' x 2'		

Notes: 1 Not all options available. Please consult your Cooper Lighting Representative for availability.