



VAS—Medium Curve

WALL MOUNT INTEGRAL ELECTRONIC BALLAST



**COMPACT FLUORESCENT
26W DTT, 32W TT, & 42W TT**



DIMENSIONS



MOUNTING BRACKET



ORDERING

FIXTURE	MOUNTING TYPE	VOLTS	FINISH	OPTIONS
Medium Curve Compact Fluorescent (PL-T, GX24q-4) Integral Electronic Ballast VCM574 (1)-CF26DTT, CF32TT, CF42TT	WCB <i>Wall Mount</i> <i>Integral Electronic Ballast</i>	1 = 120V 2 = 277V 7 = 347V* <i>*Contact Factory</i>	W Semi-Gloss White BL Semi-Gloss Black BR Semi-Gloss Bronze N Semi-Gloss Natural S Semi-Gloss Satin* SF Specify Finish (See Color Chart) CC Custom Color (Contact Factory) <i>For Textured Finish, Add "T" to Finish Selection * (e.g. TW = Textured White)</i>	PG Custom Patterned Glass Fascia** WG Waffled Glass Fascia CEG Colored Etched Glass Fascia** CWG Colored Waffled Glass Fascia** PP Perforated Metal Fascia LP Custom Fascia Template SP Solid Aluminum Fascia (Painted To Match Luminaire) DM Fluorescent Dimming Ballast ** CM Column Mount**
ORDERING EXAMPLE: VCM574 / WCB / 1 / BL / WG * Textured Finish Not available for SATIN color ** Contact Factory For Details				

SPECIFICATIONS

Housing End plates, surface mounting brackets and integral ballast housings are single piece die cast aluminum. The main housing is extruded aluminum. The standard glass fascia is .188" thick tempered molded etched glass. The fixture is shipped complete with ballast and pre-wired for installation. For use with a standard 4-0 j-box (by others). Additional structural backing is required (by others).

Reflector A patented two-tiered direct/ indirect reflector system constructed of 95% reflective, specular, peened aluminum.

Top Lens *Luminaires are provided with micro prismatic tempered glass lenses secured to an anodized aluminum doorframe. Die-cast aluminum latches with stainless steel springs hinge in either direction allowing for tool-less re-lamping and maintenance.*

Electrical: All fluorescent ballast are electronic, high power factor, thermally protected with THD of less than 10% and available in 120 & 277v. Dimming ballasts are an available option.

Labels: UL and CUL approved for installation in Damp Locations.



FIXTURE	MOUNTING TYPE	VOLTS	FINISH	OPTIONS

APPROVED: _____

JOB NAME: _____

TYPE: _____

Insight Lighting reserves the right to change specifications with out notice due to product improvements.

INSIGHT
Rio Rancho, NM 87144
TEL: 505 345-0888
www.insightlighting.com

05/28/13