







# INDOOR ARCHITECTURAL LUMINAIRES

# VAS—Medium Curve

PENDANT MOUNT  
INTEGRAL ELECTRONIC BALLASTS

COMPACT FLUORESCENT  
26W DTT, 32W TT AND 42WTT



## ORDERING

FIXTURE	MOUNTING TYPE	VOLTS	FINISH	OPTIONS
<b>Medium Curve</b>  <b>Compact Fluorescent</b> <b>Integral Electronic Ballasts</b> <b>(PL-T, GX24q-4)</b> <b>VCM574 (1)CF26DTT, CF32, CF42TT</b>	<b>PNS-X</b>  <b>Pendant Mount</b>  <b>X = Stem Length</b> <b>Min. 13" Max 96"</b>	<b>1=120V</b>  <b>2=277V</b>  <b>7=347V*</b>  <b>*Contact Factory</b>	<b>W</b> Semi-Gloss White <b>BL</b> Semi-Gloss Black <b>BR</b> Semi-Gloss Bronze <b>N</b> Semi-Gloss Natural <b>S</b> Semi-Gloss Satin* <b>SF</b> Specify Finish (See Color Chart) <b>CC</b> Custom Color (Contact Factory)  For Textured Finish, Add "T" to Finish Selection * (e.g. TW = Textured White)	<b>PG</b> Custom Patterned Glass Fascia** <b>WG</b> Waffled Glass Fascia <b>CEG</b> Colored Etched Glass Fascia** <b>CWG</b> Colored Waffled Glass Fascia** <b>PP</b> Perforated Metal Fascia <b>LP</b> Custom Fascia Template <b>SP</b> Solid Aluminum Fascia (Painted To Match Luminaire) <b>DM</b> Fluorescent Dimming Ballast **

ORDERING EXAMPLE: VCM574 / PNS-36" / 1 / CC / WG

\* Textured Finish Not available for SATIN color

\*\* Contact Factory For Details

## SPECIFICATIONS

**Housing** End plates, surface mounting brackets and integral ballast housings are single piece die cast aluminum. The main housing is extruded aluminum. The standard glass fascia is .188" thick tempered molded etched glass. The fixture is shipped complete with ballast and pre-wired for installation. For use with a standard 4-0 j-box (by others). Additional structural backing is required (by others).

**Reflector** A patented two-tiered direct/ indirect reflector system constructed of 95% reflective, specular, peened aluminum.

**Top Lens** Luminaires are provided with micro prismatic tempered glass lenses secured to an anodized aluminum doorframe. Die-cast aluminum latches with stainless steel springs hinge in either direction allowing for tool-less re-lamping and maintenance.

**Electrical:** All fluorescent ballast are electronic, high power factor, thermally protected with THD of less than 10% and available in 120 & 277v. Dimming ballasts are an available option.

**Labels:** UL and CUL approved for installation in damp locations.

FIXTURE	MOUNTING TYPE	VOLTS	FINISH	OPTIONS



APPROVED: \_\_\_\_\_  
 JOB NAME: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

Insight Lighting reserves the right to change specifications with out notice due to product improvements.

**INSIGHT**

Rio Rancho, NM 87144  
 TEL: 505 345-0888  
 www.insightlighting.com

05/24/13