HALF MOON COVE LED









SERIES 1301





WEIGHT: Lightweight, 10 oz per 12"

RETAIL / HOSPITALITY / OFFICE

FIXTURE:

- 4 sizes for easy customization: 1 ft, 2 ft, 3, ft, and 4 ft
- 48" minimum radius with 1 foot sections
- Nichia LED technology lighting performance
- Energy savings up to 50% and long life sustainability
- 7 year warranty

HIGH PERFORMANCE LEDs:

- Tightly binned mid-powered Nichia LEDs guarantee color uniformity
- Improved lumens per watt and propriety PCB system for even illumination, with superior thermal management
- 50,000 hours at 70% lumen maintenance (L70)
- 3000°K, 3500°K, or 4000°K with CRI 80 R9>50

PERFORMANCE:

- 79 Lumens/Watt @ 3500°K based on independent photometric LM79 test reporting
- 12 Watts, 880 lumens, per foot (.5" O/C)

REMOTE DRIVER:

- Philips Advance 24 VDC driver
- Class 2 universal multi voltage 120 277v (50-60Hz) input
- Dimmable constant voltage, full cut off 0 10 volt driver, .95 Power Factor
- Instant start, with no humming
- 8 foot max connection per driver (96W max)

HOUSING:

- Aluminum housing for thermal management
- Low profile depth: 1 1/4"
- Architectural grade diffused lens
- UL Damp location rated
- 24 ga interconnector wires

SPECIFICATION / ORDERING CODE: *Example 1301-V-36-3-3-LED-30*

PRODUCT	WATTS	VOLTAGE	SIZE	LED-CCT
1301-V		3		LED-30 3000K
HALF MOON	12	UNIV.	1 1'	LED-35 3500K
COVE		120-277V		LED-40 4000K
1301-V	12	3	1	

PRODUCT	WATTS	VOLTAGE	SIZE	LED-CCT
1301-V		3		LED-30 3000K
HALF MOON	36	UNIV.	3 3'	LED-35 3500K
COVE		120-277V		LED-40 4000K
1301-V	36	3	3	

PRODUCT	WATTS	VOLTAGE	SIZE	LED-CCT
1301-V		3		LED-30 3000K
HALF MOON	24	UNIV.	2 2'	LED-35 3500K
COVE		120-277V		LED-40 4000K
1301-V	24	3	2	

	1301-V	48	3	4	
(COVE		120-277V		LED-40 4000K
(HALF MOON	48	UNIV.	4 4'	LED-35 3500K
(1301-V		3		LED-30 3000K
	PRODUCT	WATTS	VOLTAGE	SIZE	LED-CCT

OPTIONS	1301-MC Mounting Clips (2/pack)	Remote Philips Advance 24V Driver
AE 111/143:	1 1 1 30 1 - WI VIOLULULULULU (1105 (7/0a(K)	T THEIR PERMITS ACTIVATION 74V THINE

SUBMITTAL	_
-----------	---

Date:	
Project:	
Fixture Type: .	
Location:	
Comments:	



TYC LIGHTING. 2800 Saturn Street Brea, CA 92821 Phone: 714.522.6688 x7 www.tyclighting.com

HALF MOON COVE LED











SERIES 1301

PHOTOMETRICS




12W per Foot

DIMENSIONS



DRIVER IN REMOTE ENCLOSURE




POSITIONING FOR SHADOW-FREE EVEN ILLUMINATION






clearance

Curved Applications






MOUNTING CLIPS

- Easy snap and lock in design
- 2 clips required per fixture
- Mounting screws by contractor



END TO END CONNECTION

- 6" lead length provided
- Lead wires to be connected and tucked under fixture



Expanded View



Top View