C O L E L I G H T I N G

Other Options

Faceplate color
Core drill installation
Tamperproof screws

eries	LED	Fluor.	Incan.	Dimming	Exterior	Interior	Feed- Thru
131	•			•	•	•	

High performance LEDs are standard with this fixture

Core drill option

Catalog Number

L131W-WHT-TP

Lamp

S

LED 4.2W, (235 Im @ 3000°K)

L131W

Photometric data available for Steplites can be downloaded at: www.colelighting.com/downloads/1

Options

Core drill installation: Supplied with 6 ft. 18/3 jacketed cord. Add suffix **-CD**.

Dimming: Standard ELV. Add suffix **-DIM**. **LED color:** 4000°K (265 lm). Add suffix **-4K**.

Tamperproof screws: Socket head faceplate

screws. Add suffix -TP.

Bronze faceplate: Satin finish, clear coated.

Add suffix -B.

Alternate faceplate color: Black or white. Add suffix -BLK or -WHT.

How to Specify

- 1. Select catalog number.
- 2. Add suffixes for options required to meet job conditions.

Steplites

L131 SERIES

Description

This compact directional Steplite features high performance LEDs. It is appropriate in a variety of interior or exterior applications where low glare and cutoff performance is desired. The rugged construction, engineering excellence, and quality make this fixture ideal for specification in most public areas.

Construction

• Housing is 16 gauge spun steel suitable for concrete pour installation • Housing coated in white polyester • Cast aluminum eyelid faceplate with a metallic aluminum polyester finish, retained by stainless steel screws • Clear ribbed spread lens set in silicone sealant • Suitable for wet locations in any wall construction.

Electrical

- Fixture is wired with high performance LEDs
- Integral driver is 120V only and features ELV dimming capability
 One 1/2"conduit knockout provided on back of housing
 Core drilled versions include 6 ft. of 18/3 jacketed cord and weatherproof strain relief.

Mounting

Holes provided in back of housing for mounting.

Custom

If your project demands a special fixture we would be pleased to discuss the production of modified standard fixtures or custom fixtures to suit your specific conditions. For more information on our custom capabilities, please contact your local Cole representative.



C.W. Cole & Company, Inc. 2560 N. Rosemead Boulevard South El Monte, CA 91733-1593

Tel. (626) 443-2473 Fax (626) 443-9253 info@colelighting.com www.colelighting.com