



ALUMLITE FLUORESCENT SERIES

Manufactured in the U.S.A.



"Lighting for the Professional Designer"

PRODUCT *construction*

Applications: Cove Lighting, Wall Lighting, Display Lighting,
Indirect Lighting, Undercabinet Lighting

Voltage: 120V or 277V (Consult Factory for Other Voltages)

Socket Types: Axial, Miniature G5, Medium Bi-Pin, G23, GX23,
G23-2, 2G7, G24D-2, G24Q, GX24D, GX24Q, 2G11

Lamps: T-2, T-5, T-8, Compact Fluorescent, Quad
Fluorescent, Triple Tube Fluorescent, Bi-X Lamps
(Lamps Not Included)

Length: Built to Order (Custom Lengths to Fit Application)

Lead Wire: Standard 6' Lengths (Custom Lengths Available)

Mounting: Surface Mount or Recessed

Material: High Quality Extruded Aluminum

Dimming: Dimming Available

Light Output: IES Files Available (Consult Factory)

Ballasts: Integral and Remote (Included)

Optional: Reflectors (RE1, RE2, RE3, RE4, or Custom)

ELECTRICAL *information*

AlumLite is a 120V or 277V fluorescent system that is available with integral or remote ballasts (consult factory for other voltages). AlumLite is available with a variety of dimming ballasts to meet your dimming control requirements.

APPLICATION *information*

AlumLite Series is available with long life, energy efficient fluorescent lamps that allow for low maintenance installations. AlumLite can be field cut or modified for an easy and fast installation not requiring exact field dimensions.

AlumLite is available in natural aluminum, anodizing, or powder coating to meet your application needs. AlumLite is available with flexible modular systems to meet those difficult radius installations without special equipment or custom curving. The flexible modular systems are designed to maintain proper lamp spacing to eliminate any dark shadows or scalloping.

AlumLite enhances any environment with nice even illumination for cove lighting, accent lighting, wall washing, or indirect lighting. Venues include hotels, schools, theatres, restaurants, casinos, retail stores, and other venues.



ETL Listed for Dry or Wet Location
Meets UL and CSA Requirements



CALIFORNIA ACCENT LIGHTING, INC.

2034 E. Lincoln Ave. #431 Anaheim, CA. 92806

P. (714)535-7900 | F. (714)535-7902 | (800) 921-CALI (2254) | info@calilighting.com | www.calilighting.com

Copyright 2010 © CALI. All rights reserved. CALI reserves the right to make changes or withdraw specifications without prior notice.