

USA 800.657.6324 www.activesafety.com

Project:
Arch:
Catalog #:
Date:

## Series 300 Photoluminescent Hand Rail Marker

## **Features**

Viewing Distance: 25 feet Operating Life: 25+ years

Activation: 1 footcandle of artificial lighting including

LED and Fluorescent.

Marker Composition: Durable photoluminescent coating on

aluminum.

Marker Color: Green illuminating color on aluminum.

Mounting: Field applied adhesive

Dimensions: Width: 1/2" & 1", Length: 10' Flat, 12' Curved. Custom sizes, curved or flat.

Features: Flat and curved profiles for stair

handrails. Non-electric. Non-radioactive. No hazardous materials. Easy installation onto a variety of substrates. Automatic

operation. Durable. Explosion-proof.

Warranty: Limited lifetime.

Green Attributes: Non-electric. Non-radioactive.

No hazardous materials. Long life.

Near-zero maintenance.

Listings and Codes: UL 1994 listed.

IBC, IFC and NFPA Compliant.

Active Safety's Series 300 Handrail Marker is a

durable aluminum strip with a photoluminescent coating that installs directly onto curved or flat handrails in exit pathways. Available in curved and flat profiles, the marker requires the use of an adhesive for permanent installations.

Designed for stairwells and exit passageways requiring a high quality finished appearance, especially in areas with a high

traffic load.

Ordering Format (example: 300 – AL – 1/2 – 12 CU)

SERIES	BACKING	WIDTH	LENGTH
300	AL - Aluminum ALA- Aluminum w/ adhesive	<u>1/2</u> – 1/2" <u>1</u> – 1"	<u>10 F</u> – 10' flat 12 <u>CU</u> – 12" curved

## **Specification Description**

Active Safety's Series 300 Hand Rail Marker. Compliant to IBC and NFPA codes.

Photoluminescent, non-electrical, non-radioactive aluminum with photoluminescent color. 25 foot visibility rating with 1 footcandle of charging illumination. Flat or curved profiles.

Active Safety Series 300.

