CP4060 - CARLTON™ 27" Bowl, Stem Suspension



Project: VisaLighting.com/products/Carlton Type:

Fill in shaded boxes using information listed below

Order CP4060 Code: MODEL

A SOURCE

B VOITAGE











A SOURCE (Select one) B VOLTAGE (Select one)

MVOLT fixture accepts 120 through 277 input voltage

Fluorescent Sources		Voltage
4F39-2FC\$40/22	Uplight - (4) 39w long twin tube, 2G11 base Bowl Light - (1) 40w and (1) 22w T5 Circular, 2GX13 base	Select MVOLT, 120V or 277V
4TF26-2FCS40/22	Uplight - (4) 26w triple, 4-pin GX24q-3 base Bowl Light - (1) 40w and (1) 22w T5 Circular, 2GX13 base	
4TF32-2FCS40/22	Uplight - (4) 32w triple, 4-pin GX24q-3 base Bowl Light - (1) 40w and (1) 22w T5 Circular, 2GX13 base	Select MVOLT, 120V, 277V or 347V
4TF42-2FC\$40/22	Uplight - (4) 42w triple, 4-pin GX24q-4 base Bowl Light - (1) 40w and (1) 22w T5 Circular, 2GX13 base	

FINISHES (Select one Trim Finish)

See page 2 for color chart

Powder Coat Painted Finishes (Standard)

AG7038	Agate Grey	CVBL	Cove Blue	GW9002	Grey White	PB1035	Pearl Beige
BMAT	Bronze Matte	CW9001	Cream White	HTHR	Heather	RUST	Rust
BRNZ	Bronze	GLIM	Glimmer	JB9005	Jet Black	SUNG	Sungold
BSIL	Blade Silver	GSIL	Graphite Silver	OBRZ	Old Bronze	TW9016	Traffic White

Metal Finishes (Premium)

rinisnes	(rremium)				
BA	Brushed Aluminum	BUA	Brushed Copper Alternative	PRA	Pewter Alternative
BB	Brushed Brass	BZA	Brushed Bronze Alternative	RBA	Rustic Brass Alternative
BBA	Brushed Brass Alternative	CB	Polished Chrome	SN	Satin Nickel
BCA	Brushed Chrome Alternative	OBA	Oil-Rubbed Bronze Alternative	SNA	Satin Nickel Alternative
BCB	Brushed Chrome	PB	Polished Brass		

35" Bowl Depicted

This complete family includes pendants, flush mount ceiling units, and wall sconces that boast

an elegant, classic trim. The luminous acrylic and traditional detailing enhance a wide range of architectural settings and styles.

DIMENSIONS

W = WidthOAH = Overall Height NBS = Nominal Bowl Size X = Body Height

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(36) indicates an overall fixture height of 36"

▲ OAH must be specified

26-1/2" (673 mm) (178 mm)25" OAH (635 mm) NBS 23x5" (584x127 mm)



DIFFUSER OPTION

Diffuser is matte white acrylic unless ABA option is selected ABA Hand Painted Alabaster Alternative

OPTIONS (Multiple Selections Allowed)

▲ Option availability may be interdependent with Voltage, Source or Other Options

Add finial. Addition of AF option increases X dimension (height) by 1-1/8" ΑF

Damp clear coat for metal finishes (required for 5 year warranty when used in damp locations) DCC

FUSE Fusing, specify 120V or 277V

REM Remote emergency battery pack; not available for 347V

• TL Top lens, tempered prismatic glass

XPS Express 10 day shipping Items marked with a bullet (•) are not available with XPS

AF Option









©Visa Lighting. Design Modification Rights Reserved.


FTL Listed

5 Year Warranty

CP4060 – CARLTON[™] 27" Bowl, Stem Suspension




Photometrics




Technical Information

- Uplight and bowl light separated for optical performance and wired for discrete operation
- High power factor electronic ballast
- Wide reflector distribution is standard; optional batwing distribution
- Easy tool-less relamping
- Mounts to standard electrical junction box (by others) with provided hardware for ceiling slopes up to 45 degrees from horizontal
- Spun metal trim
- Thermally formed 1/8" thick white acrylic diffuser with matte finish
 - ◆ UV stable
- UL-94 HB Flame Class rated
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suited for exterior applications



Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>

For additional information see <u>VisaLighting.com/materials-finishes</u>







This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved.