



For a long overall, attach the stem segments with supplied coupler. Align flats on stem to set screws and securely fasten.

### Preparation

Check all instructions with the fixture as some preparation may be necessary before the following steps.

### Instructions

- 1) Depending on the length of screws supplied with the junction box (by others), you may need to use the longer screws provided.
- 2) Insert swivel ball/stem assembly through cast swivel plate and fasten swivel ball retainer & ground wire with screws provided.
- 3) Insert stem through canopy, pull fixture wires through stem and securely fasten stem to the fixture.
- 4) Fasten cast swivel plate to junction box with 8-32 screws provided.
- 5) Make all wire connections per local and national codes.
- 6) Lift canopy in place and secure with screws provided.

When using electrical equipment, basic safety precautions should always be followed, including the following:  
 1) Read all instructions carefully before installing and save for future use. Make sure all connections are in accordance with the National Electrical Code and local regulations.  
 2) To avoid possible electric shock, be sure the power supply is turned off before servicing or installing the fixture. Service should be performed by qualified personnel.  
 3) These instructions may not cover all details or variations. If additional information is needed, please contact Visa Lighting.

**Drawing : 760658XX**  
**Rev : A**    **Sheet 1 of 1**

**VISA LIGHTING**  
 An Oldenburg Group Company  
 1717 West Civic Drive Milwaukee, WI 53209  
 414-354-6600  
 Design Modification Rights Reserved  
 © Visa Lighting 2006

**INSTALLATION INSTRUCTIONS: CP**  
**Fixture family name: Pendants**

Description: FIELD INSTRUCTION FOR MOUNTING SWIVEL HANGER TO STANDARD JUNCTION BOX

Drawing : 760658XX  
 Rev: A

Sheet 1 of 1  
 Eng: CGA

Date drawn: 4/28/2006