

IES INDOOR REPORT
PHOTOMETRIC FILENAME : EBB-15-15LED.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] Photopia 2015.0.1
[TESTLAB] TMS LIGHTING INC.
[ISSUE DATE] June 9, 2016
[TEST DATE] June 9, 2016
[MANUFAC] TMS LIGHTING INC.
[LUMCAT] EBBY PENDANT
[MORE] ALUMINUM RLM REFLECTOR 15.5 IN. DIA.
[MORE] INNER SURFACE FINISHED WITH WHITE POLYESTER POWDER COAT
[LUMINAIRE] EBB-15-15LED
[LAMP] 15W LED, OPTIC
[LAMPCAT] XP-G2

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1127
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	65
Total Luminaire Watts	17.25
Ballast Factor	1.00
CIE Type	Direct
Spacing Criteria (0-180)	0.78
Spacing Criteria (90-270)	0.78
Spacing Criteria (Diagonal)	0.96
Basic Luminous Shape	Circular
Luminous Length (0-180)	1.29 ft (Diameter)
Luminous Width (90-270)	1.29 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	3043	2651	2502
55	1164	1030	1135
65	334	356	400
75	9	13	13
85	8	13	7

IES INDOOR REPORT
PHOTOMETRIC FILENAME : EBB-15-15LED.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-30	579.01	N.A.	51.40
0-40	850.58	N.A.	75.50
0-60	1106.32	N.A.	98.20
0-90	1126.98	N.A.	100.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
0-180	1126.98	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	88.31
10-20	212.30
20-30	278.41
30-40	271.56
40-50	182.77
50-60	72.98
60-70	18.19
70-80	2.36
80-90	0.10
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : EBB-15-15LED.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	109	107	104	110	107	105	102	103	101	99	99	98	96	96	95	93	92
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83
3	99	92	86	81	97	90	85	81	87	83	79	85	81	78	83	79	77	75
4	93	84	78	73	91	83	77	72	81	75	71	79	74	70	77	73	70	68
5	87	77	71	66	85	76	70	65	75	69	65	73	68	64	71	67	63	62
6	82	72	65	60	80	71	64	59	69	63	59	68	62	58	66	62	58	56
7	77	66	59	54	76	66	59	54	64	58	54	63	58	54	62	57	53	52
8	73	62	55	50	71	61	54	50	60	54	50	59	53	49	58	53	49	48
9	68	57	51	46	67	57	50	46	56	50	46	55	50	46	54	49	45	44
10	65	54	47	43	64	53	47	43	52	47	43	52	46	42	51	46	42	41

POLAR GRAPH



Maximum Candela = 1065.04 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (90 - 270)
2 - Vertical Plane Through Horizontal Angles (0 - 180)