





FEATURES

- Edge Effects combines the classic beauty of milled wood trim with rubber wall base for ease of installation and superior performance.
- Edge Effects sculptured wall base offers rich architectural detail in high-quality rubber and provides for flexible application to wall, corners and columns. Constructed of co-extruded thermoplastic rubber Type TP, in 15 profiles including chair rail and quarter-round for ultimate design flexibility.
- Made in the USA

Edge Effects is more economical than traditional wood trim. Available in continuous rolls saving installation time and money. Once installed, it has lower maintenance cost than natural wood and delivers superior lifecycle value.





- PRE-MITERED INSIDE AND OUTSIDE CORNERS ARE
 AVAILABLE TO MATCH VARIOUS WALL BASE HEIGHTS.
 OUR PRE-MITERED CORNERS ELIMINATES STEPS AND
 TIME REQUIRED TO FINISH A JOB.
- NO PRIMING, PAINTING, CAULKING OR MITER SAW
 REQUIRED. PRE-MITERED CORNERS GIVES A UNIFORM
 FINISHED APPEARANCE.

PERFORMANCE AND FEATURES

<u></u>	AVAILABLE SIZES	12', 25', 36', 50' - Profile dependent
WARRANTY 5 YEAR	WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty.

SUSTAINABILITY

BETTER PLANTS U.S. DEPARTMENT OF ENERGY	ENERGY LEADERSHIP	With one of the largest solar arrays in the flooring industry (3.3 acres in Salem NJ) and ambitious goals to improve energy efficiency by 25% over ten years, we have an ongoing partnership with the Department of Energy to lead manufacturing into smarter energy use, as well as to reduce related carbon emissions.
•	WATER REDUCTION	Water is a precious natural resource and a key component in manufacturing. By investing in technology and a continual emphasis on efficiency and lean manufacturing, we have reduced our water use by more than 35% since 2007. We also actively help protect wetlands in the communities where we make flooring.
USA	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in eight communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	3RD PARTY CERTIFICATIONS	Certifications help navigate the world of green marketing claims. So we invest in ISO-14001 and environmentally preferable product certifications including FloorScore and Green Label Plus. All of our products may contribute to multiple LEED and Green Globe credits.
<u> </u>	PURPLE MARTINS	In the mid-1980s, we began attracting migrating birds called Purple Martins to our New Jersey manufacturing campus as a more natural alternative to the use of pesticides. This "Purple Martin Project" has proven to be an incredibly environmentally friendly and cost effective way to control insects. Our employees are engaged in the banding and tracking of the birds.
	SOLAR ARRAY	At 3.3 acres, we have one of the largest solar arrays in the flooring industry generating 1,000,000 kilowatt hours annually.



HONEYBEES

In 2009, as part of an effort to show how an industrial enterprise can co-exist with the agricultural & farming community and positively contribute to both, Mannington's New Jersey corporate site began to house honeybees, and now have 5 hives in Salem, NJ and 4 in Eustis, FL. The honeybees are thriving and each year we are able to enjoy and share the honey we produce.



RECYCLED CONTENT

We actively seek out waste streams that clog America's landfills, looking for innovative ways to use them in new products. On average, 15 tons per month of drywall, the construction industry's largest waste stream, finds new life in our VCT products. We also reclaim post-consumer carpet and tile from other flooring companies, as well as tires, telephone books, automotive glass, and other waste streams that contribute to landfills, incorporating them into carpet and hard surface flooring.



CLIMATE REGISTRY

Mannington is dedicated to reducing our greenhouse gas emissions by 25% over 10 years. Since 2007, a 10% reduction can be attributed to energy efficiencies, process efficiencies, and use of renewable energy. Additional information can be found on the climater egistry.org.







SPECIFICATIONS

Ø _o	CONSTRUCTION	Co-Extruded Thermoplastic Rubber, Type TP
<u></u>	AVAILABLE SIZES	12' (3.65 m), 25' (7.62 m), 36' (11 m), 50' (15.24 m) Profile dependent
x	OVERALL THICKNESS	3/16" (4.76 mm), 1/4" (6.35 mm), 5/16" (7.94 mm), 3/8" (9.52 mm), 1/2" (12.7 mm) Profile dependent
	PACKAGE COUNT	1 per carton
Ō	AVERAGE WEIGHT	23-48 lbs (10.43-21.80 kgs) per carton Profile dependent
	3RD PARTY CERTIFICATIONS	FloorScore
TO TO TO	LEED	Mannington Commercial products may contribute to multiple LEED credits.
MADE IN THE	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, Americanmade products.
WARRANTY 5 VEAR	WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty.
FINISH		Smooth Matte
CORNERS		Pre-mitered inside and outside corners
CORNERS PER CARTON		10
CORNER WEIGHT PER CARTON		5 - 7 lbs (2.27 kgs - 3.18 kgs) Profile dependent
SPECIFICATION (ASTM F-1861)		Type TP, Group 1
FLOORING RADIANT PANEL TEST (ASTM-E-648)		≥ .45 watts/cm², Passes - Class 1
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662)		< 450, Passes
INSTALLATION ADHESIVE		Mannington MR-101, Acrylic Wall Base Adhesive

Floor designs copyrighted by Mannington Mills, Inc 2014. For complete specifications, visit www.manningtoncommercial.com.





