

**PHYSICAL CONSTRUCTION**

Construction	Thermoplastic Rubber, Type TP Sculptured Wall Base
Finish	Smooth Matte Finish
Corners	Pre-Mitered Inside and Outside Corners

Profile	Cache 3"	Flair	Illusion	Cache 4 1/4"	Iconic
<b>Thickness</b>	3/8" (9.52 mm)	5/16" (7.94 mm)	3/8" (9.52 mm)	3/8" (9.52 mm)	3/8" (9.52 mm)
<b>Height</b>	3" (7.62 cm)	3" (7.62 cm)	3 1/4" (8.26 cm)	4 1/4" (10.8 cm)	4 1/4" (10.8 cm)
<b>Pieces per Carton</b>	1-50' (15.24 m) coiled	1-50' (15.24 m) coiled	1-36'(11 m) coiled	1-50'(15.24 m)coiled	1-50'(15.24 m) coiled
<b>Weight per Carton</b>	23 lbs (10.43 kgs)	23 lbs (10.43 kgs)	30 lbs (13.60 kgs)	37 lbs (16.80 kgs)	47 lbs (21.30 kgs)
<b>Corner Wt / Carton</b>	5 lbs (2.27 kgs)	5 lbs (2.27 kgs)	5 lbs (2.27 kgs)	6 lbs (2.73 kgs)	6 lbs (2.73 kgs)
<b>Corners / Carton</b>	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)
Profile	Marquee	Etched	Double Etched	Sophisticate	Simplicity
<b>Thickness</b>	3/8" (9.52 mm)	1/4" (6.35 mm)	1/4" (6.35 mm)	3/8" (9.52 mm)	5/16"(7.94 mm)
<b>Height</b>	4 1/4" (10.8 cm)	4 1/4" 10.8 cm)	4 1/4" (10.8 cm)	4 1/4" (10.8 cm)	4 1/2" (11.4 cm)
<b>Pieces per Carton</b>	1-50' (15.24 m) coiled	1-50' (15.24 m) coiled	1-50' (15.24 m) coiled	1-50' (15.24 m) coiled	1-36'(11 m) coiled
<b>Weight per Carton</b>	47 lbs (21.30 kgs)	45 lbs (20.40 kgs)	45 lbs (20.40 kgs)	48 lbs (21.80 kgs)	44 lbs (20.00 kgs)
<b>Corner Wt. / Carton</b>	6 lbs (2.73 kgs)	6 lbs (2.73 kgs)	6 lbs (2.73 kgs)	6 lbs (2.73 kgs)	7 lbs (3.18 kgs)
<b>Corners / Carton</b>	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)
Profile	Cetera	Regal	Elegance	Effectual-Chair Rail	Quarter-round
<b>Thickness</b>	5/16" (7.94 mm)	3/8" (9.52 mm)	3/16" (4.76 mm)	1/4" (6.35 mm)	1/2" (12.7 mm)
<b>Height</b>	4 1/2" (11.43 cm)	5 1/4" (13.3 cm)	6" (15.24 cm)	4" (10.2 cm)	1/2" (1.3 cm)
<b>Pieces per Carton</b>	1-36'(11 m) coiled	1-25'(7.62 m) coiled	1-36'(11 m) coiled	1 - 12'	1 - 12'
<b>Weight per Carton</b>	42 lbs (19 kgs)	42 lbs (19 kgs)	43 lbs (19.50 kgs)	46 lbs ( 20.87 kgs)	35 lbs (15.88 kgs)
<b>Corner Wt. / Carton</b>	5 lbs (2.27 kgs)	5 lbs (2.27 kgs)	5 lbs (2.27 kgs)	NA	NA
<b>Corners / Carton</b>	10 (20 pieces)	10 (20 pieces)	10 (20 pieces)	NA	NA

**ENVIRONMENTAL**

FloorScore Indoor Air Quality	SCS Certified
Manufacture Location	San Jose, CA USA

**TESTING**

ASTM Specification (F-1861)	Type TP, Group 1
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm <sup>2</sup> , Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 – Passes

**WARRANTY**

Warranty	Limited 5 Year Commercial Warranty
----------	------------------------------------

**INSTALLATION**

Installation Adhesive	Mannington MR-101 Acrylic Wall Base Adhesive
-----------------------	--

- In the spaces to receive rubber flooring and accessories, maintain a minimum temperature of 65° F (18° C) and a maximum temperature of 85° F (29°C) for at least 48 hours before, during, and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55° F (13° C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.