

Product Specifications
OPTIMUM EDGE 100™
Type TS Rubber Wall Base in 100 Foot Rolls

MANNINGTON
COMMERCIAL

PHYSICAL CONSTRUCTION

Construction	Thermoset Vulcanized Rubber, Type TS Wall Base in 100 Foot Rolls
Finish	PVC-Free Construction
Height / Size	Smooth Stain Luster
Corners	4" (101.6 mm) only
Overall Thickness	Coved Profile only
Pieces Per Carton	Specify jobsite wrapped corners only
Weight per Carton – 4"	1/8" (3.175 mm)
Color Availability	1 continious roll of 100 Linear Feet per carton
	Coved = 38 lbs.
	901 - Black, 902 - Deep Suede, 903 - Dark Chocolate, 904 – Bark, 905 –Pewter, 907 – Stone Gray, 911 - Sable, 913 - Mineral Gray, 918 – Flax and 933 - Sandrift

TESTING

ASTM Specification (F-1861)	Type TS, Group 1
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm², Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 – Passes
FloorScore Indoor Air Quality	SCS Certified

WARRANTY

Warranty	Limited Five Year Commercial Warranty
----------	---------------------------------------

INSTALLATION

Installation Adhesives	Mannington MR-101 Acrylic Wall Base Adhesive
------------------------	--

- Mannington Wall Base is not recommended in commercial areas that require static dissipation.
- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

Choices That Work

800 241 2262 manningtoncommercial.com

