

PHYSICAL CONSTRUCTION

Construction	Thermoset Vulcanized Rubber, Type TS Wall Base PVC-Free Construction
Finish	Smooth Stain Luster
Height / Size	2 ½" (63.5 mm) 4" (101.6 mm) 6" (152.4 mm) Coved or Toeless
Corners	Factory molded, specify jobsite wrapped or molded
Overall Thickness	1/8" (3.175 mm)
Pieces Per Carton	25 – 4' pieces = 100' per carton
Weight Per Carton – 2 ½" / 4" / 6"	Coved = 27 / 39 / 53 lbs Toeless = 24 / 39 / 50 lbs
Weight Per Carton – Corners	Coved = 3 / 4 / 7 lbs Toeless = 3 / 4 / 7 lbs

ENVIRONMENTAL

FloorScore Indoor Air Quality	SCS Certified
Manufacture Location	San Jose, CA USA

TESTING

ASTM Specification (F-1861)	Type TS, Group 1
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm², Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 – Passes

WARRANTY

Warranty	Limited Five Year Commercial Warranty
----------	---------------------------------------

INSTALLATION

Installation Adhesives	Mannington MR-101 Acrylic Wall Base Adhesive
------------------------	--

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.