

One of our most popular collections, **Ultraleather**° | **Promessa**° delivers the ultimate promise: performance and durability like no other. Featuring a pebbled texture paired with a subtle sheen, this offering is highlighted by a sizeable color palette. EPA-registered antimicrobial protection and a blended backcloth make **Promessa**° a resilient choice, ideal for a variety of high traffic settings and healthcare applications.

Additional attributes include:

- Leading durability (14+ weeks hydrolysis results)
- Exceptional wear resistance (over 400,000 Wyzenbeek cycles)
- Repellency to moisture and liquids
- Endurance to alcohol-based cleaners and disinfecting with 20% bleach/water solution

Emphasizing endless possibilities for creative applications, **Promessa**® delivers style & stamina in perfect symbiosis.







Ultraleather® | Promessa®

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface 65% Polyester, 35% Rayon Backing

Weight:

Approx. 12 oz. Per Square Yard Approx. 410 Grams Per Square Metre

Thickness:

Approx. 1.1 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)* BS 2543 / 180,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

14+ Weeks

ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:

ASTM D751

Tear Strength:

ASTM D2261

Breaking Strength:

ASTM D5034

Antimicrobial:

ASTM E2180

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Class 5 Wet & Dry

Flammability

F/R Rating:

- ASTM E84 (Adhered) Class A
- CA TB 117-2013 Pass
- FMVSS 302 & 95/28 Annex IV Pass
- NFPA 260 Class 1
- UFAC Class 1

Other Tests*:

- · ASTM E84 (Unadhered)
- BS 5852 PT 0,1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform well under these fire test conditions.

Earth Friendly

· GREENGUARD Certified

- Meets stringent chemical emission limits including hazardous VOCs (ex. Formaldehyde)
- Promotes healthier indoor air quality
- Contributes towards satisfying credits under LEED® and level®, BIFMA
- Compliant with Prop 65
- Less than 100 ppm of EPA-registered antimicrobial treatment
- No Triclocarban or Triclosan
- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No PFCs (Perfluorinated Chemicals)
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

For more information on our fabrics, cleaning and care instructions, please visit our website.



