



HETEROGENEOUS SHEET FLOORING

Marbled™ Safe-T Flooring

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. Proprietary Product: Heterogeneous slip resistant sheet floor coverings with aluminum granules, designed for safety and durability in commercial environments.
- 1.2. Recommended areas for use:
 - Education – Cafeteria, dining areas, corridors, lavatories, locker rooms (no spikes), ramps, showers, foyers, vestibules, and entryways
 - Offices –corridors, cafeterias, lavatories, foyers, vestibules, and entryways
 - Retail – Entryways and produce areas
 - Healthcare – Corridors, hydro physical therapy, patient corridors, ramps, and scrub rooms.
 - Hospitality – Around whirlpools, spas, and indoor pools, corridors, elevators, vending areas, foyers, vestibules, and entryways
 - Assisted Living – Corridors and lavatories

1.3. Manufacturer:

Tarkett	Phone:	(800) 899-8916
30000 Aurora Rd.		(440) 543-8916
Solon, Ohio 44139	Tech:	Ext 9297
Web: www.tarkettna.com	Samples:	Ext 9299
E-mail: info@johnsonite.com		

1.4. Proprietary Product Description:

- 1.4.1. Construction: Johnsonite's Marbled Safe-T features aluminum granules slip retardant particulate suspended evenly throughout the product thickness to offer superior slip resistance.

1.4.2. Styles:

- Specify MRBSFT-R (Marbled Safe-T Flooring)

1.4.3. Physical Characteristics:

- Overall thickness is 0.080" (2.0 mm)
- Packaging: Available in 6' 6" (2 m) wide and approximately 67' linear feet (20.4 m) per roll

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Sheet material meets ASTM F 1303, Type I, Grade 1, Class B performance sheet vinyl floorcovering with backing
- 2.2. Heat Stability by Color Change (ASTM F 1514): $\Delta E \leq 8$
- 2.3. Light Stability by Color Change (ASTM F 1515): $\Delta E \leq 8$
- 2.4. Electrostatic Propensity (EN 1815): < 2 kV
- 2.5. Anti Fungi and bacteria resistant
- 2.6. Static coefficient of friction (ASTM D 2047): > 0.6
- 2.7. Static Load Limit (ASTM F 970): Passes 175 psi requirement
- 2.8. Fire Performance (ASTM E648): Class 1 (Minimum 0.45 W/cm²)

3. INSTALLATION

See heterogeneous sheet flooring installation instructions for complete details.

3.1. Adhesives:

- Tarkett 925 Adhesive:
Coverage:
Porous Substrate: 250-300 sq. ft./gal.
Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive:
Approximate Coverage:
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- Tarkett RollSmart Adhesive:
Coverage: 350 - 400 sq. ft. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- Tarkett 901 SpraySmart Adhesive:
Coverage: 150 sq. ft. per. container

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Marbled Safe-T Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department

30000 Aurora Road, Solon, Ohio 44139

(800) 899-8916 ext 9297

Fax (440) 632-5643

email: info@johnsonite.com

www.tarkettna.com

