



### **Construction specifications**

Product	Vibe
Style #	7221
Fiber Content	XTI® nylon
Fiber Weight (tufted)	34 oz./Sq. Yd. (1153 g/m <sup>2</sup> )
Construction	Cut / Uncut
Dye Method	Beck Dyed
Gauge	1/8
Pattern Repeat	3/4"W x 1"L (1.905 cm x 2.54 cm)
Width	12' (3.66)
Pile Height	.344"/.250" (8.74 mm/ 6.35mm)
Total Weight	80 oz./Sq. Yd. (2713 g/m <sup>2</sup> )

### **Performance specifications**

Flammability Rating:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts / CM <sup>2</sup> Class 1.
Smoke Density:	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness	4.0 or better
Static Rating:	Less than 3.5 kV. Antistat warranted for the life of the carpet.
Warranty:	10 year wear warranty
Primary Backing	Woven Polypropylene
Secondary	Woven Polypropylene

Vibe meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Certification # GLP2950.

All Masland Designs are protected under the U. S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.