Product Specifications BASIC TEE -- ULTRABAC RE



PHYSICAL CONSTRUCTION:

CONSTRUCTION: Tip-Sheared Loop

(Non-Phthalate Construction)

FACE FIBER: Invista Antron Lumena Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent

Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment,

and a Fiber Modification Ratio of <1.5

DYE METHOD: Solution Dyed

 GAUGE:
 1/10

 STITCHES PER INCH:
 8.66

 PILE THICKNESS:
 .250 Inches

FINISHED WEIGHT: 34 Ounces Per Square Yard

DENSITY: Average Density = 4,896; Weight Density = 166,464

PRIMARY BACKING: 100% Synthetic

SECONDARY BACKING: UltraBac RE with Minimum 10% Recycled Content and Lifetime Warranty Standard

STANDARD SIZE: 12' Width PATTERN REPEAT: None

ENVIRONMENTAL:

RECYCLED CONTENT: Minimum 10% Post-Consumer Recycled Content by Total Product Weight*

MANUFACTURE LOCATION: Calhoun, Georgia 30701 USA

NSF / ANSI-140 CERTIFICATION: Platinum
CRI GREEN LABEL PLUS ID: GLP2278

WARRANTIES:

WARRANTY: Lifetime Limited Warranty, Covering Face Wear, Delamination, Tuft Bind,

Unraveling, and Static Protection

BLEACH RESISTANT WARRANTY: ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills

STAIN RESISTANT WARRANTY: XGUARD with 15 Year Limited Warranty Against Staining

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648): Class I (Direct Glue)

SMOKE CHAMBER (ASTM-E-662): Less than 450 (Flaming Mode)

METHENAMINE PILL TEST (ASTM D-2859): Passes

ELECTROSTATIC PROPENSITY (AATCC 134): Less than 3.0 KV

RECOMMENDED ADHESIVE:

MULTI-PURPOSE ADHESIVE: Mannington Ultra Adhesive

CRI GREEN LABEL PLUS ID: GLP70513

VOC LIMITS: Meets SCAQMD Rule #1168

BOND WARRANTY: 10 Year Limited Warranty When Used With Mannington UltraBac RE Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Most products contain a higher percentage of recycled content than the minimums listed above. Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.

