



Series C100

Photo-luminescent Exit Sign
High & Low Level • UL924 Listed

Project:

Type:

Catalog #:

By/Date:

Specification Features

Viewing Distance:	100 feet
Location Rating:	Wet location, indoor and outdoor.
Operating Life:	25+ years
Activation:	5 foot-candles of LED , fluorescent, metal halide or mercury vapor lighting.
Face plate:	Injected molded ABS.
Face Plate Colors:	Red, Black, Green.
Letter Color:	Photoluminescent Illuminating.
Directional:	Two (2) arrows included.
Mounting:	Wall, flag and ceiling.
Attachments:	T- Bar Bracket with ceiling or flag mount
Dimensions:	9.5" high x 17.25" wide. 13/64" depth
Features:	Non-electrical, non-radioactive, low profile, explosion proof, low maintenance, UV stable.
Warranty:	Limited lifetime warranty.
Green Attributes:	No power usage. No radioactivity. No hazardous materials.
Listings & Codes:	Minimal maintenance. Long life. Recyclable. Listed to UL924. Approved by California State Fire Marshal. Compliant to IBC, NFPA, IFC & UFC codes.

Active Safety's Series C100 photoluminescent exit signs are durable, architecturally attractive exit signs specified by leading architects and engineers for hotels, condos, schools, retail, offices, hospitals, parking garages, US military facilities and other locations conforming to the IBC, NFPA and UFC codes.

Non-electrical and non-radioactive, Active Safety Series C100 photoluminescent exit signs are a favorite with LEED® and other environmental focused projects.

Photoluminescent operation means there are no electrical connections to engineer, procure and install. Once located adjacent artificial source, Active Safety Series C100 photoluminescent exit signs will operate for 25+ years with only minimal maintenance - no lamps, batteries or radioactive tubes to ever replace or dispose of.

Ordering Format (example: C100 - S - WM - B)

SERIES	FACES	MOUNTING	FACE PLATE COLOR
C100	<u>S</u> - single <u>D</u> - double	<u>WM</u> – wall mount <u>CM</u> – ceiling or flag mount	<u>B</u> - Black <u>R</u> - Red <u>G</u> - Green

Specification Description

High [or Low Level] Exit Sign. UL 924 listed. Photoluminescent, non-electrical, non-radioactive, 100 foot visibility rating, 25+ year life. ABS plastic construction, arrows. Single and double sided face configurations consistent with ceiling, flag or wall mount applications specified on project drawings. Matching bracket for ceiling and flag mount applications. Directional arrows included.

