



the CITY

SPECIFICATION SHEET

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	120/277VAC
TOTAL POWER CONSUMPTION	610 WATTS
POWER FACTOR	0.99
TYPICAL CURRENT	5.08 AMPS @ 120V 2.2 AMPS @ 277V

LED CHARACTERISTICS

LED EMITTER TYPE	LUMILED'S
TOTAL NUMBER OF LEDS	154 LEDS
LED COLOR SPECTRUM	FULL SPECTRUM PROPRIETARY RED AND BLUE ENHANCED SPECTRAMAX® BLEND
LED OPTICS	INJECTION MOLDED OPTICS OPTIMIZED FOR CANOPY PENETRATION

LED DRIVER AND CONTROLS

LED DRIVER	ETL LISTED CONSTANT CURRENT DRIVER
LED CONTROLS	INTEGRATED WIFI CONNECTIVITY USING LIFTED LED APP (ANDROID AND IOS)

MOUNTING

MOUNTING SYSTEM	DUAL 2-POINT AIRCRAFT CABLE SUSPENDED MOUNT
-----------------	---

PERFORMANCE

PAR OUTPUT UMOLES/M ² /S AT CENTER	@ 12" = 1092
COVERAGE	20 sq Ft

DIMENSIONS AND WEIGHT

LENGTH X WIDTH X HEIGHT	18" x 18" x 4.5"
WEIGHT	37LBS

OPERATING REQUIREMENTS

OPERATING TEMPERATURE	0°- 40°C 32°-104°F
OPERATING POSITION	DOWN LIGHT ONLY

WARRANTY

LIMITED 3 YEAR WARRANTY

ORDERING LOGIC

CITY 610 WATT LED GROW LIGHT	CITY
------------------------------	------



LIFTED LED GROW LIGHTS - 505.600.1LED - www.LIFTEDLED.com