

Patty Madden Lumina

PERFORMANCE FABRIC

Lucent

62492 Peppercorn



© 2017 C.F. Stinson, LLC. All rights reserved.

Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Contains an antimicrobial agent
- Bleach-solution cleanable
- Enhanced fade resistance

Cleaning and Maintenance

Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Bleach solutions of up to 20% may be used for more difficult stains.

For additional cleaning information visit cfstinson.com

For complete specifications visit cfstinson.com

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications



Content	81% Solution Dyed Nylon, 19% Post-Consumer Recycled Polyester
Finish	GreenShield® patented, nano-particle based, reduced environmental impact soil and stain protection with an antimicrobial agent
Backing	Acrylic
Weight	16.5 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Repeat	Horizontal: 5.25 inches, Vertical: 52.25 inches, directional, non-match
Roll Size	55 yards

Performance Characteristics

Abrasion Resistance** ASTM D-4157	Exceeds 100,000 double rubs - heavy duty
Break Strength ASTM D-5034	Warp: 99 lbs. min., Fill: 100 lbs. min.
Brush Pilling ASTM D-3511	Class 5.0 min.
Colorfastness to Light AATCC-16	200 Hours, Class 5.0
Crocking AATCC-8	Dry: Class 4.0, Wet: Class 5.0
Antimicrobial	The Greenshield finish on this product features a antimicrobial agent which inhibits the growth of microbes on the protected surface.

Flammability*

California 191-53 Technical Bulletin 117, Section E	Passed
UFAC	Class 1
NFPA 260	Class 1
May contribute to compliance with California Technical Bulletin 133 when used in conjunction with other suitable components.	



Stinson®

C.F. Stinson, LLC
2849 Product Drive
Rochester Hills, MI 48309

P 800 841 6279
F 248 299 3884

cfstinson.com