

Sunburst  
61707 Peacock

PERFORMANCE FABRIC



© 2017 C.F. Stinson, LLC. All rights reserved.

Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Fluid barrier
- Contains an antimicrobial agent

Cleaning and Maintenance

Cleaning Code: **(W)** Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.

For additional cleaning information visit [cfstinson.com](http://cfstinson.com)

For complete specifications visit [cfstinson.com](http://cfstinson.com)

Dye lots may vary slightly.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Specifications



|         |  |
|---------|--|
| Content | 100% Post-Industrial Recycled Polyester Crypton Green      |
| Finish  | Crypton® Non-PFOA Soil & Stain Protection                  |
| Backing | Crypton® Fluid Barrier                                     |
| Weight  | 16.9 oz./lin. yd. ± 1.0 oz.                                |
| Width   | 54 inches  |
| Repeat  | Horizontal: 7.25 inches, Vertical: 7.0 inches, directional |

Performance Characteristics

|                                 |   |
|---------------------------------|---|
| Abrasion Resistance ASTM D-4157 | Exceeds 50,000 double rubs - heavy duty   |
| Break Strength ASTM D-5034      | Warp: 225 lbs. min., Fill: 275 lbs. min.  |
| Seam Slippage ASTM D-4034       | Warp: 60 lbs. min., Fill: 60 lbs. min.  |
| Brush Pilling ASTM D-3511       | Class 4.0 min.  |
| Colorfastness to Light AATCC-16 | 40 Hours, Class 4.0   |
| Crocking AATCC-8                | Dry: Class 4.0, Wet: Class 3.0  |
| Fluid Barrier                   | Crypton® Integrated Fluid Barrier   |
| Antimicrobial                   | Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface. |

Flammability\*

|   |              |
|---|--------------|
| California 191-53 Technical Bulletin 117, Section E | Passed       |
| UFAC  | Class 1      |
| NFPA 260  | Class 1      |
| ASTM E-84 (Unadhered)                               | Class A or 1 |

May contribute to compliance with California Technical Bulletin 133 when used in conjunction with other suitable components.



This product is produced using 100% recycled fiber.



Stinson®

C.F. Stinson, LLC  
2849 Product Drive  
Rochester Hills, MI 48309

P 800 841 6279  
F 248 299 3884

[cfstinson.com](http://cfstinson.com)