


Bistro

BT209 Grasshopper

VINYL SEATING



© 2017 C.F. Stinson, LLC. All rights reserved.

**Performance Summary**

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Fluid barrier
- Contains an antimicrobial agent
- Bleach-solution cleanable

**Cleaning and Maintenance**

Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Bleach solutions of up to 10% may be used for more difficult stains.

For additional cleaning information visit [cfstinson.com](http://cfstinson.com)

For complete specifications visit [cfstinson.com](http://cfstinson.com)

Dye lots may vary slightly.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

**Specifications**

Content	Vinyl Surface with Polyester Backing
Finish	Advanced Soil and Stain Resistant Top Coat
Backing	Polyester
Weight	26 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Roll Size	35 yards

**Performance Characteristics**

Abrasion Resistance** CFFA-1	Exceeds 250,000 double rubs - heavy duty
Break Strength CFFA-17	Warp: 85 lbs. min., Fill: 60 lbs. min.
Tear Strength CFFA-16	Warp: 12 lbs. min., Fill: 12 lbs. min.
Seam Slippage CFFA-14	Warp: 50 lbs. min., Fill: 25 lbs. min.
Crocking CFFA-7	Dry: Class 4.0, Wet: Class 3.0
Fluid Barrier	Inherent Fluid Barrier
Antimicrobial	This product features an antimicrobial agent which inhibits the growth of microbes on the protected surface.

**Flammability\***

California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1
MVSS 302	Passed
BIFMA	Class 1
May contribute to compliance with California Technical Bulletin 133 when used in conjunction with other suitable components.	



# Stinson®

C.F. Stinson, LLC  
2849 Product Drive  
Rochester Hills, MI 48309

P 800 841 6279  
F 248 299 3884

[cfstinson.com](http://cfstinson.com)