Burkshire

BRK85 Teal

VINYL SEATING

© 2017 C.F. Stinson, LLC. All rights reserved.

Stinson®

Burkshire

VINYL SEATING

Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Fluid barrier
- Contains an antimicrobial agent
- Bleach-solution cleanable

Cleaning and Maintenance

Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Bleach solutions of up to 10% may be used for more difficult stains.

For additional cleaning information visit cfstinson.com

For complete specifications visit cfstinson.com

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications	
Content	Vinyl Surface with Polyester / Cotton Backing
Finish	Advanced BeautyGard® soil and stain protection
Backing	Polyester / Cotton
Weight	37 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Roll Size	30 yards
Performance Characteristics	
Abrasion Resistance** Wyzenbeek	Exceeds 250,000 double rubs - heavy duty
Break Strength ASTM D-751-89	Warp: 65 lbs. min., Fill: 60 lbs. min.
Tear Strength ASTM D-1117-80	Warp: 14 lbs. min., Fill: 12 lbs. min.
Fluid Barrier	Inherent Fluid Barrier
Antimicrobial	This product features an antimicrobial agent which inhibits the growth of microbes on the protected surface.
Flammability*	
California 191-53 Technical Bulletin 117, Section E	Passed
NY / NJ Port Authority (FTMS 191-5903)	Passed
Boston Fire Code BFD 1X-1	Passed
FAA 25.853 (b)	Passed
Federal Specification CID A-A-2950	Passed
MVSS 302	Passed
BIFMA	Class 1
	May contribute to compliance with California Technical Bulletin 133 when used in conjunction with other suitable components.

GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

Stinson®

C.F. Stinson, LLC
2849 Product Drive
Rochester Hills, MI 48309

P 800 841 6279
F 248 299 3884

cfstinson.com