



© 2017 C.F. Stinson, LLC. All rights reserved.

Performance Summary

- Enhanced abrasion resistance
- Fluid barrier

Cleaning and Maintenance

Cleaning Code: **(W)** Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.

For additional cleaning information visit cfstinson.com

For complete specifications visit cfstinson.com

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications

Content	Static Dissipative Surface with Polyester Backing
Backing	Polyester
Weight	32.25 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Roll Size	50 yards

Performance Characteristics

Abrasion Resistance** ASTM D-3597	Exceeds 100,000 double rubs -
Break Strength CFFA-17	Warp: 78 lbs. min., Fill: 80 lbs. min.
Fluid Barrier	Inherent Fluid Barrier

Flammability*

California Technical Bulletin 117-2013 Section 1	Passed
MVSS 302	Passed
May contribute to compliance with California Technical Bulletin 133 when used in conjunction with other suitable components.	



Stinson®

C.F. Stinson, LLC
2849 Product Drive
Rochester Hills, MI 48309

P 800 841 6279
F 248 299 3884

cfstinson.com