

© 2017 C.F. Stinson, LLC. All rights reserved.

Performance Summary

Cleaning and Maintenance


Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

For additional cleaning information visit cfstinson.com

For complete specifications visit cfstinson.com

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Specifications		☼🌱🔥★🎯
Content	52% Post-Industrial Recycled Polyester, 48% Post-Consumer Recycled Polyester	
Backing	None	
Weight	11.5 oz./lin. yd. ± 1.0 oz.	
Width	66 inches	
Roll Size	60 yards	
Performance Characteristics		
Break Strength ASTM D-5034	Warp: 100 lbs. min., Fill: 125 lbs. min.	
Tear Strength ASTM D-2261	Warp: 25 lbs. min., Fill: 25 lbs. min.	
Moisture Regain ASTM D-2654	1.0% maximum	
Colorfastness to Light AATCC-16	40 Hours, Class 4.0	
Crocking AATCC-8	Dry: Class 4.0, Wet: Class 3.0	
Flammability*		
ASTM E-84 (Unadhered)	Class A or 1	
	This product is produced using 100% recycled fiber.	



Ally is an Underwriters Laboratory Recognized Component. Additional testing is not required on approved panel systems from participating manufacturers or remanufacturers.

