

SPECIFICATIONS - COLOR ANCHOR COLLECTION

| | | |
|--|---|---|
|  | CONSTRUCTION | LVT with micro-beveled edges |
|  | AVAILABLE SIZES | 6" x 36" (152 mm x 915 mm), 12" x 24" (305 mm x 610 mm), 18" x 18" (457 mm x 457 mm) |
|  | WEAR LAYER THICKNESS | 20 mil (0.51 mm) |
|  | OVERALL THICKNESS | .098" (2.5 mm) |
|  | PIECES PER CARTON | 19 pieces - 6" x 36"; 18 pieces - 12" x 24"; 12 pieces - 18" x 18" |
|  | COVERAGE PER CARTON | 28.5 sq. ft. - 6" x 36"; 36 sq. ft. - 12" x 24"; 27 sq. ft. - 18" x 18" |
|  | QUANTUM GUARD® HP | The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention and slip resistance when compared to standard LVT - resulting in 70% annual savings in maintenance costs. |
|  | QUICKSTIX® | LVT with pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix floors can be used immediately after installation, even in extreme moisture areas. |
|  | WARRANTY | This product is backed by our Limited 10 Year Commercial Warranty and Limited 10 Year Quantum Guard® HP Wear Warranty. |
|  | RAPIDLY RENEWABLE CONTENT | Contains 3% rapidly renewable resource content. |
|  | 3RD PARTY CERTIFICATIONS | FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration) |
|  | LEED | Mannington Commercial products may contribute to multiple LEED credits. |
|  | US MANUFACTURING | Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products. |
| | STATIC LOAD LIMIT | 750 PSI |
| | SPECIFICATIONS (ASTM F1700) | Class III, Type B |
| | HEAT STABILITY (ASTM F1514) | Passes |
| | STAIN & CHEMICAL RESISTANCE (ASTM F925) | Passes |
| | HUD/FHA REQUIREMENTS | Exceeds |
| | AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG) | Meets or exceeds ADA Guidelines |
| | COEFFICIENT OF FRICTION (COF) | ≥ 0.5 Leather; 0.6 Rubber |
| | FLOORING RADIANT PANEL (ASTM E648) | ≥ 0.45 watts/cm ² , Passes (Class 1) |
| | N.B.S. SMOKE CHAMBER (ASTM E662) | < 450-Passes |
| | INSTALLATION ADHESIVE | Porous Substrate: V-82 Full Spread / RH 75%, MVER 3. Non-Porous Substrate: V-95 Full Spread, 2 Part Epoxy / RH 75%, MVER 3. Porous & Non-Porous Substrate: M-Guard V-88 Full Spread, Transitional Pressure Sensitive / RH 90%, MVER 8; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH 11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH 12; QuickStix® pre-applied adhesive / 99% RH, MVER 18, pH 12. Note: Must use V-95 or XpressStep for LVT or Premium Spray adhesive under hospital beds and heavy rolling loads or where high performance is needed. |

For complete specifications, visit our website, manningtoncommercial.com.



MANNINGTON
COMMERCIAL