

**Product Specifications**  
**SAVVY -- INFINITY MODULAR (40 Square Yard Minimum)**

**MANNINGTON**  
COMMERCIAL

**PHYSICAL CONSTRUCTION:**

|                      |  |
|----------------------|--|
| CONSTRUCTION:        | Tip Sheared Patterned Loop<br>(Non-Ortho Phthalate Construction)                     |
| FACE FIBER:          | Ultron Type 6,6 Nylon, with Patented Mixed Denier / Mixed Cross Section Fiber Design |
| DYE METHOD:          | Piece  |
| GAUGE:               | 5/64   |
| STITCHES PER INCH:   | 11   |
| PILE THICKNESS:      | .168 Inches  |
| TUFTED YARN WEIGHT:  | 28 Ounces Per Square Yard  |
| DENSITY:             | Average Density = 6,000; Weight Density = 168,000                                    |
| PRIMARY BACKING:     | 100% Synthetic   |
| SECONDARY BACKING:   | Infinity Modular Reinforced Composite Closed Cell Polymer                            |
| STANDARD SIZE:       | 24" X 24" Modular Tiles  |
| INSTALLATION METHOD: | Monolithic   |

**ENVIRONMENTAL:**

|   |   |
|---|---|
| RECYCLED CONTENT:   | Contains Pre-Consumer Recycled Content* |
| MANUFACTURE LOCATION:   | Calhoun, Georgia 30701 USA              |
| NSF / ANSI-140 CERTIFICATION:                                 | Gold                                    |
| CRI GREEN LABEL PLUS ID:                                      | GLP1024                                 |
| 3 <sup>rd</sup> Party Certified Product Specific Type III EPD |   |

**WARRANTIES:**

|                           |  |
|---------------------------|--|
| WARRANTY:                 | Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection |
| STAIN RESISTANT WARRANTY: | XGUARD with 15 Year Limited Warranty Against Staining  |

**PRODUCT TESTING:**

|                                       |                              |
|---------------------------------------|------------------------------|
| RADIANT PANEL (ASTM E-648):           | Class I (Direct Glue)        |
| SMOKE CHAMBER (ASTM E-662):           | Less than 450 (Flaming Mode) |
| METHENAMINE PILL TEST (ASTM D-2859):  | Passes                       |
| DIMENSIONAL STABILTY AACHEN TEST:     | Passes                       |
| ELECTROSTATIC PROPENSITY (AATCC 134): | Less than 3.0 KV             |

**RECOMMENDED ADHESIVE:**

|                          |  |
|--------------------------|--|
| RELEASEABLE ADHESIVE:    | Mannington Infinity Pressure Sensitive Adhesive            |
| CRI GREEN LABEL PLUS ID: | GLP70522   |
| VOC LIMITS:              | Meets SCAQMD Rule #1168                                    |
| BOND WARRANTY:           | Lifetime Limited Warranty When Used With Mannington Carpet |

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

\* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.

**Choices That Work**

800 241 2262 manningtoncommercial.com