



Construction specifications

| | |
|-----------------------|---|
| Product | Verve |
| Style # | 7811 |
| Fiber Content | Masland Solution Dyed nylon |
| Fiber Weight (tufted) | 32 oz./Sq. Yd. (1085 g/m ²) |
| Construction | Tip Sheared Loop Pattern |
| Dye Method | Solution Dyed |
| Gauge | 1/10 |
| Pattern Repeat | 3/4"W x 3/4"L (1.905cm x 1.905cm) |
| Width | 12' (3.66) |
| Pile Height | .250" (6.35mm) |
| Total Weight | 78 oz./Sq. Yd. (2644 g/m ²) |

Performance specifications

| | |
|----------------------|--|
| Flammability Rating: | Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts / CM ² Class 1. |
| Smoke Density: | Passes NBS Smoke Chamber Test ASTM E-662 |
| Colorfastness | 4.0 or better |
| Static Rating: | Less than 3.5 kV. Antistat warranted for the life of the carpet. |
| Warranty: | 10 year wear warranty |
| Primary Backing | Woven Polypropylene |
| Secondary | Woven Polypropylene |

Tufted fiber weight denotes specs prior to tip shearing. Tip Shearing removes a small amount of fiber, which will vary slightly by product and production run.

Verve meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Certification # GLP1678.

All Masland Designs are protected under the U. S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.