

# SHEETROCK® Brand Patching Plaster

<b>Surface Preparation</b>	Surface should be free of all foreign material, dust, dirt and grease. Use a screwdriver to open narrow cracks to at least 1/4" wide. Dampen surface using sponge.
<b>Mixing</b>	Use clean water and equipment. Mix approximately two parts powder into one part water. Stir thoroughly; do not overthin. Mix only as much material as you can use within 60 minutes.
<b>Application</b>	<p>Pack patching plaster into crack or damaged area. Finish flush with surface.</p> <p>For cracks over 1/8" wide or 1/4" deep, apply a first coat to within 1/4" of surface. Allow to set 30 minutes. Apply additional material until patch is flush with surface. Texture to match surrounding area. Allow patch to dry completely before decorating.</p> <p>Sand area using fine-grade sandpaper. You may now decorate repaired area.</p>
<b>Decorating</b>	Interior walls may be painted or wallpapered as desired.
<b>Cleanup</b>	Clean tools and containers with soap and water immediately after use.

**Trademarks**

The following trademarks used herein are owned by United States Gypsum Company or a related company: SHEETROCK, USG.

**Note**

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

**Notice**

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than their intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

**SAFETY FIRST!**

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

