

**Model** 1924E - Snowball 3, Midsize Hip Chair

**Dimensions**

Seat Height	24.0	Depth	31.0
Seat Width	22.0	Width	24.0
Overall Height	38.5	Arm Height	32.0

**COM Yardage**

Based on pattern repeats less than 5 in. x 5 in.

Unit	0.75
Seat Yardage	0.75
Stacking	No

**Options:**

Wall saving	No
Connected	No
Tablet	No
CAL 133	Yes
Dolly	No
DuraSpec Seat	Yes



**Frame construction**

Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal.

**Seat**

The upholstered seat foundation is made with 100% recycled plastic with upholstery covers form fitted and stapled over 1 inch thick hi-resiliency polyurethane molded foam. The 100% recycled plastic platform covers the staples, making the seat easy to clean and provides for a smooth surface when stacking (stacking not available on Sled base).

**Back**

The maple back is comprised of a minimum of 6 layers of plywood, pressed into a 0.4 in.thick back, with an outer layer of maple veneer front and back. The back can be machined with one of the standard 5 designs or with a custom logo.

**Foam**

Open cell cut foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 1.8 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

**Flame retardancy**

Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

**Arms**

The arm is constructed from molded nylon.

**Glides**

Frame feet are finished with durable injection molded plastic glides.

**Load Test**

Exceeds BIFMA Seating Durability Test to 500 lbs

**Wood Finish**

Wood components are stained using custom made water based stains. They are then sealed and finished using a state of the art water based UV finish. The wood is hand sprayed and then allowed to air dry and then finally cured using our new UV tunnel. All wood components get 2 coats of our water based UV finish. This leading edge UV tunnel is very unique in that it allows Spec to finish complex shapes like wood arms and seat backs not normally curable by other UV tunnels. The UV curing process involves the use of high intensity Ultra-violet lights.