



Product Specifications

Construction	Tip-Sheared Loop
Backing	Woven Polypropylene (standard backing)
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	34 oz./sy (1153 grams/m2)
Pile Density	8559 oz./y3 (317.37 kg/m3)
Pattern Repeat	1.80" (w) x 2.13" (l) approx. (4.57cm x 5.41cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	14 stitches/in (5.51 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Encore SD Ultima Fiber
Optional Warranties	TitanBac Plus Endure Plus

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional


Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	25%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



BND01 Sandoval



BND02 Yellowstone



BND03 Ponderosa



BND04 Copper Ca...



BND05 Bitter Creek



BND06 Hawk Spri...



BND07 Sierra Mesa



BND08 Medicine B...




BND09 Great Divide




BND10 Paradise H...



BND11 Eagle's Ne...



BND12 Sweetwater



BND13 Black Mou...