



Product Specifications

|                     |                                                                    |
|---------------------|--------------------------------------------------------------------|
| Construction        | Textured Loop                                                      |
| Backing             | Woven Polypropylene (standard backing)                             |
| Dye Method          | Solution Dyed                                                      |
| Nylon Fiber Type    | Encore <sup>®</sup> SD Ultima <sup>®</sup> (with recycled content) |
| Face Weight         | 24 oz./sy (814 grams/m2)                                           |
| Pile Density        | 7200 oz./y3 (266.98 kg/m3)                                         |
| Pattern Repeat      | .20" (w) x .75" (l) approx. (.51cm x 1.91cm)                       |
| Gauge               | 1/8 (3.15 rows/cm)                                                 |
| Stitches Per Inch   | 8 stitches/in (3.15 stitches/cm)                                   |
| Standard Width      | 12 ft 3.66 m                                                       |
| Standard Adhesive   | Commercialon Premium Carpet Adhesive                               |
| Standard Warranties | Encore SD Ultima Fiber                                             |
| Optional Warranties | TitanBac Plus<br>Endure Plus                                       |

Special Technologies

|                                    |          |
|------------------------------------|----------|
| ProSept <sup>®</sup> Antimicrobial | Optional |
| ProTex <sup>®</sup> Soil Release   | Standard |
| Sentir <sup>®</sup> Odor-Blocker   | Optional |

Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | N/A Certified                      |
| Total Recycled Content | 25%                                |
| Flooring Radiant Panel | Class 1                            |
| Smoke Density          | Less than 450 flaming (ASTM E 662) |
| Static Test            | Less than 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |

Colorways



RHR01 News Radio



RHR02 Mass Tran...



RHR03 Limited Ac...



RHR04 Fast Lane



RHR05 Gridlock



RHR06 Merging Tra...