
**LOCKS** 





## SHEET METAL MINI CAM LOCK


## **NAL-S**














• 90 degrees cam rotation.

request.(Special order)

pointing upwards when locked. \* Not suitable for compression latch situation. \* Pressure to cam may cause damage to cylinder.

positions.

NAL-S-1



NAL-S-2

· Mini zinc alloy cylinder cam lock for sheet metal doors.

Keyed alike only. Keyed differently type available upon

\* Cam should be horizontal when unlocked, and should be

 Cam is reversible.
 NAL-S-1: Key withdrawals in locked position only. (Key works as a knob in unlocked position.)

NAL-S-2: Key withdrawals in both locked and unlocked

> \*Turn the cam (3) over to use NAL-S as a

counterclockwise turn lock. One Slot Type Two Slot Type

No.	Part Name	Material	Finish
1	Body	Zinc Alloy	Chrome
2	Hex Nut		Chromate
3	Cam	Steel	Chrome
4	Screw	Steel	Chromate
(5)	Key		Chrome
6	Key Ring	304 Stainless Steel	Plain


Item No.	Number of Slot (s)	Cylinder Diameter	Key Changes	Keys Included	Weight (g)	Box (pcs)	Carton (pcs)
NAL-S-1	1	12 (1/2") / Width 10.7 (7/16")	100	2	25	100	500
NAL-S-2	2	12 (1/2") / Width 10.7 (7/16")	100				

## SHEET METAL CAM LOCK


## NAL




- · Brass cylinder tubular cam lock for sheet metal doors.
- 90 degree cam rotation.
- Key is removable in locked position only. (Key acts as a knob in un-locked position.)
- · Please specify key No. or combination when ordering if necessary.
- 5,000 key changes available; Please specify keyed alike or differently when ordering.



Installation





No.	Part Name	Material	Finish		
1	Body	Brass	Chrome		
2	Key	Steel	Nickel		
3	Cam		Yellow Zinc Chromate		
4	Hex Nut	Brass			
(5)	I ICA INUL				

Item No.	Door Thickness (mm)	Cylinder Diameter	Key Changes	Keys Included	Weight (g)	Box (pcs)	Carton (pcs)
NAL	Max.10 ( 3/8" )	19 ( 3/4" )/Width 15.8 ( 5/8" )	5000	2	55	100	300

(5) Key works as a knob in unlocked position.