January 3, 2011 Updated October 10, 2018 800-424-2432







DataLink® Table Svs	tem General Information	2
	Fixed Leg Tables/Power	4
	Fixed Leg Tables/No Power	6
	Fixed Leg Tables/Power	8
	Fixed Leg Tables/No Power	10
	Wedges	12
	Non-Electrical Accessories	14
	Electrical Accessories	16
Activ8® System		20
	0 116	
Flat Screen Garage®	General Information	26
Smart Lift®		28
Flat Screen Garage®	Worksurface - Poly Grommet/PowerUp	30
	Worksurface - Villa Metal Grommet/Power Module	32
Smart Lift®	Worksurfaces - Poly Grommet/PowerUp	34
	Worksurfaces - Villa Metal Grommet/Power Module	38
	Accessories	42
Flat Screen Garage®	10-Wire/6 Circuit Beams	44
	Non-Powered Beams	48
	"C" Legs	50
	Electrical	52
	Rectangular Privacy Screens	56
	Stand Alone Privacy Screen	58
	Divider Screens	60
InTandem® Table Sys	stem General Information	64
	Worksurfaces - Poly Grommet/PowerUp	66
	Worksurfaces - Villa Metal Grommet/Power Module	74
	End-of-Run/Stand Alone Beams	82
	Middle Beams	90
	Corner Middle Beams	98
	Legs and CPU Clamps	102
	Freestanding Frames with Casters	104
	Electrical	108
Activ8® System		114
InTandem® Table Sys		
	Rectangular Privacy Screens	120
	Stand Alone Privacy Screens	122
	Corner Privacy Screens	124
	Divider Screens	126
	Rectangular Curved Privacy Screens	130
	Stand Alone Curved Privacy Screen	132
	Corner Curved Privacy Screen	134
	Curved Divider Screens	136
Wharton™ Lectern	General Information	140
Index		144

DataLink® Table System

General Information







Classroom Configuration



U-Shaped Configuration

Features			
Fixed leg	•	•	•
10-wire/6-circuit power option	•	•	•
Data/communication option	•	•	•
Rectangular worksurfaces	•	•	•
Wedge-shaped worksurfaces for radiused configurations	•	•	•
"Laid-in" wiring	•	•	•
Door-for-leg wireway	•	•	•
Metal separation of power and data wires	•	•	•
Ganging	•	•	•
Modular data connection option	•	•	•
Five edge styles	•	•	•



Power Distribution Unit (Rigid Wireway)



Dual Channel Leg Wireway (Laid-in Wiring)



Wire Manager Door



Ganger



PowerUp® Module

SPECIFICATIONS

Worksurfaces

Worksurface tops are 1-1/4" nominal overall thickness with .042" thick high-pressure laminate and .030" thick backer. Density is 45 lbs/ft³, M3 grade.

Edge Style

There are 5 choices of edge styles available: (74P); Flat Vinyl T-edge (BN); Urethane (ME); Postformed (PL); and 3/8" Wood Band Edge (34S). The BN and PL edges are not available on wedge worksurfaces. 34S edge is standard in Natural Red Oak.

Fixed Base Worksurfaces

Worksurfaces for fixed base tables have a solid 45 lb/ft³ particleboard core construction. PowerUp® Module, Activ8® or grommet locations will be available along the back edge of the worksurface away from the user in either the right- or left-hand corners, both corners or center.

Wedge Worksurfaces

Wedge worksurfaces have a solid particleboard core construction. PowerUp® Module, Activ8® or grommet locations are not available. The wedge is supported between two tables by four 1-1/2" x 3/4" rectangular metal splice tubes. Four nylon gangers are also used to draw the wedge up to each table and keep the splice tubes from disengaging.

Leg Assemblies

The leg assembly is made up of a 24" or 30" foot, leg upright with access door, fixed leg. The feet and the cantilevers are die cast aluminum and the leg and access door are extruded aluminum. The feet each have two nylon glides that attach to the foot via 5/16" diameter x 7/8" long threaded studs. The leg contains a 1" x 2-1/2" wireway that directs wires from the foot into the horizontal wire manager. The leg wireway is divided into two halves that keep data cables separate from electrical cables. The leg wireway also has an aluminum access door that hinges on two steel dowel pins and snaps shut via a nylon

snap. The cantilever attaches the leg assembly to the worksurface via raised bosses that provide 3/4" of clearance between the cantilever and the bottom of the worksurface, allowing a space to pass cables from table to table. The raised bosses on the cantilever also serve as mounting studs for the nylon table gangers that hold tables/wedges together. Each table has one right leg and one left leg assembly. The leg assemblies are available in three standard heights: 27", 29" & 32". The leg assemblies are held together by two 1/4" diameter draw bolts that clamp the assembly together. The legs are available in standard powder coat finishes. Fixed leg tables ship knocked down.

DataLink® Table System General Information



INFORMATION

WarrantyRefer to KI Terms & Conditions document or visit ki.com

DataLink® Table System

Fixed Leg Tables/Power

			MODEL NUM	RFR						
			MODEL NOM							
	Features	D x W x H	Basic Model/ Power Option	Edge Style	Grommet/ Module Location	Grommet/ Module Color	Base Finish	Surface Finish	Edge Color	Approx. Packaged Weight
	Power	24 x 36 x 27	DX243627-T6							63.0#
	Power	24 x 36 x 29	DX243629-T6							63.0#
	Power	24 x 36 x 32	DX243632-T6							63.0#
	Power	24 x 42 x 27	DX244227-T6							70.0#
	Power	24 x 42 x 29	DX244229-T6							70.0#
DLFX	Power	24 x 42 x 32	DX244232-T6							70.0#
Fixed Leg Table, 24"D	Power	24 x 48 x 27	DX244827-T6							77.0#
Available with or without a 10-	Power	24 x 48 x 29	DX244829-T6							77.0#
wire/6- circuit power distribution unit	Power	24 x 48 x 32	DX244832-T6							77.0#
("Power Option")	Power	24 x 60 x 27	DX246027-T6							88.0#
Duplex receptacles, infeeds, and "Barray Cather"	Power	24 x 60 x 29	DX246029-T6							88.0#
jumpers for the "Power Option" must be ordered separately	Power	24 x 60 x 32	DX246032-T6							89.0#
Wire trough assembly is standard on	Power	24 x 72 x 27	DX247227-T6							100.0#
all tables	Power	24 x 72 x 29	DX247229-T6							100.0#
 Data ports located in the modesty panel are standard. Data jacks are 	Power	24 x 72 x 32	DX247232-T6							101.0#
supplied by the customer										
 Includes ganger 										
See Activ8® Single Circuit Electrical										
System to order modules										
			Ø	3	•	0	3	•	Ф	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model/power option. T6 = Power

BSelect edge style.

BN - Flat vinyl T-edge - 74P edge 74P - Postformed edge ME - Urethane edge 34S - 3/8" Wood band edge

Select PowerUp/power module or grom-

Location is from the seated side of the

NOPU-NOGR - No PowerUp/no NOPU-GL- Grommet left; add \$18 NOPU-GR - Grommet right; add

NOPU-GC - Grommet center; add \$18

NOPU-GB - Grommet left and right; add \$40

NOGR-ML - PowerUp left; add \$123 **NOGR-MR** - PowerUp right; add \$123 NOGR-MC - PowerUp center; add \$123

NOGR-MB - PowerUp left and right; add \$242

NOPU-VL - Villa Grommet left; add \$70 NOPU-VR - Villa Grommet right; add \$70

NOPU-VC- Villa Grommet center; add

NOPU-VB- Villa Grommet left and right; add \$141

NOGR-VPL - Villa Power Module w/USB left; add \$337

NOGR-VPR - Villa Power Module w/USB right; add \$337

NOGR-VPC - Villa Power Module w/USB center; add \$337 - Villa Power Module

w/USB left and right; add \$673

DSelect PowerUp module/grommet color.

NOGR-VPB

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Select base finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Edge color offerings are based on edge style selections.



DataLink® Table System Fixed Leg Tables/Power

Flat Vinyl T-Edge (BN)	74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	3/8" Wood Band Edge (34S)	
\$ 1255	\$ 1282	\$ 1345	\$ 1447	\$ 1502	
1272	1299	1360	1466	1519	
1287	1313	1374	1480	1533	
1287	1313	1374	1480	1544	
1306	1332	1394	1497	1557	
1320	1351	1407	1513	1576	
1315	1349	1405	1525	1595	
1333	1362	1422	1543	1612	
1352	1377	1437	1555	1627	
1388	1419	1482	1620	1715	
1405	1433	1499	1637	1730	
1422	1449	1514	1651	1746	
1569	1601	1669	1833	1932	
1588	1619	1685	1849	1950	
1603	1635	1702	1865	1962	

INFORMATION

Wood Color Variations

High quality wood table edges and surfaces are characterized by distinctive natural colors and grain patterns. Due to natural variations of fine wood, it is impossible to exactly match colors and grains with consistency.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System Fixed Leg Tables/No Power

			MODEL NUMI	BER						
	Features	DxWxH	Basic Model/ Power Option	Edge Style	Grommet/ Module Location	Grommet/ Module Color	Base Finish	Surface Finish	Edge Color	Approx. Packaged Weight
	No Power	24 x 36 x 27	DX243627-NP							63.0#
	No Power	24 x 36 x 29	DX243629-NP							63.0#
	No Power	24 x 36 x 32	DX243632-NP							63.0#
<u>"</u>	No Power	24 x 42 x 27	DX244227-NP							
	No Power	24 x 42 x 29	DX244229-NP							70.0#
DLFX	No Power	24 x 42 x 32	DX244232-NP							70.0#
Fixed Leg Table, 24"D	No Power	24 x 48 x 27	DX244827-NP							77.0#
Duplex receptacles, infeeds, and	No Power	24 x 48 x 29	DX244829-NP							77.0#
jumpers for the "Power Option" must	No Power	24 x 48 x 32	DX244832-NP							77.0#
be ordered separately	No Power	24 x 60 x 27	DX246027-NP							88.0#
Wire trough assembly is standard on	No Power	24 x 60 x 29	DX246029-NP							88.0#
all tablesData ports located in the modesty	No Power	24 x 60 x 32	DX246032-NP							89.0#
panel are standard. Data jacks are	No Power	24 x 72 x 27	DX247227-NP							100.0#
supplied by the customer • Includes ganger	No Power	24 x 72 x 29	DX247229-NP							100.0#
	No Power	24 x 72 x 32	DX247232-NP							101.0#
 See Activ8® Single Circuit Electrical System to order modules 										
			A	3	•	D	•	•	Ф	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model/power option. NP = No Power
- BSelect edge style.

BN	- Flat vinyl I-edge
74P	- 74P edge
PL	 Postformed edge
ME	- Urethane edge
348	- 3/8" Wood band edge

Select PowerUp/power module or grom-

Location is from the seated side of the

table.	
NOPU-NOGR	- No PowerUp/no
grommet	
NOPU-GL- Gron	nmet left; add \$18
NOPU-GR	- Grommet right; add
\$18	
NOPU-GC	- Grommet center; add
\$18	
NOPU-GB	- Grommet left and
right: add \$40	

NOGR-ML	- PowerUp left; add
\$123	
NOGR-MR	- PowerUp right; add
\$123	
NOGR-MC	- PowerUp center; add
\$123	
NOGR-MB	- PowerUp left and
right; add \$242	
CCTL-NOGR	- Activ8 hole left
CCTR-NOGR	- Activ8 hole right
CCTC-NOGR	- Activ8 hole center
CCTB-NOGR	- Activ8 hole both
	Grommet left; add \$70
NOPU-VR	- Villa Grommet right;
add \$70	
	Grommet center; add
\$70	

NOPU-VB- Villa Grommet left and right;

add \$141 - Villa Power Module NOGR-VPL

w/USB left; add \$337 NOGR-VPR - Villa Power Module w/USB right; add \$337

NOGR-VPC - Villa Power Module w/USB center; add \$337

NOGR-VPB - Villa Power Module w/USB left and right; add

• Select PowerUp module/grommet

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Select base finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

• Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.
Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder. Edge color offerings are based on edge style selections.



DataLink® Table System Fixed Leg Tables/No Power

				3/8" Wood	
Flat Vinyl T-Edge (BN)	74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	Band Edge (34S)	
\$ 1091	\$ 1120	\$ 1179	\$ 1286	\$ 1339	
1110	1136	1199	1305	1356	
1125	1154	1213	1316	1372	
1125	1154	1213	1316	1381	
1141	1170	1231	1334	1397	
1159	1184	1245	1353	1414	
1148	1177	1235	1356	1428	
1165	1194	1254	1372	1442	
1179	1211	1269	1388	1461	
1208	1235	1300	1437	1531	
1225	1254	1315	1453	1550	
1240	1269	1333	1472	1564	
1372	1404	1472	1635	1736	
1388	1421	1485	1649	1749	
1405	1434	1503	1668	1767	

INFORMATION

Wood Color Variations

High quality wood table edges and surfaces are characterized by distinctive natural colors and grain patterns. Due to natural variations of fine wood, it is impossible to exactly match colors and grains with consistency.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System Fixed Leg Tables/Power

			MODEL NUM	RFR						
			model nom							
	Features	D x W x H	Basic Model/ Power Option	Edge Style	Grommet/ Module Location	Grommet/ Module Color	Base Finish	Surface Finish	Edge Color	Approx. Packaged Weight
	Power	30 x 36 x 27	DX303627-T6							75.0#
	Power	30 x 36 x 29	DX303629-T6							75.0#
	Power	30 x 36 x 32	DX303632-T6							75.0#
"	Power	30 x 42 x 27	DX304227-T6							82.0#
	Power	30 x 42 x 29	DX304229-T6							82.0#
DLFX	Power	30 x 42 x 32	DX304232-T6							83.0#
Fixed Leg Table, 30"D	Power	30 x 48 x 27	DX304827-T6							89.0#
Available with or without a 10-	Power	30 x 48 x 29	DX304829-T6							89.0#
wire/6- circuit power distribution unit	Power	30 x 48 x 32	DX304832-T6							90.0#
("Power Option")	Power	30 x 60 x 27	DX306027-T6							103.0#
Duplex receptacles, infeeds, and "B"	Power	30 x 60 x 29	DX306029-T6							103.0#
jumpers for the "Power Option" must be ordered separately	Power	30 x 60 x 32	DX306032-T6							104.0#
The wire trough assembly is standard	Power	30 x 72 x 27	DX307227-T6							116.0#
on all tables	Power	30 x 72 x 29	DX307229-T6							116.0#
Data ports located in the modesty	Power	30 x 72 x 32	DX307232-T6							117.0#
panel are standard. Data jacks are supplied by the customer										
Includes ganger										
See Activ8® Single Circuit Electrical										
System to order modules										
			•	3	•	0	(3	•	0	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model/power option. T6=Power
- BSelect edge style.

BN	- Flat vinyl T-edge
74P	- 74P edge
PL	- Postformed edge
ME	- Urethane edge
34S	- 3/8" Wood band edge

Select PowerUp/power module or grommet location.

Location is from the seated side of the NOPII-NOGE - No Powerlin/no

NOI O-NOUII	NO I OWGIOP/IIO
grommet	
	nmet left; add \$18
NOPU-GR	- Grommet right; add
\$18	
NOPU-GC	- Grommet center; ad
\$18	
NOPU-GB	- Grommet left and
right; add \$40	

NOGR-ML	- PowerUp left; add
\$123	
NOGR-MR	- PowerUp right; add
\$123	
NOGR-MC	- PowerUp center; add
\$123	
NOGR-MB	- PowerUp left and
right; add \$242	
NOPU-VL - Villa	Grommet left; add \$70

NOPU-VR - Villa Grommet right; add \$70

NOPU-VC- Villa Grommet center; add

NOPU-VB- Villa Grommet left and right; add \$141

NOGR-VPL - Villa Power Module w/USB left; add \$337 NOGR-VPR - Villa Power Module

w/USB right; add \$337 NOGR-VPC - Villa Power Module

w/USB center; add \$337 NOGR-VPB - Villa - Villa Power Module w/USB left and right; add \$673

DSelect PowerUp module/grommet color.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

- Select base finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.
- Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Surface finish offerings are based on edge style selections.
- **G**Select edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Edge color offerings are based on edge style selections.



DataLink® Table System Fixed Leg Tables/Power

Flat Vinyl T-Edge (BN)	74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	3/8" Wood Band Edge (34S)	
\$ 1320	\$ 1351	\$ 1407	\$ 1522	\$ 1590	
1335	1363	1426	1541	1604	
1354	1381	1441	1553	1621	
1354	1381	1441	1553	1628	
1367	1397	1460	1569	1646	
1386	1414	1474	1588	1663	
1383	1408	1472	1596	1680	
1399	1428	1485	1613	1697	
1417	1442	1503	1628	1715	
1467	1495	1557	1705	1812	
1482	1509	1576	1720	1828	
1499	1526	1593	1738	1846	
1661	1687	1758	1928	2039	
1674	1705	1772	1944	2057	
1690	1720	1790	1959	2071	

INFORMATION

Wood Color Variations

High quality wood table edges and surfaces are characterized by distinctive natural colors and grain patterns. Due to natural variations of fine wood, it is impossible to exactly match colors and grains with consistency.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System Fixed Leg Tables/No Power

	MODEL NUMBER									
	Features	DxWxH	Basic Model/ Power Option	Edge Style	Grommet/ Module Location	Grommet/ Module Color	Base Finish	Surface Finish	Edge Color	Approx. Packaged Weight
	No Power	30 x 36 x 27	DX303627-NP							75.0#
	No Power	30 x 36 x 29	DX303629-NP							75.0#
	No Power	30 x 36 x 32	DX303632-NP							75.0#
<u> </u>	No Power	30 x 42 x 27	DX304227-NP							82.0#
	No Power	30 x 42 x 29	DX304229-NP							82.0#
DLFX	No Power	30 x 42 x 32	DX304232-NP							83.0#
Fixed Leg Table, 30"D	No Power	30 x 48 x 27	DX304827-NP							89.0#
Duplex receptacles, infeeds, and	No Power	30 x 48 x 29	DX304829-NP							89.0#
jumpers for the "Power Option" must	No Power	30 x 48 x 32	DX304832-NP							90.0#
be ordered separately	No Power	30 x 60 x 27	DX306027-NP							103.0#
The wire trough assembly is standard	No Power	30 x 60 x 29	DX306029-NP							103.0#
on all tablesData ports located in the modesty	No Power	30 x 60 x 32	DX306032-NP							104.0#
panel are standard. Data jacks are	No Power	30 x 72 x 27	DX307227-NP							116.0#
supplied by the customer	No Power	30 x 72 x 29	DX307229-NP							116.0#
Includes ganger Con Active® Single Circuit Floatnice	No Power	30 x 72 x 32	DX307232-NP							117.0#
 See Activ8® Single Circuit Electrical System to order modules 										
System to order modules										
			A	B	•	O	•	•	0	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model/power option. NP=No Power

BSelect edge style.

BN	- Flat vinyl T-edge
74P	- 74P edge
PL	 Postformed edge
ME	- Urethane edge
348	- 3/8" Wood band edge

Select PowerUp/power module or grom-

Location is from the seated side of the

table.	
NOPU-NOGR	- No PowerUp/no
grommet	
NOPU-GL- Gron	nmet left; add \$18
NOPU-GR	- Grommet right; add
\$18	
NOPU-GC	- Grommet center; add
\$18	
NOPU-GB	- Grommet left and
right; add \$40	

NOGR-ML	- PowerUp left; add
\$123	
NOGR-MR	- PowerUp right; add
\$123	
NOGR-MC	- PowerUp center; add
\$123	
NOGR-MB	- PowerUp left and
right; add \$242	
CCTL-NOGR	- Activ8 hole left
CCTR-NOGR	- Activ8 hole right
CCTC-NOGR	- Activ8 hole center
CCTB-NOGR	- Activ8 hole both
NOPU-VL - Villa	Grommet left; add \$70
NOPU-VR	- Villa Grommet right;
add \$70	
NOPU-VC- Villa	Grommet center; add
\$70	

NOPU-VB- Villa Grommet left and right; add \$141

- Villa Power Module NOGR-VPL w/USB left; add \$337

NOGR-VPR - Villa Power Module w/USB right; add \$337 NOGR-VPC - Villa Power Module w/USB center; add \$337

NOGR-VPB - Villa Power Module w/USB left and right; add

• Select PowerUp module/grommet

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Select base finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

• Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.
Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder. Edge color offerings are based on edge style selections.



DataLink® Table System Fixed Leg Tables/No Power

Flat Vinyl T-Edge (BN)	74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	3/8" Wood Band Edge (34S)	
\$ 1159	\$ 1184	\$ 1245	\$ 1360	\$ 1428	
1175	1203	1262	1374	1442	
1191	1217	1278	1394	1461	
1191	1217	1278	1394	1469	
1208	1234	1297	1407	1483	
1225	1252	1311	1426	1500	
1213	1241	1305	1429	1513	
1231	1257	1316	1444	1528	
1245	1274	1334	1462	1548	
1284	1311	1376	1524	1629	
1300	1327	1395	1542	1647	
1315	1348	1408	1554	1664	
1462	1489	1557	1727	1841	
1477	1505	1576	1745	1858	
1495	1524	1593	1763	1873	

INFORMATION

Wood Color Variations

High quality wood table edges and surfaces are characterized by distinctive natural colors and grain patterns. Due to natural variations of fine wood, it is impossible to exactly match colors and grains with consistency.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System

Wedges

			MODEL N	IIMDED			
	MODEL	D x ANGLE	Basic Model	Edge Style	Surface Finish	Edge Color	Approx. Packaged Weight
	Wedges	24 x 30°	DLW2430				11.0#
	Available in 3 edge styles Wedges form radiused configurations by bridging adjoining rectangular worksur-						
•	faces Wedges do not have legs. They are supported by rectangular metal splice tubes,						
	which are attached to the underside of the wedge. The rectangular metal splice						
	tubes are inserted under the adjoining table top.						
V	Wedges	24 x 45°	DLW2445				17.0#
DLW							
V	Wedges	24 x 60°	DLW2460				18.0#
DLW							
V	Wedges	24 x 90°	DLW2490				22.0#
DLW							
	Wedges	30 x 30°	DLW3030				16.0#
DLW							
	Wedges	30 x 45°	DLW3045				21.0#
DLW							
	Wedges	30 x 60°	DLW3060				22.0#
DLW							
	Wedges	30 x 90°	DLW3090				26.0#
DLW							
			a	3	Ф	0	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- Select edge style.

 74P
 - 74P edge

 ME
 - Urethane edge

 34S
 - 3/8" Wood band edge

Select surface finish.

Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.

Surface finish offerings are based on edge style selections.

OSelect edge color.

Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.

Edge color offerings are based on edge style selections.

INFORMATION

Wood Color Variations

High quality wood table edges and surfaces are characterized by distinctive natural colors and grain patterns. Due to natural variations of fine wood, it is impossible to exactly match colors and grains with consistency.



DataLink® Table System Wedges





74P Edge

Urethane Edge 422

562

	Ф	

\$	389	\$	451	\$	596
		_	105		
\$	418	\$	485	\$	627
\$	507	\$	589	\$	708
•		•			
\$	389	\$	459	\$	634
\$	453	\$	528	\$	677
Φ.	407	Φ.	F74	φ	700
\$	487	\$	571	Ф	723
\$	561	\$	652	\$	833

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System Non-Electrical Accessories

	MODEL	MODEL NUMBER Basic Model	Approx. Packaged Weight
HRDPT	Table Ganger (Set of 2 for one table-to-table gang) Gangers are nylon Two gangers are required per table, included with table Two gangers snap onto the bosses located on the leg cantilever Gangers are self-storing when not in use Black only	DLGANG	1.0#
HRDPT	Table Splice Plate (Set of 2 for one table-to-table connection) • For permanent joining of tables or wedges • Two plates required per table connection • Hardware included • Black only	DLSPLICE	1.0#
₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩ ₩	Caster (Set of 4) • 2-3/4" diameter • Dual wheel locking carpet casters • Caution: casters add 3" to table height • Black only	DLCA	1.0#
	Table Truck Overall dimensions 33" x 48" Platform and upright coated with nonmar, skid-resistant vinyl Four table capacity Red only	DLTRUCK	90.0#
HRDPT		A	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



DataLink® Table System Non-Electrical Accessories

Delivered
Pricing
\$ 16
0.00
\$ 16
\$ 128
 \$ 1500

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System

			MODEL NUMBER	
				Approx.
			Basic	Packaged
	MODEL	Features	Model	Weight
alb.	Worksurface-to-Worksurface 10-Wire		DLT6JT	2.0#
	Connector for Rectangular Worksurface Connects the 10-wire power system of			
N I	two adjacent tables			
	• 33" long			
HRDPT	Silver conduit			
J.C.	Worksurface-to-Worksurface 10-Wire		DLT6JW	2.0#
	Connector for Wedges • Connects the 10-wire power system of			
The state of the s	two adjacent tables			
	The connector extends from one			
HRDPT	rectangular worksurface, under the			
	adjacent wedge, to the other rectangular worksurface			
	• 39" long			
	Silver conduit			
			4070	100
A ta	Quad-Block • Allows power to be distributed from the		4BT6	1.0#
	middle of a table series			
	The Quad-Block (along with included			
	jumper) enables infeed power from the building to be routed in two directions.			
	These units, four female openings accept			
	the male end of the power infeed and			
HRDPT	the male plug ends of two table-to-table			
	jumpers which tranfer the power to the two adjoining tables.			
		01 11 1	47 0700 4 54	
	Receptacles - 6 Circuit • Attaches to wireways of 10 wire powered	Circuit 1	47.0706.1.BL	1.0#
	tables	Circuit 2	47.0706.2.BL	1.0#
		Circuit 3	47.0706.3.BL	1.0#
	Provides two (duplex) receptacles each	Circuit 3	47.0700.41.01	4.0 "
Winds The Park The Pa	Provides two (duplex) receptacles each rated at 15 amps	Circuit 4	47.0706.4I.BL	1.0#
HRDPT	Provides two (duplex) receptacles each rated at 15 amps Some circuits are isolated ground	Circuit 4 Circuit 5	47.0706.51.BL	1.0#
HRDPT	 Provides two (duplex) receptacles each rated at 15 amps Some circuits are isolated ground circuits (622 - 4,5, & 6), Isolated ground receptacles are identified by an orange 	Circuit 4		
HRDPT	 Provides two (duplex) receptacles each rated at 15 amps Some circuits are isolated ground circuits (622 - 4,5, & 6), Isolated ground 	Circuit 4 Circuit 5	47.0706.51.BL	1.0#
HRDPT	 Provides two (duplex) receptacles each rated at 15 amps Some circuits are isolated ground circuits (622 - 4,5, & 6), Isolated ground receptacles are identified by an orange 	Circuit 4 Circuit 5	47.0706.51.BL	1.0#

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



DataLink® Table System Electrical Accessories

Deliv	livered
Prici	livered cing
\$	139
\$	147
\$	40
Ť	
\$	
	24
	24
	24
	24
	24

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

DataLink® Table System

		MODEL NUI	MBER		
	MODEL Power Strip	Basic Model PC.0SWS	Paint Color	Approx. Packaged Weight 3.0#	
HRDPT	Optional electrical source Surge protected six outlet, 110 volt electrical strip with 6' long cord to lay in wire manager trough Off-white only				
пкирт	Interest 40 Million (C. Olinsonia	DTEE		F 0 #	
	Infeed 10-Wire/6-Circuit The 10-wire/6-circuit infeed contains six lines (12 ga.) two neutrals (10 ga.), and two grounds (12 ga.) providing six circuits of power to the power distribution unit Must be hard-wired to the building power source by a licensed electrician	PTFF		5.0#	
HRDPT	• 105" long				
	NY Infeed - 10 Wire • Meets NY electrical code	DLINYT6.L		5.0#	
	If the infeed's "whip" must exit from	DLINYT6.R		5.0#	
	the left leg (as seen from the seated				
	position), select the left-hand infeed. Similarly, select the right-hand infeed if				
	the "whip" must exit from the right leg				
	(as seen from the seated position)				
HRDPT	Not for use on 36" length tables				
	O William to 40 William Adouted	47.0709.30		1.0#	
∕3 i	8-Wire to 10-Wire Adaptor • 30" long	47.0709.30		1.0#	
A second					
A STATISTICAL PROPERTY OF THE PARTY OF THE P					
HRDPT					
		A	3	-	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect paint color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder



DataLink® Table System Electrical Accessories

Deliv	vered
Prici	ing
\$	139
\$	146
	444
	444
\$	154

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 85.

Specifications and prices are subject to change without prior notice.

		MODEL NUMBER		
	MODEL	Basic Model	Approx. Packaged Weight	
	Activ8® Infeed	AC8IF.108	2.0#	
	108" cord plugs into standard 15 amp			
	outlet Control module is located 6" from table			
8	connection			
HRDPT	Diagnostic LED indicator shows power			
	status (see details below)			
	 Controller automatically limits number of connections to 8 			
	40 Ft maximum string, not including			
	infeed cord			
	Will not work with GFI/GCFI outlets or			
	backup systems such as uninterrupted power supplies			
	power supplies			
		AC8RPTDL.12	1.0#	
	Activ8® Module and Attachment Bracket	7.001.11 152.12	110#	
	- Dunlay recented to a recide O sublete			
d/ <i>a</i>	Duplex receptacles provide 2 outlets			
	Power module provides 15 amp power			
	 Power module provides 15 amp power Up to 8 modules may be used per infeed 			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential			
HRDPT	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying)			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying)			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12)			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12) Jumpers ordered separately			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12) Jumpers ordered separately Module will snap directly into KI			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12) Jumpers ordered separately			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12) Jumpers ordered separately Module will snap directly into KI Genesis® troughs and KI True® Desking stanchions No data cord management is provided			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12) Jumpers ordered separately Module will snap directly into KI Genesis® troughs and KI True® Desking stanchions			
	Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Modules snap into brackets that are attached to the InTandem®Table System (AC8RPTIT.12), WorkZone®, and DataLink® Training Table (AC8RPTDL.12) Jumpers ordered separately Module will snap directly into KI Genesis® troughs and KI True® Desking stanchions No data cord management is provided	0		

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



•
Delivered Pricing
Pricing
\$ 209
\$ 132
\$ 152

		MODEL N	IUMBER			
	MODEL	Basic Model	PowerUp Module Color	Approx. Packaged Weight		
HRDPT	Activ8® Power-Up Module Duplex receptacles provide 2 outlets Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Attached cord is approximately 12° Data tree is provided to allow data jacks to be inserted in the module Jumpers ordered separately	AC8PUM		1.0#		
HRDPT	Activ8® Villa Power Module with Metal Cover Duplex receptacles provide 2 outlets, 2 USB charging ports, 1 RJ45 data connector Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Attached cord is approximately 12* Data tree is provided to allow data jacks to be inserted in the module Jumpers ordered separately	AC8VMC		3.0#		
HRDPT	Activ8® Villa Power Module without Cover Duplex receptacles provide 2 outlets, 2 USB charging ports, 1 RJ45 data connector Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Attached cord is approximately 12° Data tree is provided to allow data jacks to be inserted in the module For use on tables with existing KI grommets Jumpers ordered separately	AC8VMN		2.0#		
		A	B			

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect module color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder



•
Delivered
Pricing
\$ 194
φ 134
\$ 412
\$ 348

			MODEL NUMBER			
	MODEL	L	Basic Model	Approx. Packaged Weight		
	Activ8® Jumper	29"	AC8JP.29	1.0#		
	Jumper lengths include 29", 53" and 77"Jumpers are all keyed alike	53"	AC8JP.53	1.0#		
an l	Jumpers are all keyed allke	77"	AC8JP.77	1.0#		
HRDPT						
			A			

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



Deli	vered
Pric	ing
\$	66

77 88

Flat Screen Garage®

General Information



Flat Screen Garage®

F	0	•	н	п	ı	r	Ω	o

Standard size cutout area 19.38"W x 7.5"D

Maximum monitor size 18.45"W x 16.5"H x 3.25"D

FLAT SCREEN GARAGE® CONSTRUCTION

Flat Screen Garage® Worksurfaces

Horizontal worksurfaces are constructed of 1-1/8" thick 45# density particleboard with .030 thick high-pressure laminate and .030 thick high-pressure backing sheet. Post-formed (PL) edge worksurfaces have elliptical front edge. Rear and side edges are covered in matching flat .024" edge banding. Urethane (ME) edge worksurfaces have elliptical molded front edge. Rear and side edges molded in 1/4" flat urethane. Worksurfaces have one or two cutouts, which accept Flat Screen Garage® unit(s). Garage units included in price for worksurface. Edges are sealed and painted black. A single grommet or PowerUp® module may be placed in most worksurfaces. Grommets are standard 5-3/4" x 2-1/4" and have a flip-up receding door. Grommets are the same size as PowerUp® modules to allow for retrofitting. The grommet or PowerUp® will be placed in the upper left corner for worksurface widths of 42", 48", and 54" or centered between the doors for double units.

ADA Tables

Single unit ADA tables may be ordered. Specify a 32" deep worksurface, ADA legs with locking casters, and a non-powered beam of chosen width. Finished height with casters, 32". Knee clearance with 32" deep worksurface, 19". ME edge not available on ADA tables.

Beam Assembly

Beam door is constructed of a .06" thick dual-durometer extrusion joined to the steel lower rail by a tongue and groove fit. The door has a continuous flexible hinge allowing it to pivot at the bottom. The beam allows all cords to be stored within. The front side of the beam is partially covered by the garage and its components with minimum accessibility from the user side. Beams for the Flat Screen Garage® must be specified as "standalone," "end-of-run left," "middle," or "end-of-run right." Standalone beams will be shipped with two end caps; end-of-run beams will be shipped with one. Middle

beams will not include any end caps.

Legs

Vertical leg tube measures 2" x 5" and is constructed of 14-gauge formed steel. All legs have vertical wire management capabilities. A reversible vertical wireway is standard with each leg. Steel trim and liquid-tight fittings are available for power infeeds at the bottom of any leg. All "C" legs can be used as either end legs or shared legs. Flat Screen Garage® legs are not interchangeable with InTandem® "C" legs. Nylon glide under toe casting can be adjusted vertically up to 1-1/4".

Garage Unit and Motor

The garage is fabricated from 16-gauge steel front and back panels and a 14-gauge steel bottom with matching powder-coated finishes. The shelf is raised to the preferred height by an electric motor enclosed in extruded aluminum. The main shelf features two holding brackets to vertically support a keyboard, and a storage area for a mouse.

Flat Screen Garage® Operation

The Flat Screen Garage® unit can be accessed with either a remote control device or by a simple push of the up button on the up/down electric switch located on the under side of the worksurface corner. The door will automatically open and the monitor, keyboard and mouse will rise to the preferred height by an enclosed electric motor. Internally stored keyboard and mouse are manually removed for use. The monitor is secured to a support bracket that can be manually adjusted to minimize glare. To limit abuse and maximize motor life, the unit is designed to shut off if it is kept moving for longer than two minutes in a ten minute span.

Infrared Receiver

Works with and must be ordered with an infrared remote control unit to lock down or unlock a room of tables featuring flatscreen garage units. One receiver is attached to each table, and can receive a signal for up to two garage units.



Flat Screen Garage® General Information

Infrared Remote Control Unit

Sends locking and unlocking signals to receivers and can also be used to raise and lower multiple units at once.

$\textbf{PowerUp} \\ \\ \textbf{@}$

PowerUp® is a UL Listed, relocatable power tap, which mounts flush into the table top. When flipped up, (cover open), one duplex receptacle and two data ports are exposed. PowerUp® is UL Listed (UL1363) as a Temporary Power Tap. The PowerUp® module is 7" long x 3-1/2" wide x 2-1/2" high and fits securely into a 6-1/4" x 3" cutout, still allowing removal without tools. The module is constructed of polycarbonate with a textured finish, meeting UL-VO minimum requirements. The module has two receptacles, rated at 15 Amps/125 Volts and two locations for data connectors. Snap-in data plates hold data connectors and allow the standard module to accommodate most manufacturers. The data connectors are not supplied with the module and are purchased by the customer. The module has a dampened spring-loaded mechanism allowing the unit to open for use and close when not in use. The power receptacles open above the plane of the worksurface to avoid accidental spills into the receptacle. Data jacks remain stationary to avoid excess wear and tear on the wire connections and promote transmission of data communication. Data ports are molded to accept RJ45 jacks, but can be modified to accept various brands of jacks. The module comes standard with a 22" cord and a 3-prong plug.

10-Wire Pre-wired Harness

UL listed the wiring configurations of the 810-wire systems are as follows: 622-Six hot conductors (12-gauge), two neutral conductors (10-gauge) and two grounds (12-gauge). System provides four 20 amp, 125 volt capacity circuits. All receptacles are rated at 15 amps, 125 volt capacity. Connection diagrams are available. Pre-wired harness plugs into the adjacent table harness for table reconfiguration.

Communications Circuitry

Data connectors and wiring must be ordered

separately by the customer.

Privacy Screens

Standard 3/4" thick core material. Both sides are laminated with .030" thick high-pressure laminate as standard. All edges are banded with edging. Available in three heights with a straight top edge.

Divider Screens

Standard 3/4" thick core material. Both sides are laminated with .030" thick high-pressure laminate as standard. All edges are banded with edging. Available in three heights with a curved top. Dividers are available only in conjunction with privacy screens.

Note

New York City and Chicago installations will require a special order to be written. Contact your CSR.

INFORMATION

Warranty

Refer to KI Terms & Conditions document or visit ki.com

Smart Lift®



Smart Lift™

	~	.+	20	•
г		ıtu	ш	

Standard size cutout area 21"W x 6"D

Maximum monitor size 21"W x 19"H x 3.6"D

SMART LIFT® CONSTRUCTION

Worksurfaces

Horizontal worksurfaces are constructed of 1-1/8" thick 45# density particleboard with .030 thick high-pressure laminate and .030 thick high-pressure backing sheet. Post-formed (PL) edge worksurfaces have elliptical front edge. Rear and side edges are covered in matching flat .024" edge banding. Urethane (ME) edge worksurfaces have elliptical molded front edge. Rear and side edges molded in 1/4" flat urethane. 74P (74P) edge is 2mm thick and bonded to all 4 sides of the surface. Worksurfaces have one or two 6" x 21" cutouts which accept Smart Lift™ unit(s). Smart Lift® price is included in the price shown for worksurface. Smart Lift® cutouts in the worksurface are sealed and painted black. A single grommet or PowerUp® module may be placed in most worksurfaces. Grommets are standard 5-3/4" x 2-1/4" and have a flip-up receding door. Grommets are the same size as PowerUp® modules to allow for retrofitting.

The grommet or PowerUp® will be placed in the upper right corner for worksurface widths of 48" and 54" or centered between the doors for the 66" and 72" double uts. The door is fabricated from 5/8" thick 45# density with .030" high-pressure laminate on both faces. The door edges are sealed and painted black.

Smart Lift® Beam Assembly

Beam door is constructed of a .06" thick dual-durometer extrusion joined to the steel lower rail by a tongue and groove fit. The door has a continuous flexible hinge allowing it to pivot at the bottom. The beam allows all cords to be stored within. The front side of the beam is partially covered by the garage and its components with minimum accessibility from the user side. Beams for the Smart Lift® must be specified as "standalone," "end-of-run left," "middle," or "end-of-run right." Standalone beams will be shipped with two end caps; end-of-run beams will be shipped with either a left or right end cap; middle beams will not include any end caps.

Smart Lift® Legs

Vertical leg tube measures 2" x 5" and is constructed of 14-gauge formed steel. All legs have vertical wire management capabilities. A reversible vertical wireway is standard with each leg. Steel trim and liquid-tight fittings are available for power infeeds at the bottom of any leg. All "C" legs can be used as either end legs or shared legs. Flat Screen Garage® legs are not interchangeable with InTandem® "C" legs. Nylon glide can be adjusted vertically up to 1-1/4".

Smart Lift® Unit

The garage housing and front panel is fabricated from 16-gauge steel with matching powder-coated finishes. Internal components and wiring for the monitor, keyboard, and mouse can be accessed by removal of seven screws attaching the front panel. The lift bar is fabricated from 11-gauge steel with a 14-gauge steel keyboard/mouse tray and is available in black powder-coat finish. The lift bar and rising door is guided by four, maintenance-free V-groove roller bearings attached to an 11-gauge roller bracket also

available in black powder-coat finish. The lift bar is raised pneumatically via a cable/pulley mechanism that is mounted inside the unit. The keyboard/mouse tray features a 3/16" diameter wire rod to hold the keyboard vertically in place for storage and provides for an area under the monitor for mouse storage. The garage unit can be specified with a keyed lock that allows every cover to be locked individually or a remote locking option that allows multiple-unit locking via control of 1-5 remote key fobs. Wire management within the unit is accomplished with a corrugated polyethylene hose and grommet/clamp arrangement. The hose is split lengthwise to allow for easier insertion of cords with large plugs. An optional monitor tilt kit can be specified to allow up to 10 degrees of tilt and reduce glare. Smart Lift™ units without monitor tilt can accommodate a VESA compliant monitor with a maximum size of 3.6" deep x 19.0" high x 21.0" wide and maximum weight of 15#. The combined keyboard and monitor thickness must be less than 4.8" thick. The maximum depth of monitor with the monitor tilt option is



reduced by .6" to 3.0".

Smart Lift® Operation

Monitor and peripherals can be accessed by lightly depressing the center, front of door and releasing. The unit will automatically raise fully allowing access to the monitor, keyboard and mouse. Internally stored keyboard and mouse may be removed manually for use. After use, the keyboard, mouse, and associated wiring can be restowed below the monitor. Storage of monitor and peripherals is accomplished by pushing down firmly on the top, center of door until slightly below worksurface height and releasing.

Remote Control Unit

Sends locking and unlocking signals to receivers. Remote must be specified separately if electric lock option (ELK) is selected.

PowerUp®

PowerUp® is a UL Listed, relocatable power tap, which mounts flush into the table top. When flipped up, (cover open), one duplex

receptacle and two data ports are exposed. PowerUp® is UL Listed (UL1363) as a Temporary Power Tap. The PowerUp® module is 7" long x 3-1/2" wide x 2-1/2" high and fits securely into a 6-1/4" x 3" cutout, still allowing removal without tools. The module is constructed of polycarbonate with a textured finish, meeting UL-VO minimum requirements. The module has two receptacles, rated at 15 Amps/125 Volts and two locations for data connectors. Snap-in data plates hold data connectors and allow the standard module to accommodate most manufacturers. The data connectors are not supplied with the module and are purchased by the customer. The module has a dampened spring-loaded mechanism allowing the unit to open for use and close when not in use. The power receptacles open above the plane of the worksurface to avoid accidental spills into the receptacle. Data jacks remain stationary to avoid excess wear and tear on the wire connections and promote transmission of data communication. Data ports are molded to accept RJ45 jacks, but can be modified to accept various brands of jacks.

The module comes standard with a 22" cord and a 3-prong plug.

10-Wire Pre-wired Harness

UL listed the wiring configurations of the 810-wire systems are as follows: 622-Six hot conductors (12-gauge), two neutral conductors (10-gauge) and two grounds (12-gauge). System provides four 20 amp, 125 volt capacity circuits. All receptacles are rated at 15 amps, 125 volt capacity. Connection diagrams are available. Pre-wired harness plugs into the adjacent table harness for table reconfiguration.

Communications Circuitry

Data connectors and wiring must be ordered separately by the customer.

Note

New York City and Chicago installations will require a special order to be written. Contact KI.

INFORMATION

Warranty

Refer to KI Terms & Conditions document or visit ki.com

Flat Screen Garage® Worksurface - Poly Grommet/PowerUp

			MODEL N	JMBER						
						Grommet/			Grommet/	
			Basic	Edge	Power	Module	Surface	Edge	Module	Enclosure
	MODEL	D x W	Model	Style	Option	Location	Finish	Color	Color	Color
- m	Single Unit	30 x 36"	ITFW3036			S				
	Legs are attached to the worksurface	30 x 42"	ITFW3042							
	through threaded steel inserts Beams and legs must be specified	30 x 48"	ITFW3048							
De la companya della companya della companya de la companya della	separately	30 x 54"	ITFW3054							
	One 22" PowerUp® module or grommet									
	is available in the upper left corner for 42",48" and 54"widths									
ITFW	• 30" depth provides 17" leg clearance									
dn	Single Unit - ADA Tops	32 x 36"	ITFW3236			S				
	 Order with ADA legs Order with non-powered beam only ME edge not available on 32" deep tables 32" depth provides 19" knee clearance 	32 x 42"	ITFW3242							
		32 x 48"	ITFW3248							
1		32 x 54"	ITFW3254							
TFW			175711005 T		_					
10.	Double Unit • Legs are attached to the worksurface	30 x 60"	ITFW3060			S				
	through threaded steel inserts	30 x 66"	ITFW3066							
	Beams and legs must be specified	30 x 72"	ITFW3072							
	separatelyOne 22" PowerUp® module or grommet									
	is available centered between the doors									
*	for double-unit 66" and 72" widths									
	30" depth provides 17" leg clearance									
TFW										
			A	B	Θ	•	•	•	О	•

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

74P	- 74P edge
PL	- Postformed edge
ME	- Urethane edge

Select top feed location

	top rood roodtrom	
N	- No top feed	
L	 Left hand top feed 	
R	 Right hand top feed 	

• Select PowerUp or grommet location. Powerup modules for Flat Screen Garage tables are fitted with 22" cords only. Left side for single unit, center for double units.

- Grommet only (Rectangular); G

add \$17

- PowerUp only; add \$122 - No PowerUp modules,no grommets (solid surface top)

Select surface finish.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Surface finish offerings are based on edge style selections.

- Select edge color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u> Fabrics & Finishes binder. Edge color offerings are based on edge style selections.
- **G**Select grommet/module color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.
- Select enclosure color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder

INFORMATION

Shipping

Worksurfaces with cutouts are shipped separately from garage units. Garage units are shipped assembled with lids pre-attached.



Flat Screen Garage® Worksurface - Poly Grommet/PowerUp

			<		
Approx. Packaged Weight	74 (74	P Edge 4P)	Po (Pl	stformed Edge _)	Urethane Edge (ME)
86.0#	\$	1788	\$	1881	\$ \$ 1999
94.0#		1814		1906	2032
104.0#		1834		1928	2047
111.0#		1898		1997	N/A
86.0#	\$	1800	\$	1892	N/A
94.0#		1827		1920	N/A
104.0#		1846		1942	N/A
111.0#		1913		2011	N/A
159.0#	\$	3310	\$		\$ \$ 3570
166.0#		3321		3490	N/A
171.0#		3324		3492	3634

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Specifications and prices are subject to change without prior notice.

Flat Screen Garage®

Worksurface - Villa Metal Grommet/Power Module

		MODEL NUMBER									
	MODEL	D x W	Basic Model	Edge Style	Power Option	Grommet/ Module Location	Surface Finish	Edge Color	Grommet/ Module Color	Enclosure Color	
m	Single Unit	30 x 42"	IVFW3042								
	 Legs are attached to the worksurface through threaded steel inserts 	30 x 48"	IVFW3048								
	Beams and legs must be specified	30 x 54"	IVFW3054								
De la companya della companya della companya de la companya della	separately										
	One 36" Power module or metal grom- met is available in the upper left corner										
	for 42",48" and 54"widths										
W	30" depth provides 17" leg clearance										
	Single Unit - ADA Tops	32 x 42"	IVFW3242								
	Order with ADA legs	32 x 48"	IVFW3248								
	 Order with non-powered beam only ME edge not available on 32" deep tables 	32 x 54"	IVFW3254								
	32" depth provides 19" knee clearance										
-W											
	Double Unit	30 x 66"	IVFW3066								
	 Legs are attached to the worksurface through threaded steel inserts 	30 x 72"	IVFW3072								
	Beams and legs must be specified										
	separately										
	One 36" Power module or metal grommet is available centered between										
	the doors for double-unit 66" and 72"										
	widths • 30" depth provides 17" leg clearance										
v	- 30 deptil provides 17 leg dearance										
••			A	B	Θ	•	(3	•	О	•	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 □ indicate that no other alternatives
 are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect edge style.

74P - 74P edge
PL - Postformed edge
ME - Urethane edge

Select top feed location.

N - No top feed
L - Left hand top feed
R - Right hand top feed

Select PowerUp or grommet location. Powerup modules for Flat Screen Garage tables are fitted with 22" cords only. Left side for single unit, center for double units.

VG - One Villa grommet only; add \$66

VM - One Villa Module w/USB and grommet; add \$317

OC - Cutouts only (for single circuit use)

Select surface finish.

Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.

Surface finish offerings are based on edge style selections.

Select edge color.

Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.

Edge color offerings are based on

Edge color offerings are based on edge style selections.

- Select grommet/module color.
 Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>.
- Select enclosure color.
 Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>

INFORMATION

Shipping

Worksurfaces with cutouts are shipped separately from garage units. Garage units are shipped assembled with lids pre-attached.



Flat Screen Garage® Worksurface - Villa Metal Grommet/Power Module

		Y /			
Approx.			•		
Packaged	74P	Edge	Postformed Edge	Ur	Urethane Edge
Weight	(74P		(PL)		(ME)
94.0#	\$ 1		\$ 1906	ф	\$ 2032
104.0#		1834	1928		2047
111.0#	1	1898	1997		N/A
94.0#	\$ 1	1827	\$ 1920		N/A
104.0#	1	1846	1942		N/A
111.0#	1	1913	2011		N/A
166.0#	\$ 3	2201	\$ 3490		N/A
171.0#	3	3324	3492		3634

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Specifications and prices are subject to change without prior notice.

Smart Lift®

Worksurfaces - Poly Grommet/PowerUp

		MODEL N	IIMRER								
	D x W	Basic Model	Edge Style	Power Option	Grommet/ Module Location	Lock Option	Surface Finish	Edge Color	Grommet/ Module Color	Enclosure Color	Approx. Packaged Weight
	30 x 36"	ISMT3036			S						81.0#
110	30 x 42"	ISMT3042			S						89.0#
	30 x 48"	ISMT3048									99.0#
	30 x 54"	ISMT3054									106.0#
ISMT											
Single Unit											
Legs are attached to the worksurface											
 through threaded steel inserts Beams and legs must be specified 											
Beams and legs must be specified separately											
One PowerUp® module or grommet											
is available in the upper right corner											
for 48" and 54" widths											
 30" depth provides 17" leg clearance Remote must be specified separately 											
if electric lock option (ELK) is selected											
• 22" PowerUp® is recommended when the beam is powered											
108" PowerUp® is recommended											
when the beam is not powered											
The lift, without the tilt option, can											
accommodate a VESA compliant monitor with a maximum size of											
3.6" deep x 19" high x 21" wide and											
maximum weight of 15 lbs											
The combined keyboard and monitor											
thickness must be less than 4.8"											
The maximum depth of monitor with											
the optional tilt bracket (specified											
separately) is reduced by .6" to 3.0"											
A single SmartLift will receive one 10											
lb kit: includes four 2-1/2 lb weights, carriage bolt and locking nut											
Samage Boil and looking nat											
		A	3	•	• • • • • • • • • • • • • • • • • • •	3	3	(•	0	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 □ indicate that no other alternatives
 are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

74P	- 74P edge	
PL	- Postformed edge	Ī
ME	- Urethane edge	Ī

Select top feed location.

o.oot top	1000 1000010111
N	- No top feed
L	- Left hand top feed
R	- Right hand top feed

Select PowerUp or grommet location.

ו זטטוטנ	ower up or grounner location.
G	 Grommet only (Rectangular)
P	- PowerUp only; add \$122
S	 No PowerUp modules,no
grom	mets (solid surface top)

Select locking option.

Remote must be specified separately if 'Electric lock' option (ELK) is selected.

NLK - No lock

ELK - Electric lock; add \$225

- Manual lock, keyed alike;

add \$35

MLS - Manual lock, keyed standard; add \$35

Select surface finish.

Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>.

Surface finish offerings are based on

edge style selections.

Select edge color.
Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>.
Edge color offerings are based on edge style selections.

- Select grommet/module color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 Fabrics & Finishes binder.
- Oselect enclosure color.
 Refer to the KI Color Addendum or KI
 Fabrics & Finishes binder

INFORMATION

Shipping

Worksurfaces with cutouts are shipped separately from garage units. Garage units are shipped assembled with lids pre-attached.



Smart Lift®

Worksurfaces - Poly Grommet/PowerUp

		$\overline{}$
/		





74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	
\$ 996	\$ 1044	\$ 1103	
1016	1064	1126	
1036	1085	1145	
1054	1103	N/A	

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern.
Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime.
Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Worksurfaces - Poly Grommet/PowerUp

		MODEL NU	MODEL NUMBER								
	D x W	Basic Model	Edge Style	Power Option	Grommet/ Module Location	Lock Option	Surface Finish	Edge Color	Grommet/ Module Color	Enclosure Color	Approx. Packaged Weight
	30 x 60"	ISMT3060			S						149.0#
STA.	30 x 66"	ISMT3066									156.0#
	30 x 72"	ISMT3072									161.0#
ISMT											
Double Unit											
. Logo are attached to the weekening											
 Legs are attached to the worksurface through threaded steel inserts 											
Beams and legs must be specified											
separately											
One PowerUp® module or grommet											
is available centered between the doors for double-unit 66" and 72"											
widths											
• 30" depth provides 17" leg clearance											
 Remote must be specified separately if electric lock option (ELK) is se- lected 											
• 22" PowerUp® is recommended											
when the beam is powered											
 108" PowerUp® is recommended when the beam is not powered 											
The lift, without the tilt option, can											
accommodate a VESA compliant											
monitor with a maximum size of											
3.6" deep x 19" high x 21" wide and											
maximum weight of 15 lbs • The combined keyboard and monitor											
thickness must be less than 4.8"											
thick											
The maximum depth of monitor with											
the optional tilt bracket (specified separately) is reduced by .6" to 3.0"											
A double SmartLift will receive two											
10 lb kits: includes eight 2-1/2 lb											
weights, carriage bolt and locking nut											
		A	3	Э	0	•	G	Э	•	0	I

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- ullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect edge style.

74P - 74P edge - Postformed edge ME - Urethane edge

Select top feed location.

- No top feed - Left hand top feed - Right hand top feed

Select PowerUp or grommet location.

G - Grommet only (Rectangular) - PowerUp only; add \$122 - No PowerUp modules,no grommets (solid surface top)

Select locking option.

Remote must be specified separately if 'Electric lock' option (ELK) is selected.

- No lock

- Electric lock; add \$318

- Manual lock, keyed alike;

add \$67 MLS - Manual lock, keyed standard; add \$67

Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Surface finish offerings are based on

edge style selections. **G** Select edge color. Refer to the <u>KI Color Addendum</u> or <u>KI</u>

Fabrics & Finishes binder. Edge color offerings are based on edge style selections.

Select grommet/module color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Select enclosure color. Refer to the $\underline{\text{KI Color Addendum}}$ or $\underline{\text{KI}}$ Fabrics & Finishes binder

INFORMATION

Shipping

Worksurfaces with cutouts are shipped separately from garage units. Garage units are shipped assembled with lids pre-attached.



Smart Lift®

Worksurfaces - Poly Grommet/PowerUp

$\overline{}$





74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)
\$ 1806	\$ 1891	\$ 2001
1873	1961	N/A
1939	2028	2146

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern.
Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime.
Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Smart Lift®

Worksurfaces - Villa Metal Grommet/Power Module

		MODEL N	MODEL NUMBER								
	D x W	Basic Model	Edge Style	Power Option	Grommet/ Module Location	Lock Option	Surface Finish	Edge Color	Grommet/ Module Color	Enclosure Color	Approx. Packaged Weight
	30 x 48"	IVMT3048									99.0#
4	30 x 54"	IVMT3054									106.0#
IVMT											
Single Unit											
• · · · · · · · · · · · · · · · · · ·											
Legs are attached to the worksurface											
through threaded steel inserts											
Beams and legs must be specified											
separately • One PowerUp® module or grommet											
is available in the upper right corner											
for 48" and 54" widths											
• 30" depth provides 17" leg clearance											
 Remote must be specified separately if electric lock option (ELK) is se- 											
lected											
 22" PowerUp® is recommended 											
when the beam is powered											
 108" PowerUp® is recommended when the beam is not powered 											
• The lift, without the tilt option, can											
accommodate a VESA compliant											
monitor with a maximum size of 3.6" deep x 19" high x 21" wide and											
maximum weight of 15 lbs											
The combined keyboard and monitor											
thickness must be less than 4.8"											
thick The maximum depth of monitor with											
the optional tilt bracket (specified											
separately) is reduced by .6" to 3.0"											
A single SmartLift will receive one 10 It with includes four 0.1/0 lb weights.											
Ib kit: includes four 2-1/2 lb weights, carriage bolt and locking nut											
oarrage boil and looking hat											
										_	I
		Φ	③	Θ	O	•	•	Θ	0	0	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 Indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

74P - 74P edge
PL - Postformed edge
ME - Urethane edge

Select top feed location.

N - No top feed
L - Left hand top feed
R - Right hand top feed

Select PowerUp or grommet location.

VG - One Villa grommet only; add

VG - One Villa grommet only; add \$66 VM - One Villa Module w/USB and

grommet; add \$317

OC - Cutouts only (for single

circuit use)

Select locking option.

Remote must be specified separately if 'Electric lock' option (ELK) is selected.

NLK - No lock ELK - Electric lock; add \$225 MLA - Manual lock, keyed alike; add \$35

MLS - Manual lock, keyed standard; add \$35

Select surface finish.

Refer to the <u>KI Color Addendum</u> or <u>KI</u>
<u>Fabrics & Finishes binder</u>.
Surface finish offerings are based on edge

Surface finish offerings are based on edge style selections.

GSelect edge color.

Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.

Edge color offerings are based on edge style selections.

- Select grommet/module color.
 Refer to the KI Color Addendum or KI
 Fabrics & Finishes binder.
- Select enclosure color.

 Refer to the <u>KI Color Addendum</u> or <u>KI</u>

Fabrics & Finishes binder



Worksurfaces - Villa Metal Grommet/Power Module









P Edge 4P)	Po (P	stformed Edge L)
\$ 1036	\$	1085
1054		1103

Ur (M	ethane E)	Edg
\$	1145	
	81/8	

INFORMATION

Shipping

Worksurfaces with cutouts are shipped separately from garage units. Garage units are shipped assembled with lids pre-attached.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Smart Lift®

Worksurfaces - Villa Metal Grommet/Power Module

		MODEL N	MODEL NUMBER								
	D x W	Basic Model	Edge Style	Power Option	Grommet/ Module Location	Lock Option	Surface Finish	Edge Color	Grommet/ Module Color	Enclosure Color	Approx. Packaged Weight
	30 x 66"	IVMT3066									156.0#
	30 x 72"	IVMT3072									161.0#
•											
IVMT											
Double Unit											
Legs are attached to the worksurface											
through threaded steel inserts											
Beams and legs must be specified											
separately											
 One PowerUp® module or grommet 											
is available centered between the											
doors for double-unit 66" and 72" widths											
• 30" depth provides 17" leg clearance											
Remote must be specified separately											
if electric lock option (ELK) is se-											
lected											
22" PowerUp® is recommended											
when the beam is powered108" PowerUp® is recommended											
when the beam is not powered											
The lift, without the tilt option, can											
accommodate a VESA compliant											
monitor with a maximum size of											
3.6" deep x 19" high x 21" wide and											
maximum weight of 15 lbs • The combined keyboard and monitor											
thickness must be less than 4.8"											
thick											
The maximum depth of monitor with											
the optional tilt bracket (specified											
separately) is reduced by .6" to 3.0"A double SmartLift will receive two											
A double SmartLift will receive two 10 lb kits: includes eight 2-1/2 lb											
weights, carriage bolt and locking nut											
5,g 1001111g 1141											
		A	3	Θ	O	ø	•	Θ	0	0	
		w	<u> </u>	<u> </u>	<u> </u>	<u> </u>		<u> </u>	Ψ	<u> </u>	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 □ indicate that no other alternatives
 are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- **B**Select edge style.

	0 ,	
74P	- 74P edge	
PL	 Postformed edge 	
ME	- Urethane edge	

Select top feed location

	top rood roodtron.
N	- No top feed
L	- Left hand top feed
R	- Right hand top feed

Select PowerUp or grommet location.

VG - One Villa grommet only; add

VG - One Villa grommet only; add \$66 VM - One Villa Module w/USB and

grommet; add \$317

OC - Cutouts only (for single

circuit use)

Select locking option.

Remote must be specified separately if 'Electric lock' option (ELK) is selected.

- No lock

ELK - Electric lock; add \$318

MLA - Manual lock, keyed alike; add

\$67

MLS - Manual lock, keyed standard; add \$67

• Select surface finish.

Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.
Surface finish offerings are based on edge style selections.

(c) Select edge color. Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>.

Edge color offerings are based on edge style selections.

- Select grommet/module color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 <u>Fabrics & Finishes binder</u>.
- Select enclosure color.

 Refer to the <u>KI Color Addendum</u> or <u>KI</u>

Fabrics & Finishes binder



Smart Lift®

Worksurfaces - Villa Metal Grommet/Power Module

		$\overline{}$
$ \leftarrow $		
	/,	





dge

74P Edge (74P)	Postformed Edge (PL)	Urethane E (ME)
\$ 1873	\$ 1961	N/A
1939	2028	2146

INFORMATION

Shipping

Worksurfaces with cutouts are shipped separately from garage units. Garage units are shipped assembled with lids pre-attached.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

	MODEL NUMBER		
		_	
	Basic	Approx. Packaged	
MODEL	Model	Weight	
Monitor Tilt	SMTTILT	1.0#	
+RDPT • Allows up to 10 degrees			
Adds .6" of depth to the i	monitor		
Locking Remote Control	LTREMOTE	0.1#	
HRDPT • Can order one per room	or one per		
control box • Only six remotes can be	programmed		
per controller box	programmou		
Single Counterweight Kit	SMTWEIGHT1	5.0#	
HRDPT • The weight kit will consis			
nut			
Kit allows weight to be active.	dded in 2-1/2		
lbs increments • The monitor, mouse, key	yhoard and		
counter weights used on	Smart Lift® unit		
should not exceed 15lbs			
Double Counterweight Kit	SMTWEIGHT2	10.0#	
HRDPT • The weight kit will consis		10.0#	
lbs weights, a carriage bo	olt and a locking		
nut • Kit allows weight to be ac	dded in 2-1/2		
lbs increments	uucu III 2 1/2		
The monitor, mouse, key			
counter weights used on should not exceed 15lbs			
SHOULD HOLE EXCEED TOILS			
	A		



HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.





Dali	vered ing			
DUII	voicu			
Pric	ing			
_	100			
\$	139			
φ	44			
\$	41			
\$	37			
\$	72			
\$	72			

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Stand Alone Beam - 10 Wire (6C) Beams provide cord management Includes beam end caps ITFB428/T6				MODEL NUN	/IBER				
Stand Alone Beam - 10 Wire (6C) Seams provide cord management 42" ITFB48S/T6							Annroy		
Beams provide cord management Includes beam end caps Rigid wireway provides mounting for (2) Duplex receptacles, infeeds and connectors must be ordered separately Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60°, 66° and 72° are double units Trim color is for the front access door Hispack/T6 11.0#		MODEL	w				Packaged		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60°, 66° and 72° are double units Trim color is for the front access door Middle Beam - 10 Wire (6C) Beams provide (CC) 42° ITFB36M/T6 42° ITFB42M/T6 G0° ITFB64M/T6 G0° ITFB60M/T6 G0° ITFB60M/T6 G0° ITFB60M/T6 G0° ITFB66M/T6 G0° ITFB72M/T6	. 6	Stand Alone Beam - 10 Wire (6C)	36"	ITFB36S/T6			9.5#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60°, 66" and 72" are double units Trim color is for the front access door Middle Beam - 10 Wire (6C) Beams provide cord management 42" ITFB36M/T6 ITFB42M/T6 ITFB48M/T6 ITFB4M/T6 ITFB60M/T6 ITFB60M/T6 ITFB60M/T6 ITFB72M/T6 ITFB7		Beams provide cord management Includes beam and cape	42"	ITFB42S/T6			11.0#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60°, 66° and 72° are double units Trim color is for the front access door Middle Beam - 10 Wire (6C) Beams provide cord management 42° ITFB36M/T6 H** ITFB42M/T6 G0° ITFB69M/T6 G0° ITFB60M/T6 G0° ITFB60M/T6 G0° ITFB66M/T6 G0° ITFB72M/T6		Rigid wireway provides mounting for (2)	48"	ITFB48S/T6			13.0#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) Duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60", 66" and 72" are double units Trim color is for the front access door Thin color is for the front access door		duplex receptacles per unit	54"	ITFB54S/T6			15.0#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60", 66" and 72" are double units Trim color is for the front access door Middle Beam - 10 Wire (6C) 36" ITFB36M/T6		Duplex receptacles, infeeds and connec-	60"	ITFB60S/T6			16.0#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available Co", 66" and 72" are double units TFB		tors must be ordered separately • Data covers not available	66"	ITFB66S/T6			17.0#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available Co", 66" and 72" are double units TFB		60", 66" and 72" are double units	72"	ITFB72S/T6			18.5#		
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60", 66" and 72" are double units Trim color is for the front access door Middle Beam - 10 Wire (6C) 36" ITFB36M/T6	1100	 Trim color is for the front access door 							
Middle Beam - 10 Wire (6C) Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60", 66" and 72" are double units Trim color is for the front access door Middle Beam - 10 Wire (6C) 36" ITFB36M/T6 11.0# 11.0# 13.0# 15.0# 15.0# 16.0# 17.0# 17.0# 18.5#									
Beams provide cord management Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available On, 66" and 72" are double units Trim color is for the front access door ITFB72M/T6	ГЕВ								
Does not include beam end cap Rigid wireway provides mounting for (2) duplex receptacles per unit Duplex receptacles, infeeds and connectors must be ordered separately Data covers not available 60", 66" and 72" are double units Trim color is for the front access door TFB ITFB48M/T6			36"	ITFB36M/T6			9.5#	_	
Data covers not available 60", 66" and 72" are double units Trim color is for the front access door TFB TFB72M/T6			42"	ITFB42M/T6			11.0#		
Data covers not available 60", 66" and 72" are double units Trim color is for the front access door TFB TFB72M/T6			48"	ITFB48M/T6			13.0#		
Data covers not available 60", 66" and 72" are double units Trim color is for the front access door TFB TFB72M/T6		duplex receptacles per unit	54"	ITFB54M/T6			15.0#		
Data covers not available 60", 66" and 72" are double units Trim color is for the front access door TFB TFB Data covers not available TFB72M/T6 TFB72M/T6 TFB72M/T6 TFB72M/T6			60"	ITFB60M/T6			16.0#		
• 60", 66" and 72" are double units • Trim color is for the front access door TFB			66"	ITFB66M/T6			17.0#		
TFB		 60", 66" and 72" are double units 	72"	ITFB72M/T6			18.5#		
	ГЕВ	55.5. 15 15. 2.10 110111 400000 4001							
	·· =			•	-	_			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect trim color. Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.
- Select paint color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 <u>Fabrics & Finishes binder</u>



Deliver	red
Delivere Pricing	
\$ 53	
	540
	576
63	532
101	018
106	062
115	
110	101
\$ 51	511
	519
	557
	513
	998
104	
113	134

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NU	MIDED				
			MODEL NO	VIDEN				
						Approx.		
	MODEL	w	Basic Model	Trim Color	Paint Color	Packaged Weight		
	End-of-Run/Left Beam - 10 Wire (6C)	36"	ITFB36L/T6			9.5#		
	Beams provide cord management	42"	ITFB42L/T6			11.0#		
	 Includes beam end cap Rigid wireway provides mounting for (2) 	48"	ITFB48L/T6			13.0#		
	duplex receptacles per unit	54"	ITFB54L/T6			15.0#		
		60"	ITFB60L/T6			16.0#		
	tors must be ordered separately • Data covers not available	66"	ITFB66L/T6			17.0#		
(1)	• 60", 66" and 72" are double units	72"	ITFB72L/T6			18.5#		
4.	Trim color is for the front access door							
ITFB								
	End-of-Run/Right Beam - 10 Wire (6C)	36"	ITFB36R/T6			9.5#		
	Beams provide cord managementIncludes beam end cap	42"	ITFB42R/T6			11.0#		
	Rigid wireway provides mounting for (2)	48"	ITFB48R/T6			13.0#		
	duplex receptacles per unit	54"	ITFB54R/T6			15.0#		
	 Duplex receptacles, infeeds and connectors must be ordered separately 	60"	ITFB60R/T6			16.0#		
	Data covers not available	66"	ITFB66R/T6			17.0#		
	• 60", 66" and 72" are double units	72"	ITFB72R/T6			18.5#		
·	Trim color is for the front access door							
ITFB								
			A	•	Θ			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect trim color. Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.
- Select paint color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 <u>Fabrics & Finishes binder</u>



De	livered
Pri	cing
\$	511
	519
	557
	613
	998
	1043
	1134
\$	511
	519
	557
	613
	998
	1043
	1134

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage® Non-Powered Beams

			MODEL NUM	IBER				
			mobile nom					
	MODEL	W	Basic Model	Trim Color	Paint Color	Approx. Packaged Weight		
	Stand Alone Beam - No Power (NN)	36"	ITFB36S/NN			8.0#		
	Includes beam end capsRigid beam provides wire management	42"	ITFB42S/NN			9.0#		
	Nigiti bearif provides whe management Data covers not available	48"	ITFB48S/NN			10.0#		
Pu Common	Trim color is for the front access door	54"	ITFB54S/NN			11.0#		
() W		60"	ITFB60S/NN			12.0#		
ITFB		66"	ITFB66S/NN			13.0#		
		72"	ITFB72S/NN			14.0#		
	End-of-Run/Left Beam - No Power (NN)	36"	ITFB36L/NN			8.0#		
	Includes beam end capRigid beam provides wire management	42"	ITFB42L/NN			9.0#		
	Data covers not available	48"	ITFB48L/NN			10.0#		
	Trim color is for the front access door	54"	ITFB54L/NN			11.0#		
٧		60"	ITFB60L/NN			12.0#		
ITFB		66"	ITFB66L/NN			13.0#		
		72"	ITFB72L/NN			14.0#		
	Middle Beam - No Power (NN)	36"	ITFB36M/NN			8.0#		
	 Does not include beam end cap Rigid beam provides wire management 	42"	ITFB42M/NN			9.0#		
	Data covers not available	48"	ITFB48M/NN			10.0#		
	 Trim color is for the front access door 	54"	ITFB54M/NN			11.0#		
		60"	ITFB60M/NN			12.0#		
ITFB		66"	ITFB66M/NN			13.0#		
		72"	ITFB72M/NN			14.0#		
. &	End-of-Run/Right Beam - No Power (NN)	36"	ITFB36R/NN			8.0#		
	Includes beam end capRigid beam provides wire management	42"	ITFB42R/NN			9.0#		
	Data covers not available	48"	ITFB48R/NN			10.0#		
	 Trim color is for the front access door 	54"	ITFB54R/NN			11.0#		
₩/		60"	ITFB60R/NN			12.0#		
ITFB		66"	ITFB66R/NN			13.0#		
		72"	ITFB72R/NN			14.0#		
			(A)	3	Θ			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect trim color. Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>.
- Select paint color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 <u>Fabrics & Finishes binder</u>



Flat Screen Garage® Non-Powered Beams

Γ	Delivered Control of the Control of	
F	Pricing	
	366	
	397	
	416	
	472	
	539	
	564	
	670	
\$	\$ 349 	
	376	
	397	
	452	
	518	
	545	
	649	
\$		
	376	
	397	
	452	
	518	
	545	
	649	
\$	349	
	376	
	397 450	
	452	
	518	
	545	
	649	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage®

				MODEL NUI	MIRED		
		MODEL	DxH	Basic Model	Leg Color	Approx. Packaged	
	&	Standard Flat Screen Garage® "C" Leg	30 x 29"	ITFL3029			
		 Legs will accept power infeed or data infeed, not both 	30 x 38"	ITFL3038		26.0#	
		 1-1/4" vertical glide adjustment 					
	\blacksquare	 "C" leg for Flat Screen Garage® is not interchangeable with standard InTandem® 					
		leg					
ITFL	v	Only one leg is included in a kit					
		ADA "C" Leg	32 x 32"	ITFLADA		20.0#	
		 Provided with two 3" locking casters per leg to achieve finished table height of 					
		32"					
_]	For use with 32" deep surfaces only Only one log is included in a kit.					
6		Only one leg is included in a kit					
ITFL							
				A	•		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect leg color. Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 <u>Fabrics & Finishes binder</u>



Flat Screen Garage® "C" Legs

Delivered Pricing

\$ 232

244

\$ 272

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N,

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage®

Flectrical

		MODEL NUM	BER			
	MODEL	Basic Model	Paint Color	Approx. Packaged Weight		
®	Infrared Receiver Order one per table	FSGRECEIVER		1.0#		
HRDPT	Order one per table					
	Infrared Remote Control Unit	FSGREMOTE		1.0#		
8	 Order one per room, plus duplicates if desired 					
	uesneu					
LIDDDT						
HRDPT	Floor Infeed 10-Wire	PTFF		5.0#		
	Provides power from fixed floor or wall sources to table power distribution system 105" infeed length Designed to pass through the standard Flat Screen Garage® leg cover			3.0#		
HRDPT						
	Overhead Infeed Circuit Pre-wired	PCOF.T6		15.0#		
HRDPT	 Provides power from ceiling source to table distribution system Includes 10' long aluminum pole with separate channel for electrical and data entry and prewired harness 					
	8-Wire to 10-Wire Adaptor	47.0568.20		1.0#		
Company of the second	• 20" long					
HRDPT						
		A	3			

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- Select paint color.

 Refer to the <u>KI Color Addendum</u> or <u>KI</u>

 <u>Fabrics & Finishes binder</u>

INFORMATION

Infrared Receiver

Works with, and must be ordered with an Infrared Remote Control Unit to lock down or unlock a room of tables featuring flatscreen garage units. One receiver is attached to each table and can receive a signal for up to two garage units.

Infrared Remote Control

Sends locking and unlocking signals to receivers and can also be used to raise and lower multiple units at once.

Floor Infeed (10-Wire)

Two 90° connectors. Flexible steel conduit with eight 12-gauge conductors in the leg. Includes steel trim plate with dual holes for electrical and data entry and six feet of liquid-tight flexible conduit .8315 diameter.

Overhead Infeed Circuit Pre-wired

Aluminum pole is 10ft. in length. Flexible steel conduit with ten 12-gauge conductors.

Includes ceiling trim plate.



Flat Screen Garage® Electrical

Deli	ivered sing 94
\$	94
Ψ	OT
\$	110
Ŧ	
\$	146
τ	
\$	556
\$	141

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage®

			MODEL NUMBER		
	MODEL	Features	Basic Model	Approx. Packaged Weight	
	Worksurface-to-Worksurface 10-Wire		46.0782.24	1.0#	
	• Connects the 10-wire power system of				
A	two adjoining tables				
HRDPT	• 18" long				
	Quad-Block		4BT6	1.0#	
	 Allows power to be distributed from the middle of a table series The Quad-block (along with included jumper) enables infeed power from the building to be routed in two directions. These units four female openings accept the male end of the power infeed and the male plug ends of two table-to-table jumpers which transfer the power to the two adjoining tables. 				
HRDPT					
TINDITI					
<u> </u>	Receptacles - 6 Circuit	Circuit 1	47.0706.1.BL	1.0#	
	 Attaches to wireways of 10 wire powered tables Provides two (duplex) receptacles each rated at 15 amps Some circuits are isolated ground circuits (622 - 4,5, & 6), Isolated ground 	Circuit 2	47.0706.2.BL	1.0#	
		Circuit 3	47.0706.3.BL	1.0#	
		Circuit 4	47.0706.4I.BL	1.0#	
HRDPT		Circuit 5	47.0706.5I.BL	1.0#	
	receptacles are identified by an orange	Circuit 6	47.0706.6I.BL	1.0#	
	triangle				



HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



Flat Screen Garage® Electrical

Daliv	orad
Delive Pricir	ereu
Pricir	nq
_	
\$	81
\$	40
Ψ	
\$	24
	24
	24
	24
	24
	24
	24

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage® Rectangular Privacy Screens

			MODEL N	UMBER			
			Basic	Surface	Approx. Packaged		
	MODEL	H x W	Model	Finish	Weight		
		11 x 36"	ITFP1136		14.0#		
	Privacy screen brackets and hardware	11 x 42"	ITFP1142		16.0#		
	supplied in Graphite Dark only 60", 66", and 72" screens are made up	11 x 48"	ITFP1148		17.0#		
	of 2 screens	11 x 54"	ITFP1154		19.0#		
	Laminate with matching edge band	11 x 60"	ITFP1160		23.0#		
4		11 x 66"	ITFP1166		25.0#		
ITFP		11 x 72"	ITFP1172		26.0#		
	Rectangular Privacy Screens - 17" Height	17 x 36"	ITFP1736		20.0#		
	Privacy screen brackets and hardware Privacy screen brackets and hardware Privacy screen brackets and hardware Privacy screen brackets and hardware	17 x 42"	ITFP1742		23.0#		
	supplied in Graphite Dark only 60", 66", and 72" screens are made up of 2 screens Laminate with matching edge band	17 x 48"	ITFP1748		26.0#		
		17 x 54"	ITFP1754		29.0#		
		17 x 60"	ITFP1760		32.0#		
		17 x 66"	ITFP1766		36.0#		
ITFP		17 x 72"	ITFP1772		38.0#		
		23 x 36"	ITFP2336		26.0#		
	 Privacy screen brackets and hardware supplied in Graphite Dark only 	23 x 42"	ITFP2342		30.0#		
	 60", 66", and 72" screens are made up 	23 x 48"	ITFP2348		34.0#		
	of 2 screens	23 x 54"	ITFP2354		38.0#		
	 Laminate with matching edge band 	23 x 60"	ITFP2360		42.0#		
		23 x 66"	ITFP2366		47.0#		
		23 x 72"	ITFP2372		49.0#		
ITFP							
			A	3			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect surface finish. Refer to the $\underline{\text{KI Color Addendum}}$ or $\underline{\text{KI}}$ Fabrics & Finishes binder.

style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by Surface finish offerings are based on edge the supplier's color/pattern code:

> Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

> KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



Flat Screen Garage® Rectangular Privacy Screens

Daliv	ivered
Prici	ing
	212
	237
	240
	267
	365
	397
	398
	237
	269
	272
	306
	410
	446
	449
	258
	294
	299
	338
	446
	487
	490

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage® Stand Alone Privacy Screen

			MODEL NU	IMBER		
	MODEL	H x W	Basic Model	Surface Finish	Approx. Packaged Weight	
	Rectangular Stand Alone Privacy Screens	11 x 36"	ITFPA1136		14.0#	
	- 11" Height	11 x 42"	ITFPA1142		16.0#	
	 Stand Alone screens are positioned along the back side of the table (length). 	11 x 48"	ITFPA1148		17.0#	
	No divider screens attached	11 x 54"	ITFPA1154		19.0#	
	 Privacy screen brackets and hardware 	11 x 60"	ITFPA1160		23.0#	
W	supplied in Graphite Dark only 60", 66", and 72" screens are made up of 2 screens	11 x 66"	ITFPA1166		25.0#	
ITFP		11 x 72"	ITFPA1172		26.0#	
	Laminate with matching edge band					
	Rectangular Stand Alone Privacy Screens	17 x 36"	ITFPA1736		20.0#	
	 17" Height Stand Alone screens are positioned along the back side of the table (length). No divider screens attached Privacy screen brackets and hardware 	17 x 42"	ITFPA1742		23.0#	
		17 x 48"	ITFPA1748		26.0#	
		17 x 54"	ITFPA1754		29.0#	
•		17 x 60"	ITFPA1760		32.0#	
	supplied in Graphite Dark only	17 x 66"	ITFPA1766		36.0#	
=	 60", 66", and 72" screens are made up of 2 screens 	17 x 72"	ITFPA1772		38.0#	
ITFP	Stand Alone privacy screens are not					
	available in 23" height					
	Laminate with matching edge band					
			A	B		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- **B**Select surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



Flat Screen Garage® Stand Alone Privacy Screen

Delivered Pricing	
\$ 219	
243	
245	
272	
372	
404	
405	
Ф 040	
\$ 243 277	
282	
314	
418	
452	
454	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage®

Divider Screens

			MODEL NUI	MBER		
	MODEL	H x W	Basic Model	Surface Finish	Approx. Packaged Weight	
	End Divider Screens - 11" Height • Divider screen brackets and hardware	11 x 30"	ITDV1130/E		13.0#	
	supplied in Graphite Dark only					
	 Must be used in conjunction with privacy screen 					
	Laminate with matching edge band					
ITDV						
	End Divider Screens - 17" Height Divider screen brackets and hardware supplied in Graphite Dark only Must be used in conjunction with privacy screen	17 x 30"	ITDV1730/E		17.0#	
	Laminate with matching edge band					
ITDV						
TIDV	End Divider Screens - 23" Height	23 x 30"	ITDV2330/E		22.0#	
	Divider screen brackets and hardware supplied in Graphite Dark only					
	Must be used in conjunction with privacy					
•	screenLaminate with matching edge band					
	Laminate with matching edge band					
ITDV						
			Ø	3		

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- Select surface finish.

 Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>.

 Surface finish offerings are based on edge style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



Flat Screen Garage® Divider Screens

Delivered Pricing
ricing
\$ 225
\$ 245
S 267

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N,

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flat Screen Garage®

Divider Screens

			MODEL NUMBE	R		
			Basic	Surface	Approx.	
	MODEL	H x W	Model	Finish	Packaged Weight	
	Middle Divider Screens - 11" Height	11 x 30"	ITDV1130/M74P		13.0#	
	 Divider screen brackets and hardware 	11 x 30"	ITDV1130/MME		13.0#	
	supplied in Graphite Dark only	11 x 30"	ITDV1130/MPL		13.0#	
	Must be used in conjunction with privacy screen					
	Laminate with matching edge band					
ITDV						
	Middle Divider Screens - 11" Height • Divider screen brackets and hardware	17 x 30"	ITDV1730/M74P		17.0#	
		17 x 30"	ITDV1730/MME		17.0#	
	supplied in Graphite Dark only • Must be used in conjunction with privacy	17 x 30"	ITDV1730/MPL		17.0#	
	screen					
	Laminate with matching edge band					
25						
ITDV						
	Middle Divider Screens - 23" Height	23 x 30"	ITDV2330/M74P		22.0#	
	Divider screen brackets and hardware supplied in Graphite Dark only	23 x 30"	ITDV2330/MME		22.0#	
	Must be used in conjunction with priva-	23 x 30"	ITDV2330/MPL		22.0#	
	cyscreen					
	23" height divider screens are not avail-					
	able on 24" deep worksurfaces • Laminate with matching edge band					
***	g ougo build					
ITDV						
			A	•		
			•	_		

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- Select surface finish.

 Refer to the <u>KI Color Addendum</u> or <u>KI Fabrics & Finishes binder</u>.

 Surface finish offerings are based on edge style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



Flat Screen Garage® Divider Screens

Deliv Pric	livered cing
\$	239
	239
	239
_	
	261
	261 261
	201
\$	279
	279
	279

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System

General Information







Back-to-Back	Configuration
--------------	---------------

Carrel Configuration

Classroom Configuration

Features			
Rectangular worksurfaces	•	•	•
Square or transitional corner worksurfaces	•	•	•
Postformed laminate or urethane edge styles	•	•	•
10-wire power, hard-wire power, non-powered or NY infeed beam options	•	•	•
Optional data covers to conceal data wires	•	•	•
"C" legs in 27", 29", and 38" worksurface heights	•	•	•
10-wire, 6-circuit pre-wired electrical system	•	•	•
Floor or overhead power infeeds available in 8-wire or hard wire	•	•	•
Keyboards, CPU holders, security kits and wheelchair kits available	•	•	•

SPECIFICATIONS

Worksurfaces

Horizontal worksurfaces are constructed of 1-1/8" thick 45# density particleboard with .030 thick high-pressure laminate and .030 thick high-pressure backing sheet. Overall thickness is 1-1/4".

There are three choices of edges offered for InTandem®: (74P); Urethane (ME); and Postformed (PL).

Grommets are standard 5-3/4" x 2-1/4" and have a flip-up receding door. Grommets are the same size as PowerUp® modules to allow for retrofitting.

Dual-Door Beam

Lay-in access to data cables from the back side of the desk. Access to power and data cables is also available from the front. Beam doors are constructed of .06" thick dual durometer extrusion and pivot at the bottom. Electrical trough is constructed of 16-gauge

formed steel. Openings on the back have a 16-gauge steel removable outlet cover. With hard-wire power, the top raceway is covered by a 20-gauge formed steel cover with holes for simplex receptacles. Wiring and connections are supplied by the electrician.

Data trough is constructed of 16-gauge steel. Terminated end of data cables snap into prepunched holes in the data trough. Multiple data plates also snap into the data trough. The customer provides data jacks and data plates. An optional data cover can be specified to cover the data trough. Data cover is constructed of 24-gauge steel. Standard ABS plastic beam end caps enclose the wires on end-of-run and stand-alone beams. Middle and corner middle beam assemblies do not include end caps.

Legs

All legs have vertical wire management capabilities. A reversible vertical wireway is standard on each leg. Steel trim with liquid-tight fittings are available for power infeeds at the bottom of any leg. All legs can

be retrofitted in the field. All "C" legs can be used as either end legs or shared legs. "C" legs are used when connecting tables in a row. Vertical leg tube is 2" x 5", 14-gauge formed steel. Nylon glide under toe casting can be adjusted vertically 1-1/4".

Corner Worksurface Support Leg

Square-shaped leg for transitional corner surface is 2" x 2", 14-gauge steel. One leg is required per worksurface. Wire management is not available on this leg.

Freestanding Frames with Casters

Available on 30" depth worksurfaces only. Model number includes a stand-alone beam with right and left end caps, two "C" legs and four 2-3/4" diameter dual wheel locking, black, carpet casters. The stand-alone beam is not available with 10-Wire, hard-wire, communications outlets or data raceway covers. An optional surge protected six-outlet, 110 volt electrical strip with a six foot cord is available to lay in the beam. Freestanding frames with casters are not UL listed.

PowerUp®

PowerUp® is a UL Listed, relocatable power tap, which mounts flush into the table top. When flipped up, (cover open), one duplex receptacle and two data ports are exposed. PowerUp® is UL Listed (UL1363) as a Temporary Power Tap.

The PowerUp® module is 7" long x 3-1/2" wide x 2-1/2" high and fits securely into a 6-1/4" x 3" cutout, still allowing removal without tools. The module is constructed of polycarbonate with a textured finish, meeting UL-VO minimum requirements. The module has two receptacles, rated at 15 Amps/125 Volts and two locations for data connectors. Snap-in data plates hold data connectors and allow the standard module to accommodate most manufacturers. The data connectors are not supplied with the module and are purchased by the customer.

The module has a dampened spring-loaded mechanism allowing the unit to open for use and close when not in use. The power receptacles open above the plane of the

14

InTandem® Table System

General Information



PowerUp® Module



Closed Grommet



Open Grommet



Back-to-Back Power Access



Beam - Front



Beam - Back



Beam - Interior



Power Infeed



Data Cable Entry



Top Feed



Table-to-Table Connection



Privacy and Divider Screens



Keyboard Tray



CPU Holder



Wheelchair Kit

worksurface to avoid accidental spills into the receptacle. Data jacks remain stationary to avoid excess wear and tear on the wire connections and promote transmission of data communication. Data ports are molded to accept RJ45 jacks, but can be modified to accept various brands of jacks. The module comes standard with either a 22", 108", or 180" cord and 3-prong plug.

10-Wire Pre-wired Harness

The wiring configurations of the 810-wire systems are as follows: 622-Six hot conductors (12-gauge), two neutral conductors (10-gauge) and two grounds (12-gauge). System provides four 20 amp, 125 volt capacity circuits. All receptacles are rated at 15 amps, 125 volt capacity. Connection diagrams are available. Pre-wired harness plugs into the adjacent table harness for table reconfiguration.

10-Wire Harness - T-Shaped

10-Wire electrical harness of galvanized steel is available for T-shaped configurations. Available for 24", 30" deep worksur-

faces.

10-Wire Harness - Back-To-Back

10-Wire electrical harness of galvanized steel is available for back-to-back configurations. Available for all width tables.

End-of-Run Beam - NY 10-Wire Infeed

The City of New York 10-Wire Infeed uses a power infeed table beam supplied with a service entry box. Box is 2.25 cubic inches for each of the 10 wires entering from source and leaving to pre-wired harness system. Includes steel trim plate with dual holes for electrical and data entry and six feet of liquid-tight flexible conduit .83 diameter.

Communications Circuitry

Data connectors and wiring must be ordered separately by the customer.

Privacy Screens

Standard 3/4" thick core material. Both sides are laminated with .030" thick high-pressure laminate as standard. All edges are banded with edging. Available in three heights with a

straight top edge.

Divider Screens

Standard 3/4" thick core material. Both sides are laminated with .030" thick high-pressure laminate as standard. All edges are banded with edging. Available in three heights with a curved top. Dividers are available only in conjunction with privacy screens.

Wheelchair Accessible Kit

Made of 11-gauge steel. Designed for easy retrofit of existing InTandem® units. Available in widths of 42" through 72" and in 29" height to make the overall surface height 32". Standard to fit 30" deep worksurface and the support arms.

*Note: Wheelchair kits for 42" wide tables can only be used when at least one of the legs of the ADA table are in the shared position (one leg shared with an adjoining table).

INFORMATION

Warranty

Refer to KI Terms & Conditions document or visit ki.com

UL Listing

The InTandem Table System is Listed to applicable UL Standards and requirements by Underwriters Laboratories, Inc. Two of the Standards used to evaluate InTandem Table Units are UL 1286, Office Furnishings and UL 723, Standard for Test for Surface Burning Characteristics of Building Materials. The freestanding frames with casters are not included in the Listed System.

		MODEL NUMBER								
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
^	Rectangular (Non-Powered Beam)-Two	24 x 24"	ITWS2424/NB			□ □				22.0#
•	Grommets 1-1/4" solid core top with plastic laminate surface	24 x 30"	ITWS2430/NB							26.0#
4		24 x 36"	ITWS2436/NB							31.0#
		24 x 42"	ITWS2442/NB							36.0#
ITWS	 2-1/4" x 5-3/4" grommet for wire man- agement is standard 	24 x 48"	ITWS2448/NB							41.0#
	PowerUp® module can be ordered in	24 x 54"	ITWS2454/NB							46.0#
	place of grommet	24 x 60"	ITWS2460/NB							51.0#
	 Legs are attached to the worksurface through threaded steel inserts 	24 x 66"	ITWS2466/NB		_					56.0#
	PowerUp® modules with non-powered	24 x 72"	ITWS2472/NB							61.0#
	beams include a 108" cord	30 x 24"	ITWS3024/NB							26.0#
	 Beams and legs must be specified separately 	30 x 30"	ITWS3030/NB							32.0#
	Suparatory	30 x 36"	ITWS3036/NB							38.0#
		30 x 42"	ITWS3042/NB							40.0#
		30 x 48"	ITWS3048/NB							50.0#
		30 x 54"	ITWS3054/NB							57.0#
		30 x 60"	ITWS3060/NB							63.0#
		30 x 66"	ITWS3066/NB							70.0#
		30 x 72"	ITWS3072/NB							75.0#
	Rectangular (Non-Powered Beam)-Four	24 x 60"	ITWQ2460/NB		_					51.0#
	Grommets	24 x 66"	ITWQ2466/NB							56.0#
4	 1-1/4" solid core top with plastic lami- nate surface 	24 x 72"	ITWQ2472/NB		_					61.0#
	• 2-1/4" x 5-3/4" grommet for wire management is standard	30 x 60"	ITWQ3060/NB							63.0#
		30 x 66"	ITWQ3066/NB							70.0#
ITWS	 PowerUp® module can be ordered in place of grommet 	30 x 72"	ITWQ3072/NB							75.0#
	Legs are attached to the worksurface									
	through threaded steel inserts									
	 PowerUp[®] modules with non-powered beams include a 108" cord 									
	Beams and legs must be specified									
	separately									
			Δ	B	Θ	0	•	•	Θ	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

- 74P edge 74P - Postformed edge ME - Urethane edge

Select top power feed.

\$235

- No power - Left power - Right power

• Select number of PowerUp modules.

- No PowerUp module - One PowerUp module; add \$119 - Two PowerUp modules; add

Select PowerUp module/grommet color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder

Select surface finish.

Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Edge color offerings are based on edge style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	
\$ 267	\$ 286	N/A	
277	294	N/A	
299	318	410	
326	345	439	
334	354	454	
408	426	N/A	
443	461	512	
448	466	543	
454	473	570	
277	294	N/A	
289	306	N/A	
311	328	448	
350	365	481	
358	377	496	
428	446	N/A	
453	471	561	
466	483	N/A	
468	485	629	
\$ 462	\$ 480	\$ 512	
466	483	543	
467	484	589	
473	491	561	
481	500	N/A	
489	505	643	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUMBER							
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
\&	Rectangular (Powered Beam)-Two	24 x 24"	ITWS2424/PB							22.0#
	Grommets • 1-1/4" solid core top with plastic lami-	24 x 30"	ITWS2430/PB							26.0#
	nate surface	24 x 36"	ITWS2436/PB							31.0#
*	• 2-1/4" x 5-3/4" grommet for wire man-	24 x 42"	ITWS2442/PB							36.0#
ITWS	agement is standard	24 x 48"	ITWS2448/PB							41.0#
	 PowerUp[®] module can be ordered in place of grommet 	24 x 54"	ITWS2454/PB							46.0#
	 Legs are attached to the worksurface 	24 x 60"	ITWS2460/PB							51.0#
	through threaded steel inserts	24 x 66"	ITWS2466/PB							56.0#
	 PowerUp® modules with powered beams include a 22" cord 		ITWS2472/PB							61.0#
	Beams and legs must be specified	30 x 24"	ITWS3024/PB							26.0#
	separately	30 x 30"	ITWS3030/PB							32.0# 38.0#
		30 x 36" 30 x 42"	ITWS3036/PB ITWS3042/PB		_					38.0# 40.0#
		30 x 42	ITWS3042/PB							40.0# 50.0#
		30 x 46	ITWS3046/PB							50.0# 57.0#
		30 x 60"	ITWS3054/FB							63.0#
		30 x 66"	ITWS3066/PB							70.0#
		30 x 72"	ITWS3072/PB							75.0#
	Rectangular (Powered Beam)-Four	24 x 60"	ITWQ2460/PB							51.0#
Rectangular (Powere Grommets 1-1/4" solid core to nate surface 2-1/4" x 5-3/4" groi		24 x 66"	ITWQ2466/PB							56.0#
4	 1-1/4" solid core top with plastic lami- 	24 x 72"	ITWQ2472/PB							61.0#
•	nate surface • 2-1/4" x 5-3/4" grommet for wire management is standard	30 x 60"	ITWQ3060/PB							63.0#
		30 x 66"	ITWQ3066/PB							70.0#
ITWS	 PowerUp[®] module can be ordered in 	30 x 72"	ITWQ3072/PB							75.0#
	place of grommetLegs are attached to the worksurface									
	through threaded steel inserts									
	 PowerUp® modules with powered beams include a 22" cord 									
	Beams and legs must be specified separately									
	copulatory									
			Ø	•	Θ	O	•	•	Ө	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect edge style.

\$200

- 74P edge 74P - Postformed edge ME - Urethane edge

Select top power feed.

- No power - Left power - Right power

• Select number of PowerUp modules.

- No PowerUp module - One PowerUp module; add \$100 - Two PowerUp modules; add

Select PowerUp module/grommet color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder

Select surface finish.

edge style selections.

Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder. Surface finish offerings are based on

edge style selections.

GSelect edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Edge color offerings are based on

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)	
\$ 267	\$ 286	N/A	
277	294	N/A	
299	318	410	
326	345	439	
334	354	454	
408	426	N/A	
443	461	512	
448	466	543	
454	473	570	
277	294	N/A	
289	306	N/A	
311	328	448	
350	365	481	
358	377	496	
428	446	N/A	
453	471	561	
466	483	N/A	
468	485	629	
\$ 462	\$ 480	\$ 512	
466	483	543	
467	484	589	
473	491	561	
481	500	N/A	
489	505	643	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUM	DED						
					Тор	No. of	Grommet/			Approx.
	MODEL	D x W	Basic Model	Edge Style	Power Feed	PowerUp Modules	Module Color	Surface Finish	Edge Color	Packaged Weight
<u></u>	Corner (Non-Powered Beam) Square	24 x 24"	ITSC2424/NB							22.0#
	One support leg required per corner surface to be ordered separately	30 x 30"	ITSC3030/NB							32.0#
	Corner surfaces are not available with									
*	urethane edge									
VS	Square corners are not available with powered beams									
	Square corners are not available with									
	PowerUp® modules									
	Square corner surfaces have all four									
	edges covered with matching flat .024" edge banding									
	Corner (Non-Powered Beam) Transitional One support leg required per corner surface to be ordered separately	24 x 36"	ITTC2436/NB							45.0#
		24 x 42"	ITTC2442/NB							62.0#
		30 x 42"	ITTC3042/NB							62.0#
"	Corner surfaces are not available with									
	urethane edge									
• Transitional corners come standard with										
	two grommets • Transitional corner surfaces have edges									
	on side and rear covered with matching									
	flat .024" edge banding									
			Δ	(3)	Θ	O	(3	(a)	Ø	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.
 - 74P edge - Postformed edge
- Select top power feed.
 - No power Left power - Right power
- Select number of PowerUp modules.
 - No PowerUp module 0 - One PowerUp module; add \$119 - Two PowerUp modules; add \$235
- Select PowerUp module/grommet color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder
- Select surface finish.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Edge color offerings are based on

edge style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



InTandem® Table System Worksurfaces - Poly Grommet/PowerUp





741 (74	P Edge IP)	Postformed Edç (PL)
\$	397	\$ 413
	448	466

\$ 723	\$ 741
862	879
994	1013

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Worksurfaces - Poly Grommet/PowerUp

			MODEL NUM	IBER						
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
\&	Corner (Powered Beam) Transitional	24 x 36"	ITTC2436/PB							45.0#
	 One support leg required per corner surface to be ordered separately 	24 x 42"	ITTC2442/PB							62.0#
	Corner surfaces are not available with	30 x 42"	ITTC3042/PB							62.0#
V	urethane edge									
	Transitional corners come standard with									
ITWS	two grommetsTransitional corner surfaces have edges									
	on side and rear covered with matching									
	flat .024" edge banding									
			0	3	0	0	•	•	Ѳ	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

74P - 74P edge - Postformed edge

Select top power feed.

- No power - Left power - Right power

• Select number of PowerUp modules.

- No PowerUp module - One PowerUp module; add \$100 - Two PowerUp modules; add \$200

- Select PowerUp module/grommet color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder
- Select surface finish.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Edge color offerings are based on

edge style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.



InTandem® Table System Worksurfaces - Poly Grommet/PowerUp





74F (74	P Edge P)	Po (Pl	stformed L)	Edg
\$	723	\$	741	
	862		879	
	994		1013	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUME	BER						
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
	Rectangular (Non-Powered Beam)-Two Grommets	24 x 24"	IVWS2424/NB							22.0#
		24 x 30"	IVWS2430/NB							26.0#
	 1-1/4" solid core top with plastic lami- nate surface 	24 x 36"	IVWS2436/NB							31.0#
*	• 2-1/4" x 5-3/4" metal grommet for wire	24 x 42"	IVWS2442/NB							36.0#
IVWS	management is standard Power module can be ordered in place of metal grommet Legs are attached to the worksurface through threaded steel inserts Power modules with non-powered beams include a 108" cord	24 x 48"	IVWS2448/NB							41.0#
		· .	IVWS2454/NB							46.0#
		24 x 60"	IVWS2460/NB		_					51.0#
		24 x 66"	IVWS2466/NB							56.0#
		24 x 72"	IVWS2472/NB							61.0#
	Beams and legs must be specified	30 x 24"	IVWS3024/NB							26.0#
	separately	30 x 30"	IVWS3030/NB							32.0#
		30 x 36"	IVWS3036/NB							38.0#
		30 x 42"	IVWS3042/NB							40.0#
		30 x 48"	IVWS3048/NB							50.0#
		30 x 54"	IVWS3054/NB							57.0#
		30 x 60"	IVWS3060/NB							63.0#
		30 x 66"	IVWS3066/NB							70.0#
		30 x 72"	IVWS3072/NB							75.0#
			A	B	Θ	O	•	•	Θ	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

74P - 74P edge - Postformed edge ME - Urethane edge

Select top power feed.

- No power - Left power R - Right power

• Select number of power modules. No Villa modules on 24" wide worksurfaces (grommets only)

- No power module (two metal Villa grommets only); add \$132

- One Villa module w/USB and grommet and one Villa grommet; add

- Two Villa modules w/USB and grommets; add \$633 - Cutouts only (for single

circuit use)

- Select power module/grommet color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u> Fabrics & Finishes binder.
- Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Surface finish offerings are based on edge style selections.
- **G**Select edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Edge color offerings are based on edge style selections.



74P Edge (74P)	Postformed Edge (PL)	Urethane Edge (ME)
\$ 267	\$ 286	N/A
277	294	N/A
299	318	410
326	345	439
334	354	454
408	426	N/A
443	461	512
448	466	543
454	473	570
277	294	N/A
289	306	N/A
311	328	448
350	365	481
358	377	496
428	446	N/A
453	471	561
466	483	N/A
468	485	629

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUMI	BER						
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
	Rectangular (Powered Beam)-Two Grommets	24 x 24"	IVWS2424/PB							22.0#
		24 x 30"	IVWS2430/PB							26.0#
	 1-1/4" solid core top with plastic lami- nate surface 	24 x 36"	IVWS2436/PB							31.0#
~	2-1/4" x 5-3/4" metal grommet for wire	24 x 42"	IVWS2442/PB							36.0#
IVWS		24 x 48"	IVWS2448/PB							41.0#
		24 x 54"	IVWS2454/PB							46.0#
		24 x 60"	IVWS2460/PB		_					51.0#
	through threaded steel inserts		IVWS2466/PB							56.0#
	Power modules with powered beams	24 x 72"	IVWS2472/PB							61.0#
	 include a 36" cord Beams and legs must be specified 	30 x 24"	IVWS3024/PB							26.0#
	separately	30 x 30"	IVWS3030/PB							32.0#
		30 x 36"	IVWS3036/PB							38.0#
		30 x 42"	IVWS3042/PB							40.0#
		30 x 48"	IVWS3048/PB							50.0#
		30 x 54"	IVWS3054/PB							57.0#
		30 x 60"	IVWS3060/PB							63.0#
		30 x 66"	IVWS3066/PB							70.0#
		30 x 72"	IVWS3072/PB							75.0#
			A	3	Θ	0	•	(3	Θ	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

- 74P edge 74P - Postformed edge ME - Urethane edge

Select top power feed.

- No power - Left power - Right power

• Select number of power modules. No Villa modules on 24" wide worksurfaces (grommets only)

- No power module (two metal Villa grommets only); add \$132

- One Villa module w/USB and grommet and one Villa grommet; add

- Two Villa modules w/USB and grommets; add \$633

- Cutouts only (for single

circuit use)

- Select power module/grommet color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.
- Select surface finish. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Surface finish offerings are based on edge style selections.
- **G**Select edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder. Edge color offerings are based on edge

style selections.



74P Ed (74P)	dge Postforme (PL)	d Edge Urethane Edge (ME)
	67 \$ 286	N/A
	77 294	N/A
	99 318	410
	26 345	439
	34 354	454
	08 426	N/A
	43 461	512
	48 466	543
	54 473 77 294	570 N/A
	89 306	N/A
	11 328	448
	50 365	481
	58 377	496
	28 446	N/A
	53 471	561
46	66 483	N/A
46	68 485	629

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime.
Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUM	BER						
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
	Corner (Non-Powered Beam) Transitional One support leg required per corner surface to be ordered separately	24 x 36"	IVTC2436/NB							45.0#
		24 x 42"	IVTC2442/NB							62.0#
		30 x 42"	IVTC3042/NB							62.0#
"	Corner surfaces are not available with									
	urethane edge Transitional corners come standard with									
VWS										
	two metal grommets									
	 Transitional corner surfaces have edges on side and rear covered with matching 									
	flat .024" edge banding									
	- 0		A	•	•	• • • • • • • • • • • • • • • • • • •	(3	a	Э	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

- 74P edge - Postformed edge

Select top power feed.

- No power - Left power - Right power

OV - No power modules.

OV - No power module (two metal Villa grommets only); add \$132

1V - One Villa module w/USB and

grommet and one Villa grommet; add

- Two Villa modules w/USB and grommets; add \$633

- Cutouts only (for single circuit use)

• Select power module/grommet color.

Refer to the $\underline{\text{KI Color Addendum}}$ or $\underline{\text{KI}}$ Fabrics & Finishes binder.

Select surface finish. Refer to the $\underline{\text{KI Color Addendum}}$ or $\underline{\text{KI}}$ Fabrics & Finishes binder.

Surface finish offerings are based on edge style selections.

GSelect edge color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Edge color offerings are based on edge style selections.







74P (74I	Edge P)		Pos (PL	tformed)	Edge
\$	723		\$	741	
	862			879	
	994			1013	

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUM	BER						
	MODEL	D x W	Basic Model	Edge Style	Top Power Feed	No. of PowerUp Modules	Grommet/ Module Color	Surface Finish	Edge Color	Approx. Packaged Weight
	Corner (Powered Beam) Transitional	24 x 36"	IVTC2436/PB							45.0#
surface to be ordered separately		24 x 42"	IVTC2442/PB							62.0#
	Corner surfaces are not available with	30 x 42"	IVTC3042/PB							62.0#
	urethane edge									
	 Transitional corners come standard with 									
IVWS	two metal grommets Transitional corner surfaces have edges									
	on side and rear covered with matching									
	flat .024" edge banding									
			Ø	3	Θ	Ð	•	•	Θ	

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect edge style.

74P - 74P edge
PL - Postforme - Postformed edge

Select top power feed.

- No power - Left power - Right power

• Select number of power modules.

OV - No power module (two metal Villa grommets only); add \$132

- One Villa module w/USB and grommet and one Villa grommet; add

- Two Villa modules w/USB and

grommets; add \$633 - Cutouts only (for single circuit use)

Select power module/grommet color.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Select surface finish. Refer to the $\underline{\text{KI Color Addendum}}$ or $\underline{\text{KI}}$ Fabrics & Finishes binder.


Surface finish offerings are based on edge style selections.

GSelect edge color.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Edge color offerings are based on edge style selections.





74P Edge (74P)	Postformed Edge (PL)
\$ 723	\$ 741
862	879
994	1013

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code

KI's standard finish is the supplier's recommended finish for that color/pattern. Note: Nonstandard laminates from these suppliers (example: textured laminates), require an upcharge and additional leadtime. Contact KI.

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

				MODEL NUMB	ER		
	MODEL	Features	W	Basic Model	Beam Color	Approx. Packaged Weight	
	End-of-Run Stand Alone Beam - 10-Wire		24"	ITSB24/T6/ND		7.0#	
₩ V	(T6) - Without Data Cover (ND)		30"	ITSB30/T6/ND		8.0#	
	Includes beam end capsData jacks/connectors, connection plates		36"	ITSB36/T6/ND		9.0#	
	and wiring are not included. Beams are		42"	ITSB42/T6/ND		11.0#	
4	pre-punction to accept most data plates.		48"	ITSB48/T6/ND		12.0#	
	Duplex receptacles, infeeds and connectors must be ordered separately (see Electrical section)		54"	ITSB54/T6/ND		14.0#	
TSB			60"	ITSB60/T6/ND		18.0#	
			66"	ITSB66/T6/ND		21.0#	
			72"	ITSB72/T6/ND		23.0#	
		Quad	60"	ITSQ60/T6/ND		19.0#	
		Quad	66"	ITSQ66/T6/ND		22.0#	
		Quad	72"	ITSQ72/T6/ND		24.0#	
	End-of-Run Stand Alone Beam - Hard-		24"	ITSB24/HC/ND		5.0#	
	Wire (HC) - Without Data Cover (ND)		30"	ITSB30/HC/ND		6.0#	
	 Includes beam end caps Hard-wire beams include simplex recep- 		36"	ITSB36/HC/ND		7.0#	
	tacles		42"	ITSB42/HC/ND		9.0#	
	Must specify hard-wire infeed separately		48"	ITSB48/HC/ND		10.0#	
	 Electrician to supply wires and connectors 		54"	ITSB54/HC/ND		12.0#	
TSB	tors		60"	ITSB60/HC/ND		13.0#	
			66"	ITSB66/HC/ND		15.0#	
			72"	ITSB72/HC/ND		19.0#	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect beam color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder

Beam Receptacle Requirements

	10-Wire	Hard-Wire
Beam Length	Duplex on front of beam	Simplex on front of beam
24"	1	2
30"	2	4
36"	2	4
42"	2	4
48"	2	4
54"	2	4
60"	2/4	8
66"	2/4	8
72"	2/4	8



Delivered	
Pricing	
\$ 322	
351	
402	
435	
468	
492	
682	
718	
771	
886	
925	
965	
\$ 299	
342	
359	
406	
451	
473	
544	
584	
634	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

				MODEL NUMBER		
						Approx.
	MODEL	Features	W	Basic Model	Beam Color	Packaged Weight
. 10	End-of-Run Stand Alone Beam - No Power		24"	ITSB24/NN/ND		3.0#
	(NN) - Without Data Cover (ND)		30"	ITSB30/NN/ND		4.0#
	Includes beam end capsData jacks/connectors, connection plates		36"	ITSB36/NN/ND		5.0#
	and wiring are not included. Beams are		42"	ITSB42/NN/ND		7.0#
	pre-punched to accept most data plates.		48"	ITSB48/NN/ND		8.0#
			54"	ITSB54/NN/ND		10.0#
			60"	ITSB60/NN/ND		13.0#
			66"	ITSB66/NN/ND		13.0#
			72"	ITSB72/NN/ND		23.0#
		Quad	60"	ITSQ60/NN/ND		19.0#
		Quad	66"	ITSQ66/NN/ND		22.0#
		Quad	72"	ITSQ72/NN/ND		24.0#
- 7	End-of-Run Stand Alone Beam - Hard-	Left	36"	ITSB36/NYLT6/ND		11.0#
	Wire (HC) - Without Data Cover (ND)	Right	36"	ITSB36/NYRT6/ND		11.0#
	 Includes beam end caps 	Left	42"	ITSB42/NYLT6/ND		13.0#
	For NY infeed, left or right is determined by placement of the infeed leg when	Right	42"	ITSB42/NYRT6/ND		13.0#
	by placement of the infeed leg when seated at the table	Left	48"	ITSB48/NYLT6/ND		14.0#
	NY beam is 10-wire beam infeed for use	Right	48"	ITSB48/NYRT6/ND		14.0#
	in New York City by the Bureau of Elec-	Left	54"	ITSB54/NYLT6/ND		16.0#
	trical Control Advisory Board. Includes connection box, flexible conduit and all	Right	54"	ITSB54/NYRT6/ND		16.0#
	fittings necessary to connect to building	Left	60"	ITSB60/NYLT6/ND		20.0#
	power source. Does not include infeed	Right	60"	ITSB60/NYRT6/ND		20.0#
	wiring.	Left	66"	ITSB66/NYLT6/ND		23.0#
		Right	66"	ITSB66/NYRT6/ND		23.0#
		Left	72"	ITSB72/NYLT6/ND		25.0#
		Right	72"	ITSB72/NYRT6/ND		25.0#
		ingili	12	A	3	20.01

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: ullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect beam color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder Beam Receptacle Requirements

10-Wire
Duplex Receptacles
1
1
2
2
2
2
4

When back-to-back electrical is utilized with the New York 10-Wire System, one additional receptacle can be added to each size beam length for the back



Delivered	ed	
Pricing		
\$ 233 245		
258		
288		
313		
325		
349		
375		
418		
392		
418		
465		
\$ 830		
830		
914		
914	14	
936	36	
936		
963		
963		
988		
988		
1019		
1019		
1070		
1070	70	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

				MODEL NUME	ER		
	MODEL	Features	W	Basic Model	Beam Color	Approx. Packaged Weight	
4	End-of-Run Stand Alone Beam - 10-Wire		24"	ITSB24/T6/DC		7.0#	
	(T6) - With Data Cover (DC)		30"	ITSB30/T6/DC		8.0#	
V	 Includes beam end caps Data jacks/connectors, connection plates 		36"	ITSB36/T6/DC		9.0#	
	and wiring are not included. Beams are		42"	ITSB42/T6/DC		11.0#	
	pre-punched to accept most data plates		48"	ITSB48/T6/DC		12.0#	
	Duplex receptacles, infeeds and connec-		54"	ITSB54/T6/DC		14.0#	
data cover	tors must be ordered separately (see Electrical section) • Data covers conceal data wires in trough		60"	ITSB60/T6/DC		18.0#	
			66"	ITSB66/T6/DC		21.0#	
SB			72"	ITSB72/T6/DC		23.0#	
		Quad	60"	ITSQ60/T6/DC		19.0#	
		Quad	66"	ITSQ66/T6/DC		22.0#	
		Quad	72"	ITSQ72/T6/DC		24.0#	
7	End-of-Run Stand Alone Beam - Hard-		24"	ITSB24/HC/DC		5.0#	
	Wire (HC) - With Data Cover (DC)		30"	ITSB30/HC/DC		6.0#	
	 Includes beam end caps Hard-wire beams include simplex recep- 		36"	ITSB36/HC/DC		7.0#	
	tacles		42"	ITSB42/HC/DC		9.0#	
	Must specify hard-wire infeed separately		48"	ITSB48/HC/DC		10.0#	
	 Electrician to supply wires and connectors 		54"	ITSB54/HC/DC		12.0#	
data cover	 Data covers conceal data wires in trough 		60"	ITSB60/HC/DC		13.0#	
	ű		66"	ITSB66/HC/DC		15.0#	
SB			72"	ITSB72/HC/DC		19.0#	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect beam color. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder

Beam Receptacle Requirements

	10-Wire	Hard-Wire
Beam Length	Duplex on front of beam	Simplex on front of beam
24"	1	2
30"	2	4
36"	2	4
42"	2	4
48"	2	4
54"	2	4
60"	2/4	8
66"	2/4	8
72"	2/4	8



Delivered	
Pricing	
\$ 367	
400	
461	
502	
536	
564	
782	
836	
888	
988	
1043	
1083	
\$ 349	
391	
420	
471	
518	
546	
647	
698	
749	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

				MODEL NUMBER		
	MODEL	Features	W	Basic Model	Beam Color	Approx. Packaged Weight
	End-of-Run Stand Alone Beam - No Power		24"	ITSB24/NN/DC		3.0#
	(NN) - With Data Cover (DC)		30"	ITSB30/NN/DC		4.0#
	Includes beam end capsData jacks/connectors, connection plates		36"	ITSB36/NN/DC		5.0#
	and wiring are not included. Beams are		42"	ITSB42/NN/DC		7.0#
	pre-punched to accept most data plates.		48"	ITSB48/NN/DC		8.0#
	Data covers conceal data wires in trough		54"	ITSB54/NN/DC		10.0#
data cover			60"	ITSB60/NN/DC		13.0#
			66"	ITSB66/NN/DC		13.0#
ITSB			72"	ITSB72/NN/DC		23.0#
		Quad	60"	ITSQ60/NN/DC		19.0#
		Quad	66"	ITSQ66/NN/DC		22.0#
		Quad	72"	ITSQ72/NN/DC		24.0#
	End-of-Run Stand Alone Beam - NY Infeed	Left	36"	ITSB36/NYLT6/DC		11.0#
₩	(NYL) - With Data Cover (DC)	Right	36"	ITSB36/NYRT6/DC		11.0#
	 Includes beam end caps For NY infeed, left or right is determined 	Left	42"	ITSB42/NYLT6/DC		13.0#
	by placement of the infeed leg when	Right	42"	ITSB42/NYRT6/DC		13.0#
	seated at the table	Left	48"	ITSB48/NYLT6/DC		14.0#
	 NY beam is 10-wire beam infeed for use in New York City by the Bureau of Elec- 	Right	48"	ITSB48/NYRT6/DC		14.0#
data cover	trical Control Advisory Board. Includes	Left	54"	ITSB54/NYLT6/DC		16.0#
	connection box to connect to building	Right	54"	ITSB54/NYRT6/DC		16.0#
ITSB	power source. Does not include infeed	Left	60"	ITSB60/NYLT6/DC		20.0#
	wiring.	Right	60"	ITSB60/NYRT6/DC		20.0#
		Left	66"	ITSB66/NYLT6/DC		23.0#
		Right	66"	ITSB66/NYRT6/DC		23.0#
		Left	72"	ITSB72/NYLT6/DC		25.0#
		Right	72"	ITSB72/NYRT6/DC		25.0#

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: ullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.

BSelect beam color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder Beam Receptacle Requirements

	10-Wire
Beam Length	Duplex Receptacles
36"	1
42"	1
48"	2
54"	2
60"	2
66"	2
72"	4

When back-to-back electrical is utilized with the New York 10-Wire System, one additional receptacle can be added to each size beam length for the back



Delivere	red
Pricing	
\$ 27	
29	
31	
35	
37	
40	
45	
49	
53	
49 53	
	0 A
	84 90
\$ 88	89
\$ 88 88	89 89
\$ 88 88 97	89 89 78
\$ 88 88 97 97	89 89 78 78
\$ 88 88 97 97 100	89 89 78 78 08
\$ 88 88 97 97 100 100	89 89 78 78 08
\$ 88 88 97 97 100 100	89 89 78 78 08 08
\$ 88 88 97 97 100 100 103 103	89 89 78 78 08 08 08 38
\$ 88 88 97 97 100 100 103 103	89 89 78 78 08 08 08 38 38
\$ 88 88 97 97 100 100 103 103 108	89 89 78 78 08 08 08 38 38 88
\$ 88 88 97 97 100 100 103 103 108 108	89 78 78 78 08 08 08 88 88 88 88
\$ 88 88 97 97 100 100 103 103 108 108 113	89 78 78 08 08 08 08 88 88 88 88 88 88
\$ 88 88 97 97 100 100 103 103 108 108	89 78 78 08 08 08 08 88 88 88 88 88 88 89 91

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System

				MODEL NUMBE	R	
	MODEL	Features	W	Basic Model	Beam Color	
	Middle Beam - 10-Wire (T6) - Without		24"	ITMB24/T6/ND		7.0#
	Data Cover (ND)		30"	ITMB30/T6/ND		8.0#
	 Does not include beam end caps Data jacks/connectors, connection plates 		36"	ITMB36/T6/ND		9.0#
	and wiring are not included. Beams are		42"	ITMB42/T6/ND		11.0#
	pre-punched to accept most data plates		48"	ITMB48/T6/ND		12.0#
ITMB	Duplex receptacles, infeeds and connec-		54"	ITMB54/T6/ND		14.0#
	tors must be ordered separately. (See Electrical section)		60"	ITMB60/T6/ND		18.0#
			66"	ITMB66/T6/ND		21.0#
			72"	ITMB72/T6/ND		23.0#
		Quad	60"	ITMQ60/T6/ND		19.0#
		Quad	66"	ITMQ66/T6/ND		22.0#
		Quad	72"	ITMQ72/T6/ND		24.0#
A.	Middle Beam - Hard-Wire (HC) - Without		24"	ITMB24/HC/ND		5.0#
	Data Cover (ND)		30"	ITMB30/HC/ND		6.0#
	 Does not include beam end caps Hard-wire beams include simplex recep- 		36"	ITMB36/HC/ND		7.0#
	tacles		42"	ITMB42/HC/ND		9.0#
	Must specify hard-wire infeed separately		48"	ITMB48/HC/ND		10.0#
TMB	 Electrician to supply wires and connectors 		54"	ITMB54/HC/ND		12.0#
	1013		60"	ITMB60/HC/ND		13.0#
			66"	ITMB66/HC/ND		15.0#
			72"	ITMB72/HC/ND		19.0#
				Ø	•	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect beam color.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder

Beam Receptacle Requirements

	10-Wire	Hard-Wire
Beam Length	Duplex on front of beam	Simplex on front of beam
24"	1	2
30"	2	4
36"	2	4
42"	2	4
48"	2	4
54"	2	4
60"	2/4	8
66"	2/4	8
72"	2/4	8



Delivered	
Pricing	
\$ 305	
329	
408	
413	
451	
467	
650	
691	
739	
855	
900	
928	
\$ 285	
325	
338	
383	
430	
452	
520	
561	
611	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System

				MODEL NUMBE	R	
	MODEL	Features	W	Basic Model	Beam Color	
	Middle Beam - No Power (NN) - Without		24"	ITMB24/NN/ND		3.0#
	Data Cover (ND) Does not include beam end caps		30"	ITMB30/NN/ND		4.0#
			36"	ITMB36/NN/ND		5.0#
			42"	ITMB42/NN/ND		7.0#
			48"	ITMB48/NN/ND		8.0#
ITMB			54"	ITMB54/NN/ND		10.0#
			60"	ITMB60/NN/ND		11.0#
			66"	ITMB66/NN/ND		13.0#
			72"	ITMB72/NN/ND		14.0#
		Quad	60"	ITMQ60/NN/ND		18.0#
		Quad	66"	ITMQ66/NN/ND		21.0#
		Quad	72"	ITMQ72/NN/ND		23.0#
				Ø	3	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect beam color. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder



Deli	red
Pric	
\$	214
	229
	239
	269
	289
	305
	325
	354
	398
	368
	400
	439

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

				MODEL NUMBI	ER	
	MODEL	Features	W	Basic Model	Beam Color	Approx. Packaged Weight
â	Middle Beam - 10-Wire (T6) - With Data		24"	ITMB24/T6/DC		7.0#
	Cover (DC)		30"	ITMB30/T6/DC		8.0#
	 Does not include beam end caps Data jacks/connectors, connection plates 		36"	ITMB36/T6/DC		9.0#
	and wiring are not included. Beams are		42"	ITMB42/T6/DC		11.0#
	pre-punched to accept most data plates		48"	ITMB48/T6/DC		12.0#
Tive of	Duplex receptacles, infeeds and connec-		54"	ITMB54/T6/DC		14.0#
data cover	tors must be ordered separately. (See Electrical section.)		60"	ITMB60/T6/DC		18.0#
	Data covers conceal data wires in trough		66"	ITMB66/T6/DC		21.0#
ЛВ			72"	ITMB72/T6/DC		23.0#
		Quad	60"	ITMQ60/T6/DC		19.0#
		Quad	66"	ITMQ66/T6/DC		22.0#
		Quad	72"	ITMQ72/T6/DC		24.0#
Â	Middle Beam - Hard-Wire (HC) - With		24"	ITMB24/HC/DC		5.0#
	Data Cover (DC)		30"	ITMB30/HC/DC		6.0#
	 Does not include beam end caps Hard-wire beams include simplex recep- 		36"	ITMB36/HC/DC		7.0#
data cover	tacles		42"	ITMB42/HC/DC		9.0#
	 Must specify hard-wire infeed separately 		48"	ITMB48/HC/DC		10.0#
	 Electrician to supply wires and connectors 		54"	ITMB54/HC/DC		12.0#
	Data covers conceal data wires in trough		60"	ITMB60/HC/DC		13.0#
			66"	ITMB66/HC/DC		15.0#
			72"	ITMB72/HC/DC		19.0#

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect beam color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder Beam Receptacle Requirements

	10-Wire	Hard-Wire
Beam Length	Duplex on front of beam	Simplex on front of beam
24"	1	2
30"	2	4
36"	2	4
42"	2	4
48"	2	4
54"	2	4
60"	2/4	8
66"	2/4	8
72"	2/4	8



Delivered	
Pricing	
\$ 353	
378	
470	
481	
518	
540	
748	
809	
857	
957	
1018	
1049	
\$ 329	
375	
402	
451	
498	
526	
620	
680	
731	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

				MODEL NUMBE	R		
	MODEL	Features	W	Basic Model	Beam Color		
Ø.	Middle Beam - No Power (NN) - With		24"	ITMB24/NN/DC		3.0#	
	Data Cover (DC) Does not include beam end caps Data connectors, connection plates and wiring are not included. Beams are prepunched to accept most data plates		30"	ITMB30/NN/DC		4.0#	
			36"	ITMB36/NN/DC		5.0#	
			42"	ITMB42/NN/DC		7.0#	
			48"	ITMB48/NN/DC		8.0#	
	Data covers conceal data wires in trough		54"	ITMB54/NN/DC		10.0#	
data cover			60"	ITMB60/NN/DC		11.0#	
			66"	ITMB66/NN/DC		13.0#	
ITMB			72"	ITMB72/NN/DC		14.0#	
		Quad	60"	ITMQ60/NN/DC		18.0#	
		Quad	66"	ITMQ66/NN/DC		21.0#	
		Quad	72"	ITMQ72/NN/DC		23.0#	
				A	ß		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect beam color.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder



Delivered Pricing	
\$ 261	
277	
298	
331	
358	
378	
427	
470	
513	
471	
513	
560	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUMBER			
			Basic	Beam	Approx. Packaged	
	MODEL	W	Model	Color	Weight	
		24"	ITCB24/T6/ND		17.0#	
	` ,	30"	ITCB30/T6/ND		20.0#	
	 Does not include beam end caps 	36"	ITCB36/T6/ND		23.0#	
	 Data jacks/connectors, connection plates 	42"	ITCB42/T6/ND		26.0#	
ITCB	and wiring are not included. Beams are pre-punched to accept most data plates.	72	110042/10/10		20.0#	
1105	Support legs are required for corner					
	beams and must be ordered separately.					
	Duplex receptacles, infeeds and connec-					
	tors must be ordered separately (See Electrical section)					
	Corner beams with 10-wire electrical					
	include a pass through cable on the					
	right side. This elimates the need for a					
	worksurface to worksurface connector on the right.					
	on the right.					
		0.41	ITCB24/HC/ND		13.0#	
	Corner Middle Beam - Hard-Wire (HC) -	24"				
		30"	ITCB30/HC/ND		16.0#	
	Hard-wire beams include simplex recep-	36"	ITCB36/HC/ND		19.0#	
	lacies	42"	ITCB42/HC/ND		22.0#	
ITCB	Support legs are required for corner					
	 beams and must be ordered separately Must specify hard-wire infeed separately 					
	Electrician to supply wires and connec-					
	tors					
_	Comor imagic Boam 110 i onoi (iiii)	24"	ITCB24/NN/ND		9.0#	
	Daniel and Santonia harmonia and area	30"	ITCB30/NN/ND		12.0#	
	Does not include beam end caps.Support legs are required for corner	36"	ITCB36/NN/ND		15.0#	
(C) (D)	beams and must be ordered separately	42"	ITCB42/NN/ND		18.0#	
ITCB						
			A	B		
			w	\mathbf{v}		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect beam color. Refer to the KI Color Addendum or KI Fabrics & Finishes binder

10-Wire Hard-Wire

	10-wire	naru-wire
Beam Length	Duplex on front of beam	Simplex on front of beam
24"	0	0
30"	2	4
36"	2	4
42"	2	4

Beam Receptacle Requirements

24" corner beams for both 10-Wire anc Hard-Wire power include power pass through only.



De	Delivered Professional Control of the Control of th
Pr	Pricing
\$	\$ 1139
	1191
	1302
	1362
\$	\$ 1082
	1130
	1237
	1294
	\$ 777
\$	
\$	812
\$	
\$	812 903 971

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUMBER			
	MODEL	W	Basic Model	Beam Color	Approx. Packaged Weight	
	Corner Middle Beam - 10-Wire (T6) -	24"	ITCB24/T6/DC		17.0#	
	With Data Cover (DC)	30"	ITCB30/T6/DC		20.0#	
	 Does not include beam end caps Data jacks/connectors, connection plates 	36"	ITCB36/T6/DC		23.0#	
	and wiring are not included. Beams are	42"	ITCB42/T6/DC		26.0#	
ITCB	pre-punched to accept most data plates					
	Support legs are required for corner					
	 beams and must be ordered separately Duplex receptacles, infeeds and connec- 					
	tors must be ordered separately					
	 Corner beams with 10-wire electrical 					
	include a pass through cable on the right side. This eliminates the need for					
	a worksurface to worksurface connector					
	on the right					
	Data covers conceal data wires in trough					
	Corner Middle Beam - Hard-Wire (HC) -	24"	ITCB24/HC/DC		13.0#	
	With Data Cover (DC)	30"	ITCB30/HC/DC		16.0#	
	 Does not include beam end caps Hard wire beams include simplex recep- 	36"	ITCB36/HC/DC		19.0#	
	tacles	42"	ITCB42/HC/DC		22.0#	
ITCB	Must specify hard-wire infeed separately					
	 Electrician to supply wires and connectors 					
	Data covers conceal data wires in trough					
	Support legs are required for corner					
	beams and must be ordered separately					
	Corner Middle Beam - No Power (NN) -	24"	ITCB24/NN/DC		9.0#	
	With Data Cover (DC)	30"	ITCB30/NN/DC		12.0#	
	 Does not include beam end caps Support legs are required for corner 	36"	ITCB36/NN/DC		15.0#	
	beams and must be ordered separately	42"	ITCB42/NN/DC		18.0#	
ITCB	Data covers conceal data wires in trough					
			Ø	3		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: ullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect beam color.

Refer to the KI Color Addendum or KI Fabrics & Finishes binder

Beam Receptacle Requirements

	10-Wire	Hard-Wire
Beam Length	Duplex on front of beam	Simplex on front of beam
24"	0	0
30"	2	4
36"	2	4
42"	2	4

24" corner beams for both 10-Wire and Hard-Wire power include power pass through only.



D	Nali:d
Di Pi	Delivered Pricing
\$	5 1295
•	1355
	1483
	1557
\$	1235
	1287
	1411
	1478
\$	
	927
	1031
	1107

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Legs and CPU Clamps

				MODEL NU	IMBER			
		MODEL	D x H	Basic Model	Leg Color	Paint Color	Approx. Packaged Weight	
	<i>a.</i>	"C" Leg	24 x 27"	ITCL2427			15.0#	
		Legs will accept power infeed or data	24 x 29"	ITCL2429			16.0#	
	~ ₁	infeed, not both • 1-1/4" vertical glide adjustment	24 x 38"	ITCL2438			21.0#	
		Only one leg is included in a kit	30 x 27"	ITCL3027			19.0#	
			30 x 29"	ITCL3029			20.0#	
			30 x 38"	ITCL3038			26.0#	
•								
ITCL		Councy Cumpant Lan	27"	ITCS27			12.0#	
	\Diamond	• One corner support leg required per	29"	ITCS27			12.0#	
	: :	corner worksurface	29	110329			14.0#	
		 Wire manmagement is not available on corner support legs 						
		• 1-1/4" vertical glide adjustment						
	\forall	,						
ITCL								
		CPU Clamp - Large		INTCPULG			15.0#	
		 For 30" deep worksurfaces only Accommodates single or double CPUs 						
		with combined widths of 5.5" to 9"						
HRDPT								
		• For 24" and 30" deep worksurfaces		INTCPUSM			10.0#	
		Accomodates single or double CPU						
		widths of 3.8" to 5.8"						
	Approx.							
HRDPT								
ואטאו								
				A	B	Θ		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: ullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect trim color. Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>



InTandem® Table System Legs and CPU Clamps

Deliv	livered
Prici	cing
\$	206
	210
	233
	218
	234
	247
Φ.	104
	121 131
\$	169
Ψ	100
\$	134
Ψ	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Freestanding Frames with Casters

			MODEL NUMBE	R			
			Danie.	Tolar	Approx.		
	MODEL	DxWxH	Basic Model	Trim Color	Packaged Weight		
	29" Legs - Without Data Cover (ND)	30 x 24 x 29"	ITFC302429/ND		45.0#		
	 Includes stand alone beam with two end 	30 x 30 x 29"	ITFC303029/ND		47.0#		
	caps, two C legs and four carpet casters	30 x 36 x 29"	ITFC303629/ND		48.0#		
	Non-powered beams onlyWorksurface must be specified sepa-	30 x 42 x 29"	ITFC304229/ND		50.0#		
	rately	30 x 48 x 29"	ITFC304829/ND		51.0#		
	,	30 x 54 x 29"	ITFC305429/ND		53.0#		
		30 X 34 X 29	1170303429/ND		J3.0#		
Ø							
ITFC							
TIFU	38" Legs - Without Data Cover (ND)	30 x 42 x 38"	ITFC304238/ND		61.0#		
	Includes stand alone beam with two end	30 x 42 x 38"	ITFC304236/ND		62.0#		
	caps, two C legs and four carpet castersNon-powered beams only						
		30 x 54 x 38"	ITFC305438/ND		64.0#		
	 Worksurface must be specified sepa- rately 						
	rately						
•							
ITEO							
ITFC							
			Δ	3			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: ullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect trim color. Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>



InTandem® Table System Freestanding Frames with Casters

Deliv	vered
Pricir	ng
	653
	668
	696
	730
	749
	772
	927
	952
	985

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Freestanding Frames with Casters

			MODEL NUMBI	ER		
					Approx.	
			Basic	Trim	Packaged	
	MODEL	DxWxH	Model	Color	Weight	
	29" Legs - With Data Cover (DC)	30 x 24 x 29"	ITFC302429/DC		45.0#	
	 Includes stand alone beam with two end caps, two C legs and four carpet casters 	30 x 30 x 29"	ITFC303029/DC		47.0#	
	Non-powered beams only	30 x 36 x 29"	ITFC303629/DC		48.0#	
	 Worksurface must be specified sepa- 	30 x 42 x 29"	ITFC304229/DC		50.0#	
	rately	30 x 48 x 29"	ITFC304829/DC		51.0#	
		30 x 54 x 29"	ITFC305429/DC		53.0#	
ITFC						
	38" Legs - With Data Cover (DC) Includes stand alone beam with two end caps, two C legs and four carpet casters Non-powered beams only Worksurface must be specified separately	30 x 42 x 38"	ITFC304238/DC		61.0#	
		30 x 48 x 38"	ITFC304838/DC		62.0#	
		30 x 54 x 38"	ITFC305438/DC		64.0#	
ITFC		10 00"	1771U/ 1000		24.0"	
	 Wheelchair Accessible Kit Available in Graphite Dark only 	42 x 29"	ITWK.4229		24.0#	
	 Available in Graphile Dark only Specify table width and existing leg height Wheelchair kits for 42" wide tables can only be used when at least one of the 	48 x 29"	ITWK.4829		26.0#	
		54 x 29"	ITWK.5429		28.0#	
		60 x 29"	ITWK.6029		30.0#	
₩ WDDDT	legs of the ADA table are in the shared	66 x 29"	ITWK.6629		32.0#	
HRDPT	position (one leg shared with an adjoin-	72 x 29"	ITWK.7229		34.0#	
	ing table)					
	All sizes of kits accommodate one wheelchair only (based on current ADA)					
	clearance guidelines)					
	·					
			A	3		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: ullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect trim color. Refer to the <u>KI Color Addendum</u> or <u>KI</u> <u>Fabrics & Finishes binder</u>



InTandem® Table System Freestanding Frames with Casters

n	Delivered
P	Pricing
\$	\$ 698
	714
	751
	793
	818
	840
\$	\$ 992
	1017
	1055
\$	\$ 377
	386
	393
	400
	411
	426

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Flectrica

			MODEL NUI	MBER				
					Approx.			
			Basic	Paint	Packaged			
	MODEL	Н	Model	Color	Weight			
a	Floor Infeed 10-Wire • Provides power from fixed floor or wall		PTFF		5.0#			
3	sources to table power distribution							
	system							
	105" infeed lengthDesigned to pass through the standard							
	Intandem® leg cover							
HRDPT	Ÿ							
ואטאו	Floor Infeed Hard-Wire Kit	27"	ITHK.27		4.0#			
₩	Provides conduit from fixed floor or	29"	ITHK.29		4.0#			
ff	wall sources to table power distribution	38"	ITHK.23		5.0#			
	system. Customer to provide wiring • Select height to match leg height; ie, 27",	00	1111111.00		0.0#			
all l	29" or 38"							
HRDPT								
al	Overhead Infeed Circuit Pre-wired		PCOF.T6		15.0#			
	 Provides power from ceiling source to table distribution system 							
	Includes 10' long aluminum pole with							
	separate channel for electrical and data							
HRDPT	entry and prewired harness							
Φ.	Overhead Infeed Hard-Wire Kit • Provides channel from ceiling source to		PCHK0		12.0#			
	table distribution system							
	 Includes 10' long aluminum pole with 							
₩	separate channel for electrical and data entry. Customer to provide wiring.							
HRDPT	chary. Sustainer to provide wiring.							
ППОГІ	Vertical Wireway Cover		ITELW29		1.0#			
\mathbb{Q}	For 29" leg only		TILLWES		1.0#			
#//								
<i>III</i>								
¥								
HRDPT								
			•	•	-			
			•	•				

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- 2. Model number, including options. See "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- Select paint color.

 Refer to the <u>KI Color Addendum</u> or <u>KI</u>

 <u>Fabrics & Finishes binder</u>

INFORMATION

Floor Infeed (10-Wire)

Two 90° connectors. Flexible steel conduit with ten 12-gauge conductors in the leg. Includes steel trim plate with dual holes for electrical and data entry and six feet of liquid-tight flexible conduit .8315 diameter.

Floor Infeed Hard-Wire Kit

Three 90° connectors. Flexible steel conduit in the leg. Includes steel trim plate with dual holes for electrical and data entry and six feet of liquid-tight flexible conduit .8315 diameter.

Overhead Infeed Circuit Pre-wired

Aluminum pole is 10ft. in length. Flexible steel conduit with ten 12-gauge conductors. Includes ceiling trim plate.

Overhead Infeed Hard-Wire Kit

Aluminum pole is 10ft. in length. Includes ceiling trim plate.



Deli	elivered	
DO!		
Pric	ricing	
φ	146	
Ф	140	
φ	100	
Ъ	102	
	102	
	102	
	109	
	100	
Φ	FF0	
\$	556	
_	170	
\$	179	
_		
\$	33	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

	MODEL	Features	L	MODEL NUMBER Basic Model	Approx. Packaged Weight
	Worksurface-to-Worksurface 10-Wire		15"	48.0268.17	1.0#
E James Land	Connector Connects the 10-wire power system of two adjoining tables Is "long"				
HRDPT					
	10-Wire Harness for T-Shaped Configura-		24"	ITTT6.24	4.0#
The state of the s	tions		30"	ITTT6.30	5.0#
O. C. Communication	 Provides continuous power from table- to-table for T-shaped table configura- tions 		36"	ITTT6.36	6.0#
HRDPT	Select size according to table depth				
	10-Wire Harness for Back-to-Back		30"	ITBBT6.30	5.0#
The state of the s	Configurations Provides continuous power from table-to-table for back-to-back configurations For tables 30"-54" wide: Select size ac-		36"	ITBBT6.36	6.0#
A			42"	ITBBT6.42	6.0#
V.			48"	ITBBT6.48	7.0#
HRDPT	cording to table width		54"	ITBBT6.54	7.0#
	 For tables 60"-72" wide: Use 1-IT-BBT6.30 on 60" and 66" wide tables. Use 1-ITBBT6.36 on 72" wide tables. Note: 60, 66, and 72" wide tables require quad beams for both tables in the back-to-back configuration 				
	Back-to-Back Ganging Kit			46.5003	1.0#
	 Ganger kits must be specified for back-to-back configurations Two kits are required per set of tables to be ganged 				
HRDPT					
	Receptacles - 6 Circuit	Circuit 1		47.0706.1.BL	1.0#
	Attaches to wireways of 10 wire powered tables	Circuit 2		47.0706.2.BL	1.0#
	tables • Provides two (duplex) receptacles each	Circuit 3		47.0706.3.BL	1.0#
-	rated at 15 amps	Circuit 4		47.0706.4I.BL	1.0#
HRDPT	Some circuits are isolated ground	Circuit 5		47.0706.5I.BL	1.0#
	circuits (622 - 4,5, & 6), Isolated ground receptacles are identified by an orange triangle	Circuit 6		47.0706.6I.BL	1.0#

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

1

InTandem® Table System

Dali	vered
Pric	ing
\$	78
\$	150
	158
	171
\$	158
	175
	191
	210
	236
Φ.	236
\$	
\$	236
\$	236
\$	236
\$	236
\$	236
	236 5
\$	236
	236
	236 5 24 24 24
	236 5 24 24 24 24
	24 24 24 24 24 24
	236 5 24 24 24 24

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

		MODEL NUMBER			
			Approx.		
		Basic	Packaged		
	MODEL	Model	Weight		
	Quad-Block • Allows power to be distributed from the	4BT6	1.0#		
	middle of a table series				
	The Quad-Block (along with included jumper) enables infeed power from the				
S Car	building to be routed in two directions.				
•	These units, four female openings accept				
HRDPT	the male end of the power infeed and the male plug ends of two table-to-table				
	jumpers which tranfer the power to the				
	two adjoining tables.				
	Hard-Wire Back-to-Back Electrical	IHB.RECP	0.2#		
	Receptacle				
HRDPT					
	Electrical Strip	PC.OSWS	3.0#		
	Optional electrical source for unit on				
(BBBB -	castersSurge protected, six outlet, 110 volt				
	electrical strip with 6' long cord to lay in				
<i>t</i> 3	beam				
HRDPT					
C. Constitution of the second	8-Wire to 10-Wire Adaptor • 20" long	47.0568.20	1.0#		
	20 10119				
A STATE OF THE STA					
HRDPT					
		Ø			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

14

InTandem® Table System

Delivered
Pricing
\$ 40
\$ 41
\$ 139
\$ 141

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

		MODEL NUMBER			
			A		
		Basic	Approx. Packaged		
	MODEL	Model	Weight		
	Activ8® Infeed	AC8IF.108	2.0#		
	108" cord plugs into standard 15 amp	7.00	2.0"		
	outlet				
9	Control module is located 6" from table connection				
HRDPT	Diagnostic LED indicator shows power				
	status (see details below)				
	Controller automatically limits number of connections to 8				
	40 Ft maximum string, not including				
	infeed cord				
	Will not work with GFI/GCFI outlets or				
	backup systems such as uninterrupted power supplies				
	parisi supplied				
		AC8RPTIT.12	1.0#		
	Activ8® Module and Attachment Bracket				
	Duplex receptacles provide 2 outlets				
	 Power module provides 15 amp power Up to 8 modules may be used per infeed 				
TE .	per UL Standard 962				
•	Modules may be connected (recon-				
HRDPT	nected in any order without sequential keying)				
	Jumpers ordered separately				
	No data cord management is provided				
		A			

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



Delivered Pricing \$ 209

\$ 132

		MODEL N	IUMBER	
	MODEL	Basic Model	PowerUp Module Color	Approx. Packaged Weight
HRDPT	Activ8® Power-Up Module Duplex receptacles provide 2 outlets Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Attached cord is approximately 12" Data tree is provided to allow data jacks to be inserted in the module Jumpers ordered separately			1.0#
HRDPT	Activ8® Villa Power Module with Metal Cover Duplex receptacles provide 2 outlets, 2 USB charging ports, 1 RJ45 data connector Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Attached cord is approximately 12° Data tree is provided to allow data jacks to be inserted in the module Jumpers ordered separately	AC8VMC		3.0#
HRDPT	Activ8® Villa Power Module without Cover Duplex receptacles provide 2 outlets, 2 USB charging ports, 1 RJ45 data connector Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Attached cord is approximately 12° Data tree is provided to allow data jacks to be inserted in the module For use on tables with existing KI grommets Jumpers ordered separately			2.0#
		A	•	

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\Box$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- Select module color.
 Refer to the <u>KI Color Addendum</u> or <u>KI</u>
 <u>Fabrics & Finishes binder</u>



Deli	ivered
Pric	cina
\$	194
Ψ	177
\$	412
•	
\$	348

			MODEL NUMBER			
	MODEL	L	Basic Model	Approx. Packaged Weight		
	Activ8® Jumper • Refer to Connection Zone Benching Planning Guide for size recommenda- tions • Jumpers are all keyed alike	29"	AC8JP.29	1.0#		
		53"	AC8JP.53	1.0#		
		77"	AC8JP.77	1.0#		
63						
HRDPT						
			A			

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of $\hfill\square$ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.



Deli	vered ing	
Pric	ing	
\$	66	
	77	
	88	

InTandem® Table System Rectangular Privacy Screens

	MODEL	Features	H x W	Basic Model	Surface Finish	Approx. Packaged Weight
	Rectangular Privacy Screens - 11" Height		11 x 24"	ITPS1124		11.0#
	 Privacy screen brackets and hardware 		11 x 30"	ITPS1130		13.0#
	supplied in Graphite Dark only • 60", 66", and 72" screens are made up of		11 x 36"	ITPS1136		14.0#
	2 screens		11 x 42"	ITPS1142		16.0#
	Screen is laminate with matching edge		11 x 48"	ITPS1148		17.0#
•	band		11 x 54"	ITPS1154		19.0#
ITPS		(2 pcs)	11 x 60"	ITPS1160		23.0#
		(2 pcs)	11 x 66"	ITPS1166		25.0#
		(2 pcs)	11 x 72"	ITPS1172		26.0#
	Rectangular Privacy Screens - 17" Height Privacy screen brackets and hardware supplied in Graphite Dark only 60", 66", and 72" screens are made up of 2 screens Screen is laminate with matching edge band		17 x 24"	ITPS1724		14.0#
			17 x 30"	ITPS1730		17.0#
			17 x 36"	ITPS1736		20.0#
			17 x 42"	ITPS1742		23.0#
			17 x 48"	ITPS1748		26.0#
			17 x 54"	ITPS1754		29.0#
		(2 pcs)	17 x 60"	ITPS1760		32.0#
ITPS		(2 pcs)	17 x 66"	ITPS1766		36.0#
		(2 pcs)	17 x 72"	ITPS1772		38.0#
	Rectangular Privacy Screens - 23" Height • Privacy screen brackets and hardware		23 x 24"	ITPS2324		18.0#
	supplied in Graphite Dark only		23 x 30"	ITPS2330		22.0#
i l	• 60", 66", and 72" screens are made up of		23 x 36"	ITPS2336		26.0#
· L	2 screens		23 x 42"	ITPS2342		30.0#
	 23" height privacy screens are not avail- able on 24" deep worksurfaces 		23 x 48"	ITPS2348		34.0#
	Screen is laminate with matching edge		23 x 54"	ITPS2354		38.0#
	band	(2 pcs)	23 x 60"	ITPS2360		42.0#
		(2 pcs)	23 x 66"	ITPS2366		47.0#
ITPS		(2 pcs)	23 x 72"	ITPS2372		49.0#
				A	3	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by Surface finish offerings are based on edge the supplier's color/pattern code:

> Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Rectangular Privacy Screens

De	elivered	
Pri	ricing	
\$	183	
	198	
	214	
	240	
	243	
	270	
	368	
	402	
	404	
\$		
	220	
	240	
	272	
	277	
	311	
	413	
	451	
	453	
\$	219	
	240	
	261	
	298 303	
	342	
	342 451	
	495	
	495	
	490	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Stand Alone Privacy Screen

				MODEL NU	IMBER		
	MODEL	Features	H x W	Basic Model	Surface Finish	Approx. Packaged Weight	
	Rectangular Stand Alone Privacy Screens		11 x 24"	ITPSA1124		11.0#	
	- 11" Height		11 x 30"	ITPSA1130		13.0#	
	Stand Alone screens are positioned slang the book side of the table (length)		11 x 36"	ITPSA1136		14.0#	
	along the back side of the table (length). No divider screens attached		11 x 42"	ITPSA1142		16.0#	
	Privacy screen brackets and hardware		11 x 48"	ITPSA1148		17.0#	
W	supplied in Graphite Dark only		11 x 54"	ITPSA1154		19.0#	
	 60", 66", and 72" screens are made up of 2 screens Screen is laminate with matching edge 	(2 pcs)	11 x 60"	ITPSA1160		23.0#	
		(2 pcs)	11 x 66"	ITPSA1166		25.0#	
	band	(2 pcs)	11 x 72"	ITPSA1172		26.0#	
•	Rectangular Stand Alone Privacy Screens		17 x 24"	ITPSA1724		14.0#	
	- 17" Height		17 x 30"	ITPSA1730		17.0#	
	 Stand Alone screens are positioned along the back side of the table (length). 		17 x 36"	ITPSA1736		20.0#	
	No divider screens attached		17 x 42"	ITPSA1742		23.0#	
	Privacy screen brackets and hardware		17 x 48"	ITPSA1748		26.0#	
	supplied in Graphite Dark only		17 x 54"	ITPSA1754		29.0#	
	 60", 66", and 72" screens are made up of 2 screens 	(2 pcs)	17 x 60"	ITPSA1760		32.0#	
PS	Stand Alone privacy screens are not	(2 pcs)	17 x 66"	ITPSA1766		36.0#	
	available in 23" height	(2 pcs)	17 x 72"	ITPSA1772		38.0#	
	Screen is laminate with matching edge band						
				•	B		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge the supplier's color/pattern code: style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



\sim	A I	Privacy	O

Deli	livered
Pric	
	188
	206
	223
	246
	248
	277
	378
	408
	410
	211
	229
	246
	279
	286
	318
	425
	459
	461

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Corner Privacy Screens

			MODEL N	UMBER			
					Approx.		
			Basic	Surface	Packaged		
	MODEL	H x W	Model	Finish	Weight		
	Corner Privacy Screens - 11" Height	11 x 24"	ITCP1124		20.0#		
	 Privacy screen brackets and hardware supplied in Graphite Dark only 	11 x 30"	ITCP1130		23.0#		
	Screen is laminate with matching edge	11 x 36"	ITCP1136		26.0#		
	band	11 x 42"	ITCP1142		29.0#		
ITPS							
	Corner Privacy Screens - 17" Height Privacy screen brackets and hardware supplied in Graphite Dark only Screen is laminate with matching edge band	17 x 24"	ITCP1724		26.0#		
/		17 x 30"	ITCP1730		32.0#		
		17 x 36"	ITCP1736		38.0#		
/		17 x 42"	ITCP1742		44.0#		
ITPS							
	Corner Privacy Screens - 23" Height	23 x 30"	ITCP2330		42.0#		
	 Privacy screen brackets and hardware supplied in Graphite Dark only 	23 x 36"	ITCP2336		49.0#		
	 23" height privacy screens are not avail- 	23 x 42"	ITCP2342		57.0#		
·	able on 24" deep worksurfaces						
	Screen is laminate with matching edge						
•	band						
ITPS							
			A	(3)			
			•	•			

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by Surface finish offerings are based on edge the supplier's color/pattern code:

> Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Corner Privacy Screens

Delivered Pricing	
Pricing	
\$ 368	
379	
401	
454	
\$ 410	
430	
456	
278	
529	
259	
\$ 490	
\$ 490 520	
\$ 490	
\$ 490 520	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUM	ADED		
			MODEL NUI	MREK		
	MODEL	H x W	Basic Model	Surface Finish	Approx. Packaged Weight	
	End Divider Screens - 11" Height	11 x 24"	ITDV1124/E		11.0#	
	Divider screen brackets and hardware supplied in Graphite Dark only	11 x 30"	ITDV1130/E		13.0#	
	Must be used in conjunction with privacy					
	screen					
3 /	 Screen is laminate with matching edge band 					
ITD./	San a					
ITDV	Fud Divides Coverns 478 Heinki	17 x 24"	ITDV1724/E		14.0#	
	End Divider Screens - 17" Height • Divider screen brackets and hardware	17 x 24 17 x 30"	ITDV1724/E		14.0#	
04	supplied in Graphite Dark only	17 × 50	IIDVII/30/L		17.0#	
	 Must be used in conjunction with privacy screen 					
	Screen is laminate with matching edge band					
ITDV						
	End Divider Screens - 23" Height	23 x 30"	ITDV2330/E		22.0#	
	Divider screen brackets and hardware					
	supplied in Graphite Dark only • Must be used in conjunction with privacy					
	screen					
	23" height divider screens are not avail- able on 24" doop workeurfeees.					
	able on 24" deep worksurfaces • Screen is laminate with matching edge					
•	band					
ITDV						
			(A)	3		

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by Surface finish offerings are based on edge the supplier's color/pattern code:

> Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Divider Screens

Dolis	livered	
חושם	INVERTED .	
Prici	livered icing	
\$		
	225	
\$	219	
	245	
	240	
\$	267	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

			MODEL NUMBE	R		
	MODEL	H x W	Basic Model	Surface Finish	Approx. Packaged Weight	
	Middle Divider Screens - 11" Height	11 x 24"	ITDV1124/M74P		11.0#	
	Divider screen brackets and hardware	11 x 24"	ITDV1124/MME		11.0#	
	supplied in Graphite Dark only Must be used in conjunction with privacy	11 x 24"	ITDV1124/MPL		11.0#	
	screen	11 x 30"	ITDV1130/M74P		13.0#	
	Screen is laminate with matching edge	11 x 30"	ITDV1130/MME		13.0#	
TDV	band	11 x 30"	ITDV1130/MPL		13.0#	
101	M74P for use with 74P edge worksur-	11 × 00	TIBVITOO/WII E		10.0#	
	faces • MME for use with urethane edge work- surfaces (shown)					
	MPL for use with post-formed laminate					
	edge worksurfaces					
	Middle Divider Screens - 17" Height	17 x 24"	ITDV1724/M74P		14.0#	
	Divider screen brackets and hardware supplied in Graphite Dark only	17 x 24"	ITDV1724/MME		14.0#	
	Must be used in conjunction with privacy.	17 x 24"	ITDV1724/MPL		14.0#	
649	screen	17 x 30"	ITDV1730/M74P		17.0#	
	Screen is laminate with matching edge	17 x 30"	ITDV1730/MME		17.0#	
***	band	17 x 30"	ITDV1730/MPL		17.0#	
DV	 M74P for use with 74P edge worksur- faces 					
	MME for use with urethane edge work-					
	surfaces (shown)					
	MPL for use with post-formed laminate					
	edge worksurfaces					
	Middle Divider Screens - 23" Height	23 x 30"	ITDV2330/M74P		22.0#	
	Divider screen brackets and hardware					
	supplied in Graphite Dark only	23 x 30"	ITDV2330/MME		22.0#	
	- Wast be asea in conjunction with privacy	23 x 30"	ITDV2330/MPL		22.0#	
•	screen					
	23" height divider screens are not avail- able on 24" deep worksurfaces					
	Screen is laminate with matching edge					
	band					
TDV	 M74P for use with 74P edge worksur- 					
	faces					
	 MME for use with urethane edge work- surfaces (shown) 					
	MPL for use with post-formed laminate					
	edge worksurfaces					

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge the supplier's color/pattern code: style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Divider Screens

Deliv	vered
Prici	vered ing
\$	218
	218
	218
	239
	239
	239
	20.6
\$	234
	234
	234
	261
	261
	261
\$	279
	279
	279

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Rectangular Curved Privacy Screens

				MODEL NU	IMBER		
	MODEL	Features	W	Basic Model	Surface Finish	Approx. Packaged Weight	
	Rectangular Curved Privacy Screens - 9"		24"	ITPSC924		9.0#	
(a)	Height		30"	ITPSC930		11.0#	
	Curved top edge is 9" high at ends, 11" high is middle.		36"	ITPSC936		12.0#	
J.B	high in middle • 3/4" thick core material		42"	ITPSC942		14.0#	
ITPC	Mounted to brackets which bolt to beam 60", 66", and 72" screens consist of two screens Screen is laminate with matching edge band		48"	ITPSC948		15.0#	
			54"	ITPSC954		17.0#	
		(2 pcs)	60"	ITPSC960		21.0#	
		(2 pcs)	66"	ITPSC966		23.0#	
		(2 pcs)	72"	ITPSC972		24.0#	
	Rectangular Curved Privacy Screens - 15"		24"	ITPSC1524		12.0#	
	Height		30"	ITPSC1530		15.0#	
	 Curved top edge is 15" high at ends, 17" high in middle 		36"	ITPSC1536		18.0#	
	3/4" thick core material		42"	ITPSC1542		21.0#	
	Mounted to brackets which bolt to beam		48"	ITPSC1548		24.0#	
•	60", 66", and 72" screens consist of two		54"	ITPSC1554		27.0#	
ITPC	screens • Screen is laminate with matching edge	(2 pcs)	60"	ITPSC1560		30.0#	
	band	(2 pcs)	66"	ITPSC1566		33.0#	
		(2 pcs)	72"	ITPSC1572		36.0#	

(

0

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- **B**Select surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge the supplier's color/pattern code: style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Rectangular Curved Privacy Screens

n	elivered
P	icing
\$	
	308
	321
	367
	415
	420
	596
	629
	643
\$	306
	319
	338
	392
	449
	456
	610
	652
	679

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Stand Alone Curved Privacy Screen

				MODEL MUS	ADED	
				MODEL NUM	/IRFK	
	MODEL	Features	W	Basic Model	Surface Finish	Approx. Packaged Weight
	Rectangular Stand Alone Curved Privacy		24"	ITPSAC924		9.0#
	Screens - 9" Height		30"	ITPSAC930		11.0#
	 Stand Alone screens are positioned along the back side of the table (length). 		36"	ITPSAC936		12.0#
	No divider screens attached		42"	ITPSAC942		14.0#
ITPC	 Curved top edge is 9" high at ends, 11" 		48"	ITPSAC948		15.0#
	high in middle • 3/4" thick core material		54"	ITPSAC954		17.0#
	5/4 thick core material 60", 66", and 72" screens consist of two screens	(2 pcs)	60"	ITPSAC960		21.0#
		(2 pcs)	66"	ITPSAC966		23.0#
	Screen is laminate with matching edge	(2 pcs)	72"	ITPSAC972		24.0#
	band					
	Rectangular Stand Alone Curved Privacy		24"	ITPSAC1524		12.0#
	Screens - 15" Height		30"	ITPSAC1530		15.0#
	 Stand Alone screens are positioned along the back side of the table (length). 		36"	ITPSAC1536		18.0#
	No divider screens attached		42"	ITPSAC1542		21.0#
	 Curved top edge is 15" high at ends, 17" 		48"	ITPSAC1548		24.0#
₩	high in middle • 3/4" thick core material		54"	ITPSAC1554		27.0#
ITPC	 3/4 thick core material 60", 66", and 72" screens consist of two 	(2 pcs)	60"	ITPSAC1560		30.0#
	screens	(2 pcs)	66"	ITPSAC1566		33.0#
	Screen is laminate with matching edge	(2 pcs)	72"	ITPSAC1572		36.0#
	band					
				Δ	3	

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge the supplier's color/pattern code: style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Stand Alone Curved Privacy Screen

Delivered	d
Pricing	
\$ 295	
308	
321	
367	
415	
420	
596	
629	
643	3
\$ 306	
319	
338	8
392	2
449	9
456	6
610	0
652	
679	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

InTandem® Table System Corner Curved Privacy Screen

								_
		N	ODEL NU	MBER				
	MODEL		asic Nodel	Surface Finish	Approx. Packaged Weight			
		24" IT	TPCC924		20.0#		 	
	Height	30" IT	ГРСС930		20.0#			
	Curved top edge is 9" high at ends, 11" bigh is middle.	36" IT	TPCC936		20.0#			
	high in middle • 3/4" thick core material	42" IT	TPCC942		20.0#			
ITPC	 Mounted to brackets which bolt to beam 							
	Screen is laminate with matching edge							
	band							
_		24" IT	TPCC1524		26.0#			
		30" IT	TPCC1530		26.0#			
	Curved top edge is 15" high at ends, 17" high in middle	36" IT	TPCC1536		26.0#			
	3/4" thick core material	42" IT	TPCC1542		26.0#			
	· Mounted to brackets which bolt to beam							
ITPC	Screen is laminate with matching edge							
	band							
			(A)	3				

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

Surface finish offerings are based on edge the supplier's color/pattern code: style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Corner Curved Privacy Screen

Delivered Pricing \$ 596 611 643 733 \$ 610 634 679 786				
Pricing \$ 596 611 643 733 *** *** *** *** *** *** ** ** ** **				
Pricing \$ 596 611 643 733 *** *** *** *** *** ** ** ** ** **	- ··			
\$ 596 611 643 733 * 610 634 679	Deliv Prici	vered ing		
643 733 * 610 634 679				
733 \$ 610 634 679		611		
\$ 610 634 679		643		
634 679		733		
634 679				
679				
786				
		786		

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Curved Divider Screens

			MODEL NUI	WRFR			
	MODEL	D	Basic Model	Surface Finish	Approx. Packaged Weight		
	End Curved Divider Screens - 9" Height	24"	ITDC924/E		11.0#		
	 Curved top edge is 9" high at ends, 11" high in middle 	30"	ITDC930/E		11.0#		
	3/4" thick core material						
,	 Mounted to bracket which bolts to 						
*	underside of worksurface • Must be used in conjuntion with privacy						
ITDC	Screen is laminate with matching edge band						
	 End Curved Divider Screens - 15" Height Curved top edge is 15" high at ends, 17" 	24"	ITDC1524/E		11.0#		
0.0	high in middle	30"	ITDC1530/E		11.0#		
	 3/4" thick core material 						
ITDC	Mounted to bracket which bolts to underside of worksurface						
	Must be used in conjuntion with privacy						
	screens						
	Screen is laminate with matching edge band						
	Saria						
			A				

HOW TO ORDER

Indicate the following information on order

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: • The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- · Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect surface finish. Refer to the **KI Color Addendum** or **KI** Fabrics & Finishes binder.

style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by Surface finish offerings are based on edge the supplier's color/pattern code:

> Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Curved Divider Screens

Delive Pricin	ered
Pricin	ng
	264
	275
\$ 2	294
3	309

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N.

Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Curved Divider Screens

			MODEL NUMBER	R		
			Basic	Surface	Approx. Packaged	
	MODEL	D	Model	Finish	Weight	
	Middle Curved Divider Screens - 9"	24"	ITDC924/M74P		11.0#	
	Height	24"	ITDC924/MME		11.0#	
	 Curved top edge is 9" high at ends, 11" high in middle 	24"	ITDC924/MPL		11.0#	
	3/4" thick core material	30"	ITDC930/M74P		11.0#	
	Mounted to bracket which bolts to underside of worksurface Must be used in conjuntion with privacy screens	30"	ITDC930/MME		11.0#	
ITDC		30"	ITDC930/MPL		11.0#	
	Screen is laminate with matching edge band					
	Middle Curved Divider Screens - 15" Height	24"	ITDC1524/M74P		11.0#	
		24"	ITDC1524/MME		11.0#	
	Curved top edge is 15" high at ends, 17" high in middle.	24"	ITDC1524/MPL		11.0#	
	high in middle • 3/4" thick core material	30"	ITDC1530/M74P		11.0#	
	Mounted to bracket which bolts to	30"	ITDC1530/MME		11.0#	
***	underside of worksurface	30"	ITDC1530/MPL		11.0#	
ITDC	 Must be used in conjuntion with privacy screens Screen is laminate with matching edge 					
	band					
			A	<u> </u>		

HOW TO ORDER

Indicate the following information on order form:

- 1. Quantity of each item.
- Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- Alpha-numeric characters in place of

 □ indicate that no other alternatives
 are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- ③ Select surface finish.
 Refer to the KI Color Addendum or KI Fabrics & Finishes binder.

Faurice of Fillisties united:

Surface finish offerings are based on edge the supplier's color/pattern code: style selections.

FINISH INFORMATION

Additional Laminate Offering

Additional laminates beyond KI standard offering, are available with two weeks extended leadtime. To specify additional laminates, use these designators followed by the supplier's color/pattern code:

Formica - LF/supplier's color pattern code Nevamar - LN/supplier's color pattern code Wilsonart - LW/supplier's color pattern code



InTandem® Table System Curved Divider Screens

Deli Pric	vered	
	295	
	295	
	295	
	308	
	308	
	308	
\$	306	
	306	
	306	
	319	
	319	
	319	

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C


Shipping

Ships knocked down, FOB Bonduel, WI 54107, freight prepaid. Freight class 70.

Wharton™ Lectern

General Information







Wharton™ Lectern w/out Keyboard Drawer (WLECT.NKBD)

Features		
Electrically-adjusted height	•	•
Perforated metal shrouds	•	•
Slide-open frosted Plexiglas	•	•
Technology well with simplex power outlet	•	•
Light	•	•
Microphone	•	•
2 additional external power outlets	•	•
Swing-out drink caddies	•	•
Pencil rail	•	•
Sliding keyboard drawer with mouse pad	•	
Drop-in black plastic storage tray	•	•
Frosted Plexiglas filler panel	•	•
General Dimensions		
Adjustable height	37-1/2" - 47"	37-1/2" - 47"

Adjustable height	37-1/2" - 47"	37-1/2" - 47"
Тор	21.6"D x 31.8"W - 47.8"W	21.6"D x 31.8"W - 47.8"W
Technology well	3"D x 12"W x 12"H	3"D x 12"W x 12"H
Drop-in storage tray	12"D x 13.5"W	12"D x 13.5"W
Acrylic insert	13.7"D x 14.5"W	13.7"D x 14.5"W

SPECIFICATIONS

Note: Pictures shown above with Creston Monitor which is purchased separately.

Metal components of the lectern are powder coated for superior appearance and durability. All plastic and fiberglass components are color matched in accordance with the KI color program.

Height Adjustment

Lecterns are height adjustable through a range of 37.5" to 47". Adjustment is accomplished by the push of a button, conveniently located on the presenter side.

Lectern Top

Tops are constructed of 1" thick frosted acrylic (Plexiglas). Organic top shape is 21.6" deep by 31.8" wide. Flush-mounted into the top are two 1/4"-thick recessed sliding surfaces. When the surfaces are open, top measures 47.8" wide. Sculpted aluminum pencil rail is located at the bottom

of each surface.

Lectern Basin

The basin is constructed of 3/16" thick fiberglass and painted to match metal components. The basin supports the acrylic top and houses the control panel or storage tray. It also houses the optional keyboard tray, the technology well, and the adjustment motor and controller.

Lectern Column

Outermost shrouds of column are formed from 18-gauge perforated sheet steel. Bottom shroud can be slid upward to allow limited access to wiring. Shrouds can be completely removed to allow wiring of additional technology. Power module with two simplex plugs is located on the front shroud (speaker side). Inside the shrouds is a telescoping frame assembly, comprised of two 3" diameter x 14-gauge steel tubes that are welded to a steel foot. Two 2-5/8" x 16-gauge steel tubes telescope inside the 3" outer tubes. Nylon bushings ensure a smooth, telescopic action between the

tubes.

Lectern Base

The base is machined out of 5/8" plate thick steel. The crescent shape provides excellent stability and clearance for the speaker's feet.

Technology Well

The technology well is a 3" deep x 12" wide x 12" high tapered repository for management of power and data cables. The well is accessible via a hinged door in the acrylic top, featuring one simplex power outlet and room to store a laptop cord, including the power transformer. The well is constructed of 16-gauge sheet steel. The door is machined of 1"-thick acrylic, and matches the top in material and finish. The door has a steel lip, which engages a magnetic latch. A 1/2" relief allows the cords to be routed from the well while the door is closed.

Drink Caddies

Two caddies store below the basin and swing out for use. Caddies are made of aluminum and powder coated for durability. The

right caddy has a recessed pocket for holding mugs or miscellaneous items. The left caddy has a cupholder with a formed wire basket for holding large drink containers.

Microphone

The microphone is a high-quality gooseneck microphone from Shure (model MX412/C). The microphone is installed into the acrylic top and isolated via a shock mount. The microphone supplied with the Wharton™ Lectern includes a standard XLR connection. Audio speakers and amplification are required to project sound. Audio speakers and amplification are not supplied by KI.

Light

The light is a high-quality, low voltage gooseneck lamp from Littlite (model MX412/C). This model features a 5W dimmable halogen bulb on a 12" gooseneck. The light is factory installed to the acrylic top and wired into the powerstrip inside the lectern. For replacement purposes, the bulb is a Q5 tungsten-halogen bulb rated 12V, 380mA (AC or DC). 5 watt.



Wharton[™] Lectern
General Information

Drop-In Storage Tray

The storage tray is used when a Crestron monitor is not purchased, and simply drops into the opening beneath the sliding doors. The storage tray is made of vacuum-formed ABS sheet, 3/16" thick and measures 12" deep x 13.5" wide. The depth varies from 1" to 2.8" so that a laptop placed in the tray will rest at a comfortable keying angle.

Acrylic Insert

The insert is used when the presenter wants the maximum amount of surface space instead of a Crestron monitor or the storage tray. The acrylic insert measures 13.7" deep x 14.5" wide and is 1/4" thick.

Crestron Control Panel

The lectern top is designed to accept a separately purchased Crestron touchpanel control system, model TS1542-C. Crestron can be reached at 1-800-237-2041 or visit their website (www.crestron.com) to find the dealer nearest you.

INFORMATION

Warranty

Refer to KI Terms & Conditions document or visit ki.com

Wharton[™] Lectern

		MODEL NUM	BER	
				Арргох.
		Basic	Paint	Packaged
	MODEL	Model	Color	Weight
Л	Wharton Lectern • Electrically adjustable height from 37.5" -	WLECT.KBD		268.0#
	47"			
	 Frosted Plexiglas top slides open from 			
	31.8" - 47.8"			
	 Accommodates field-installed, separately purchased* Crestron LCD control panel 			
	below the slide-open top. See www.			
	crestron.com			
	 Black plastic tray stores a laptop com- puter below the slide-open top when no 			
	control panel is used			
LIDDAT	Frosted Plexiglas panel fills opening			
HRDPT	below the slide-open top when neither control panel or laptop are used			
	Black gooseneck adjustable microphone			
	and adjustable halogen note light with			
	dimmerTwo additional grounded power outlets			
	on speaker side of lectern column			
	 Pop-open technology well in top with 			
	grounded power outlet for plug-in of			
	speaker's laptop6' long power cord plugs into wall or			
	floor outlet providing power to lectern			
	Includes a factory installed black sliding			
	keyboard drawer with slide-out non- handed mouse pad			
	There are 6 rubber feet attached to the			
	underside of the base			
	Ships Fully Assembled			
	Wharton Lectern	WLECT.NKBD		244.0#
4 -	 Includes all of the above except does not 			
	have a sliding keyboard drawer			
	 Black plastic snap-in cover fills keyboard opening in lectern body 			
	Ships Fully Assembled			
HRDPT				
	'	•		
		w	U	

HOW TO ORDER

Indicate the following information on order

- Quantity of each item.
 Model number, including options. See
 "How To Build a Model Number".
- 3. Any special service required.

Note: \bullet The \square indicates that a choice is required.

- \bullet The absence of the \square indicates that no choice is required.
- \bullet Alpha-numeric characters in place of \square indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A Select basic model.
- BSelect paint color. Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.

4

Wharton™ Lectern

Delivered Pricing

\$ 10968

\$ 10806

SPECIAL SERVICES

Special Carton Marking

With specially marked information

N/C

Shipping

Ships assembled, FOB Manitowoc, WI 54220, freight prepaid. Freight class 125.

Index

Model No.	Description	Page	Model No.	Description	Page
46.0782.24	Electrical: Worksurface-to-Worksurface 10-Wire Connector	54	ITDV1124/M74P	Divider Screens: Middle Divider Screens - 11" Height	128
46.5003	Electrical: Back-to-Back Ganging Kit	110	ITDV1130/E	Divider Screens: End Divider Screens - 11" Height	60
47.0568.20	Electrical: 8-Wire to 10-Wire Adaptor	52	ITDV1130/M74P	Divider Screens: Middle Divider Screens - 11" Height	62
47.0706.1.BL	Electrical Accessories: Receptacles - 6 Circuit	16	ITDV1724/E	Divider Screens: End Divider Screens - 17" Height	126
47.0709.30	Electrical Accessories: 8-Wire to 10-Wire Adaptor	18	ITDV1724/M74P	Divider Screens: Middle Divider Screens - 17" Height	128
48.0268.17	Electrical: Worksurface-to-Worksurface 10-Wire Connector	110	ITDV1730/E	Divider Screens: End Divider Screens - 17" Height	60
4BT6	Electrical Accessories: Quad-Block	16	ITDV1730/M74P	Divider Screens: Middle Divider Screens - 11" Height	62
AC8IF.108	Activ8® Infeed	20	ITDV2330/E	Divider Screens: End Divider Screens - 23" Height	60
AC8JP.29	Activ8® Jumper	24	ITDV2330/M74P	Divider Screens: Middle Divider Screens - 23" Height	62
AC8PUM	Activ8® Power-Up Module	22	ITELW29	Electrical: Vertical Wireway Cover	108
AC8RPTDL.12	Activ8® Module and Attachment Bracket	20	ITFB36L/NN	Non-Powered Beams: End-of-Run/Left Beam - No Power (NN)	48
AC8RPTIT.12	Activ8® Module and Attachment Bracket	114	ITFB36L/T6	10-Wire/6 Circuit Beams: End-of-Run/Left Beam - 10 Wire (6C)	46
AC8VMC	Activ8® Villa Power Module with Metal Cover	22	ITFB36M/NN	Non-Powered Beams: Middle Beam - No Power (NN)	48
AC8VMN	Activ8® Villa Power Module without Cover	22	ITFB36M/T6	10-Wire/6 Circuit Beams: Middle Beam - 10 Wire (6C)	44
DLCA	Non-Electrical Accessories: Caster (Set of 4)	14	ITFB36R/NN	Non-Powered Beams: End-of-Run/Right Beam - No Power (NN)	48
DLGANG	Non-Electrical Accessories: Table Ganger (Set of 2 for one	4.4	ITFB36R/T6	10-Wire/6 Circuit Beams: End-of-Run/Right Beam - 10 Wire (6C)	46
DI INVTE I	table-to-table gang)	14	ITFB36S/NN ITFB36S/T6	Non-Powered Beams: Stand Alone Beam - No Power (NN)	48
DLINYT6.L DLSPLICE	Electrical Accessories: NY Infeed - 10 Wire	18	ITFC302429/DC	10-Wire/6 Circuit Beams: Stand Alone Beam - 10 Wire (6C)	44
DESPEIGE	Non-Electrical Accessories: Table Splice Plate (Set of 2 for one table-to-table connection)	14	ITFC302429/DC	Freestanding Frames with Casters: 29" Legs - With Data Cover (DC) Freestanding Frames with Casters: 29" Legs - Without Data Cover (ND	106
DLT6JT	Electrical Accessories: Worksurface-to-Worksurface 10-Wire	14	ITFC302429/ND	Freestanding Frames with Casters: 28" Legs - Without Data Cover (ND)	106
DETOOT	Connector for Rectangular Worksurface	16	ITFC304238/ND	Freestanding Frames with Casters: 38" Legs - With Data Cover (ND	
DLT6JW	Electrical Accessories: Worksurface-to-Worksurface 10-Wire	10	ITFL3029	"C" Legs: Standard Flat Screen Garage® "C" Leg	50
D210011	Connector for Wedges	16	ITFLADA	"C" Legs: ADA "C" Leg	50
DLTRUCK	Non-Electrical Accessories: Table Truck	14	ITFP1136	Rectangular Privacy Screens: Rectangular Privacy Screens - 11" Heigh	
DLW2430	Wedges: Wedges	12	ITFP1736	Rectangular Privacy Screens: Rectangular Privacy Screens - 17" Heigh	
DLW2445	Wedges: Wedges	12	ITFP2336	Rectangular Privacy Screens: Rectangular Privacy Screens - 23" Heigh	
DLW2460	Wedges: Wedges	12	ITFPA1136	Stand Alone Privacy Screen: Rectangular Stand Alone Privacy	
DLW2490	Wedges: Wedges	12		Screens - 11" Height	58
DLW3030	Wedges: Wedges	12	ITFPA1736	Stand Alone Privacy Screen: Rectangular Stand Alone Privacy	
DLW3045	Wedges: Wedges	12		Screens - 17" Height	58
DLW3060	Wedges: Wedges	12	ITFW3036	Worksurface - Poly Grommet/PowerUp: Single Unit	30
DLW3090	Wedges: Wedges	12	ITFW3060	Worksurface - Poly Grommet/PowerUp: Double Unit	30
DX243627-NP	Fixed Leg Tables/No Power: Fixed Leg Table, 24"D	6	ITFW3236	Worksurface - Poly Grommet/PowerUp: Single Unit - ADA Tops	30
DX243627-T6	Fixed Leg Tables/Power: Fixed Leg Table, 24"D	4	ITHK.27	Electrical: Floor Infeed Hard-Wire Kit	108
DX303627-NP	Fixed Leg Tables/No Power: Fixed Leg Table, 30"D	10	ITMB24/HC/DC	Middle Beams: Middle Beam - Hard-Wire (HC) - With Data Cover (DC)	94
DX303627-T6	Fixed Leg Tables/Power: Fixed Leg Table, 30"D	8	ITMB24/HC/ND	Middle Beams: Middle Beam - Hard-Wire (HC) - Without Data	
FSGRECEIVER	Electrical: Infrared Receiver	52		Cover (ND)	90
FSGREMOTE	Electrical: Infrared Remote Control Unit	52	ITMB24/NN/DC	Middle Beams: Middle Beam - No Power (NN) - With Data Cover (DC)	96
IHB.RECP	Electrical: Hard-Wire Back-to-Back Electrical Receptacle	112	ITMB24/NN/ND	Middle Beams: Middle Beam - No Power (NN) - Without Data	
INTCPULG	Legs and CPU Clamps: CPU Clamp - Large	102		Cover (ND)	92
INTCPUSM	Legs and CPU Clamps: CPU Clamp - Small	102	ITMB24/T6/DC	Middle Beams: Middle Beam - 10-Wire (T6) - With Data Cover (DC)	94
ISMT3036	Worksurfaces - Poly Grommet/PowerUp: Single Unit	34	ITMB24/T6/ND	Middle Beams: Middle Beam - 10-Wire (T6) - Without Data Cover (ND) 90
ISMT3060	Worksurfaces - Poly Grommet/PowerUp: Double Unit	36	ITPCC1524	Corner Curved Privacy Screen: Corner Curved Privacy Screens	
ITBBT6.30	Electrical: 10-Wire Harness for Back-to-Back Configurations	110	ITD00004	- 15" Height	134
ITCB24/HC/DC	Corner Middle Beams: Corner Middle Beam - Hard-Wire (HC) -	100	ITPCC924	Corner Curved Privacy Screen: Corner Curved Privacy Screens	104
ITODO 4 /LIO /NID	With Data Cover (DC)	100	ITDC1104	- 9" Height	134
ITCB24/HC/ND	Corner Middle Beams: Corner Middle Beam - Hard-Wire (HC) -	00	ITPS1124	Rectangular Privacy Screens: Rectangular Privacy Screens -	100
ITCD24/NINI/DC	Without Data Cover (ND) Corpor Middle Peams: Corpor Middle Peam No Pewer (NN)	98	ITDC1704	11" Height Postangular Privacy Screens: Postangular Privacy Screens	120
ITCB24/NN/DC	Corner Middle Beams: Corner Middle Beam - No Power (NN) -	100	ITPS1724	Rectangular Privacy Screens: Rectangular Privacy Screens -	100
ITCDQ4/NINI/NID	With Data Cover (DC)	100	ITDC0204	17" Height	120
ITCB24/NN/ND	Corner Middle Beams: Corner Middle Beam - No Power (NN) - Without Data Cover (ND)	98	ITPS2324	Rectangular Privacy Screens: Rectangular Privacy Screens - 23" Height	120
ITCB24/T6/DC	Corner Middle Beams: Corner Middle Beam - 10-Wire (T6) -	30	ITPSA1124	Stand Alone Privacy Screens: Rectangular Stand Alone Privacy	120
110024/10/00	With Data Cover (DC)	100	IIFOATIZ4	Screens - 11" Height	122
ITCB24/T6/ND	Corner Middle Beams: Corner Middle Beam - 10-Wire (T6) -	100	ITPSA1724	Stand Alone Privacy Screens: Rectangular Stand Alone Privacy	122
110024/10/110	Without Data Cover (ND)	98	III OAI124	Screens - 17" Height	122
	Legs and CPU Clamps: "C" Leg	102	ITPSAC1524	Stand Alone Curved Privacy Screen: Rectangular Stand Alone	122
ITCI 2427	· · ·	124	111 0A01324	Curved Privacy Screens - 15" Height	132
ITCL2427	Corner Drivacy Screens: Corner Drivacy Screens - 11" Height	124	ITPSAC924	Stand Alone Curved Privacy Screen: Rectangular Stand Alone	132
ITCP1124	Corner Privacy Screens: Corner Privacy Screens - 11" Height	101			
ITCP1124 ITCP1724	Corner Privacy Screens: Corner Privacy Screens - 17" Height	124 124	111 0/10324		120
ITCP1124 ITCP1724 ITCP2330	Corner Privacy Screens: Corner Privacy Screens - 17" Height Corner Privacy Screens: Corner Privacy Screens - 23" Height	124		Curved Privacy Screens - 9" Height	132
ITCP1124 ITCP1724 ITCP2330 ITCS27	Corner Privacy Screens: Corner Privacy Screens - 17" Height Corner Privacy Screens: Corner Privacy Screens - 23" Height Legs and CPU Clamps: Corner Support Leg	124 102	ITPSC1524	Curved Privacy Screens - 9" Height Rectangular Curved Privacy Screens: Rectangular Curved	
ITCP1124 ITCP1724 ITCP2330 ITCS27 ITDC1524/E	Corner Privacy Screens: Corner Privacy Screens - 17" Height Corner Privacy Screens: Corner Privacy Screens - 23" Height Legs and CPU Clamps: Corner Support Leg Curved Divider Screens: End Curved Divider Screens - 15" Height	124 102 136	ITPSC1524	Curved Privacy Screens - 9" Height Rectangular Curved Privacy Screens: Rectangular Curved Privacy Screens - 15" Height	132 130
ITCP1124 ITCP1724 ITCP2330 ITCS27 ITDC1524/E ITDC1524/M74P	Corner Privacy Screens: Corner Privacy Screens - 17" Height Corner Privacy Screens: Corner Privacy Screens - 23" Height Legs and CPU Clamps: Corner Support Leg Curved Divider Screens: End Curved Divider Screens - 15" Height Curved Divider Screens: Middle Curved Divider Screens - 15" Height	124 102 136 138		Curved Privacy Screens - 9" Height Rectangular Curved Privacy Screens: Rectangular Curved Privacy Screens - 15" Height Rectangular Curved Privacy Screens: Rectangular Curved	130
ITCP1124 ITCP1724 ITCP2330 ITCS27 ITDC1524/E	Corner Privacy Screens: Corner Privacy Screens - 17" Height Corner Privacy Screens: Corner Privacy Screens - 23" Height Legs and CPU Clamps: Corner Support Leg Curved Divider Screens: End Curved Divider Screens - 15" Height	124 102 136	ITPSC1524	Curved Privacy Screens - 9" Height Rectangular Curved Privacy Screens: Rectangular Curved Privacy Screens - 15" Height	





Model No.	Description	Page
ITSB24/HC/ND	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	
	Beam - Hard-Wire (HC) - Without Data Cover (ND)	82
ITSB24/NN/DC	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	
	Beam - No Power (NN) - With Data Cover (DC)	88
ITSB24/NN/ND	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	
	Beam - No Power (NN) - Without Data Cover (ND)	84
ITSB24/T6/DC	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	
	Beam - 10-Wire (T6) - With Data Cover (DC)	86
ITSB24/T6/ND	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	
	Beam - 10-Wire (T6) - Without Data Cover (ND)	82
ITSB36/NYLT6/DC	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	-
	Beam - NY Infeed (NYL) - With Data Cover (DC)	88
ITSR36/NYLT6/ND	End-of-Run/Stand Alone Beams: End-of-Run Stand Alone	00
110000/141210/140	Beam - Hard-Wire (HC) - Without Data Cover (ND)	84
ITSC2424/NB	Worksurfaces - Poly Grommet/PowerUp: Corner (Non-Pow-	0-1
11002424/100	ered Beam) Square	70
ITTC2436/NB	Worksurfaces - Poly Grommet/PowerUp: Corner (Non-Pow-	70
11102430/ND	ered Beam) Transitional	70
ITTC2436/PB	Worksurfaces - Poly Grommet/PowerUp: Corner (Powered	70
11162430/FB		72
ITTT6.24	Beam) Transitional Electrical: 10-Wire Harness for T-Shaped Configurations	
		110
ITWK.4229	Freestanding Frames with Casters: Wheelchair Accessible Kit	106
ITWQ2460/NB	Worksurfaces - Poly Grommet/PowerUp: Rectangular (Non-	cc
ITWO04CO/DD	Powered Beam)-Four Grommets	66
ITWQ2460/PB	Worksurfaces - Poly Grommet/PowerUp: Rectangular (Pow-	co
ITM/CO 4O 4/NID	ered Beam)-Four Grommets	68
ITWS2424/NB	Worksurfaces - Poly Grommet/PowerUp: Rectangular (Non-	0.0
ITM00404/DD	Powered Beam)-Two Grommets	66
ITWS2424/PB	Worksurfaces - Poly Grommet/PowerUp: Rectangular (Pow-	0.0
11/514/00 40	ered Beam)-Two Grommets	68
IVFW3042	Worksurface - Villa Metal Grommet/Power Module: Single Unit	32
IVFW3066	Worksurface - Villa Metal Grommet/Power Module: Double Unit	32
IVFW3242	Worksurface - Villa Metal Grommet/Power Module: Single Unit	0.0
I) /B 4T00 40	- ADA Tops	32
IVMT3048	Worksurfaces - Villa Metal Grommet/Power Module: Single Unit	38
IVMT3066	Worksurfaces - Villa Metal Grommet/Power Module: Double Unit	40
IVTC2436/NB	Worksurfaces - Villa Metal Grommet/Power Module: Corner	7.0
	(Non-Powered Beam) Transitional	78
IVTC2436/PB	Worksurfaces - Villa Metal Grommet/Power Module: Corner	
	(Powered Beam) Transitional	80
IVWS2424/NB	Worksurfaces - Villa Metal Grommet/Power Module: Rectan-	
	gular (Non-Powered Beam)-Two Grommets	74
IVWS2424/PB	Worksurfaces - Villa Metal Grommet/Power Module: Rectan-	
	gular (Powered Beam)-Two Grommets	76
LTREMOTE	Accessories: Locking Remote Control	42
PC.OSWS	Electrical Accessories: Power Strip	18
PCHK0	Electrical: Overhead Infeed Hard-Wire Kit	108
PCOF.T6	Electrical: Overhead Infeed Circuit Pre-wired	52
PTFF	Electrical Accessories: Infeed 10-Wire/6-Circuit	18
SMTTILT	Accessories: Monitor Tilt	42
SMTWEIGHT1	Accessories: Single Counterweight Kit	42
SMTWEIGHT2	Accessories: Double Counterweight Kit	42
WLECT.KBD	Wharton Lectern	142
WLECT.NKBD	Wharton Lectern	142

KI 1330 Bellevue Street P.O. Box 8100 Green Bay, Wisconsin 54308-8100 I-800-424-2432 www.ki.com

KI and Furnishing Knowledge are registered trademarks of Krueger International, Inc.

© 2011 KI All Rights Reserved. Litho in USA. Code KI-11485R1/KI/VL/211