

# FRETWORK

## Crosshatch

Modular Tile

### Construction

Tufted, Tip Shear

### Tile Size

1 m x 1 m (39.4" x 39.4")

### Yarn Type

Milliken-Certified WearOn® Nylon  
Type 6,6

### Stain Repel / Stain Resist / Soil Release

StainSmart®

### Antimicrobial

AlphaSan® AF Built-In Protection†

### Dye Method

DDI (Digital Dye Infusion)

### Tufted Face Weight

27 oz/yd<sup>2</sup> (915.5 g/m<sup>2</sup>)

### Tufts\*

144/in<sup>2</sup> (2,230/100 cm<sup>2</sup>)

### Finished Pile Height

0.17" (4.32 mm)

### Average Density (Finished)

5,718

### Standard Backing

PVC-Free Comfort Plus® ES Cushion  
Available with TractionBack®

### Recycled Content by Total Weight

ES Backing: 35.5% Pre-Consumer,  
0.0% Post-Consumer  
ESP Backing: 27.0% Pre-Consumer,  
10.0% Post-Consumer

### Nominal Total Thickness

0.37" (9.4 mm)

### Nominal Total Weight

111.0 oz/yd<sup>2</sup> (3,764 g/m<sup>2</sup>)

### Flammability (Radiant Panel

**ASTM-E-648)**

≥ 0.45 (Class I)

### Smoke Density (NFPA-258-T or

**ASTM-E-662)**

≤ 450

### Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 Wet or Dry

### Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

### Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

### Recommended Maintenance

MilliCare® Textile and Carpet Care  
Service Network

### Indoor Air Quality—CRI Green Label Plus™

GLP0793, Carpet Category 5Y

### Recommended Installation Method(s)

Monolithic

\* This product utilizes Milliken's patented, high density tufting process called multiple yarn infusion. Conventional measurements of gauge and stitch rate are inadequate and misleading. Therefore, tufts per square inch are shown to provide accurate specifications.

### WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®)

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.