# Milliken.

### **FRETWORK**

### Kaleidoscope

Modular Tile

#### Construction

Tufted, Tip Shear

#### Tile Size

1 m x 1 m (39.4" x 39.4")

#### **Yarn Type**

Milliken-Certified WearOn® Nylon Type 6,6

### Stain Repel / Stain Resist / Soil Release

StainSmart®

#### **Antimicrobial**

AlphaSan® AF Built-In Protection†

#### **Dye Method**

DDI (Digital Dye Infusion)

#### **Tufted Face Weight**

 $27 \text{ oz/yd}^2 (915.5 \text{ g/m}^2)$ 

#### Tufts\*

144/in<sup>2</sup> (2,230/100 cm<sup>2</sup>)

#### **Finished Pile Height**

0.17" (4.32 mm)

#### **Average Density (Finished)**

5,718

#### **Standard Backing**

PVC-Free Comfort Plus® ES Cushion

#### **Recycled Content by Total Weight**

ES Backing: 35.5% Pre-Consumer, 0.0% Post-Consumer ESP Backing: 27.0% Pre-Consumer, 10.0% Post-Consumer

#### **Nominal Total Thickness**

0.37" (9.4 mm)

#### **Nominal Total Weight**

 $111.0 \text{ oz/yd}^2 (3,764 \text{ g/m}^2)$ 

### Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

### **Smoke Density (NFPA-258-T or**

**ASTM-E-662)** 

 $\leq 450$ 

## Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

#### **Lightfastness (AATCC 16E)**

≥ 4.0 at 80 Hours

#### **Crocking (AATCC 165)**

 $\geq$  4.0 Wet or Dry

## Static Electricity (AATCC-134) 20% R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

### Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

#### **Recommended Maintenance**

MilliCare® Textile and Carpet Care Service Network

### Indoor Air Quality—CRI Green Label

GLP0793, Carpet Category 5Y

### **Recommended Installation Method(s)**Monolithic

#### WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®) Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability Lifetime Tuft Bind Lifetime Edge Ravel Flammability









This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

<sup>\*</sup> This product utilizes Milliken's patented, high density tufting process called multiple yarn infusion. Conventional measurements of gauge and stitch rate are inadequate and misleading. Therefore, tufts per square inch are shown to provide accurate specifications.