## Milliken.

## **SENSE**

## Surround

Modular Tile

Construction

Tufted, Textured Loop

**Tile Size** 

1 m x 1 m (39.4" x 39.4")

**Yarn Type** 

Antron Legacy® Nylon Type 6,6

**Stain Repel / Stain Resist / Soil** 

Release

StainSmart®

**Bleach Resistance** 

ColorSeal®

**Antimicrobial** 

AlphaSan® AF Built-In Protection†

**Dye Method** 

DDI (Digital Dye Infusion)

**Tufted Face Weight** 

 $20 \text{ oz/yd}^2 (678.1 \text{ g/m}^2)$ 

Gauge

1/13

Stitches Per Inch

11.2

**Tufts** 

146/in<sup>2</sup> (2,255/100 cm<sup>2</sup>)

**Finished Pile Height** 

0.14" (3.56 mm)

**Finished Pile Thickness** 

0.09" (2.29 mm)

**Average Density (Finished)** 

7,400

**Standard Backing** 

PVC-Free Underscore® ES Cushion

Available with TractionBack®

**Recycled Content by Total Weight** 

ES Backing: 37.1% Pre-Consumer,

0.0% Post-Consumer

ESP Backing: 27.0% Pre-Consumer,

10.1% Post-Consumer

**Nominal Total Thickness** 

0.32" (8.1 mm)

**Nominal Total Weight** 

 $94.5 \text{ oz/yd}^2 (3,204 \text{ g/m}^2)$ 

Flammability (Radiant Panel

**ASTM-E-648**)

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or** 

**ASTM-E-662)** 

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

**Lightfastness (AATCC 16E)** 

≥ 4.0 at 80 Hours

**Crocking (AATCC 165)** 

 $\geq$  4.0 Wet or Dry

Static Electricity (AATCC-134) 20%

R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating (TARR)** 

Severe Traffic End-Use Applications

**Recommended Maintenance** 

MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label

Plus™

GLP0793, Carpet Category 5Y

**Recommended Installation Method(s)** 

Monolithic

## WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®) Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability Lifetime Tuft Bind Lifetime Edge Ravel Flammability









This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.