MIDNIGHT SPARKLE

Overview II

illiken,

Construction Tufted, Textured Loop

Tile Size 36" X 36" (91.4 x 91.4 cm)

Yarn Type Milliken-Certified WearOn® Nylon Type 6,6

Stain Repel / Stain Resist / Soil Release StainSmart®

Antimicrobial AlphaSan[®] AF Built-In Protection⁺

Dye Method Millitron®

Tufted Face Weight 24 oz/yd^2 (814 g/m²)

Gauge 1/8

Stitches Per Inch 8.8

Tufts 70.4/in² (1,090/100 cm²)

Finished Pile Height 0.11" (2.79 mm)

Average Density (Finished) 7,855

Standard Backing PVC-Free Comfort Plus® ES Cushion Available with TractionBack®

Recycled Content by Total Weight ES Backing: 47.3% Pre-Consumer, 0.0% Post-Consumer ESP Backing: 36.0% Pre-Consumer, 11.3% Post-Consumer

Nominal Total Thickness 0.35" (8.9 mm)

Nominal Total Weight 112 oz/yd² (3,798 g/m²)

Flammability (Radiant Panel **ASTM-E-648)** \geq 0.45 (Class I)

Smoke Density (NFPA-258-T or **ASTM-E-662**) < 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859 Self-Extinguishing

Lightfastness (AATCC 16E) > 4.0 at 80 Hours

Crocking (AATCC 165) \geq 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H.,70° F. ≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR) Severe Traffic End-Use Applications

Recommended Maintenance MilliCare[®] Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™ GLP0793, Carpet Category 5Y

Recommended Installation Method(s) Monolithic

WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®) Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency

Lifetime Floor Release Lifetime Cushion Resiliency Lifetime Moisture Resistance Lifetime Delamination of Backing Lifetime Staining/Soiling (StainSmart®)





Customer Concierge 800.824.2246 | millikenfloors.com © 2016 Milliken & Company | Made in the USA





Lifetime Dimensional Stability Lifetime Tuft Bind Lifetime Edge Ravel Flammability

This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

 \uparrow (EU) No 528/2012 (BPR): Overview II contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.