## Milliken.

## MIDNIGHT SPARKLE

## Vineyard

Modular Tile

Construction

Tufted, Textured Loop

Tile Size

36" X 36" (91.4 x 91.4 cm)

Yarn Type

Milliken-Certified WearOn® Nylon Type 6,6

Stain Repel / Stain Resist / Soil Release

StainSmart®

**Antimicrobial** 

AlphaSan® AF Built-In Protection†

**Dye Method** 

Millitron®

**Tufted Face Weight** 

 $24 \text{ oz/yd}^2 (814 \text{ g/m}^2)$ 

Gauge

1/8

**Stitches Per Inch** 

8.8

**Tufts** 

70.4/in<sup>2</sup> (1,090/100 cm<sup>2</sup>)

**Finished Pile Height** 

0.11" (2.79 mm)

**Average Density (Finished)** 

7,855

**Standard Backing** 

PVC-Free Comfort Plus® ES Cushion

Available with TractionBack®

**Recycled Content by Total Weight** 

ES Backing: 47.3% Pre-Consumer, 0.0% Post-Consumer

ESP Backing: 36.0% Pre-Consumer, 11.3% Post-Consumer

**Nominal Total Thickness** 

0.35" (8.9 mm)

**Nominal Total Weight** 

 $112 \text{ oz/yd}^2 (3,798 \text{ g/m}^2)$ 

Flammability (Radiant Panel

**ASTM-E-648)** 

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or** 

**ASTM-E-662)** 

 $\leq 450$ 

**Methenamine Pill Test (CPSC FF-1-70** 

or **ASTM D 2859** 

Self-Extinguishing

**Lightfastness (AATCC 16E)** 

> 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR)

Severe Traffic End-Use Applications

**Recommended Maintenance** 

MilliCare® Textile and Carpet Care

Service Network

Indoor Air Quality—CRI Green Label

Plus™

GLP0793, Carpet Category 5Y

**Recommended Installation Method(s)**Monolithic

WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®) Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability Lifetime Tuft Bind Lifetime Edge Ravel Flammability









This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.