

# MIDNIGHT SPARKLE

## Misty Valley

Modular Tile

**Construction**

Tufted, Textured Loop

**Tile Size**

36" X 36" (91.4 x 91.4 cm)

**Yarn Type**Milliken-Certified WearOn® Nylon  
Type 6,6**Stain Repel / Stain Resist / Soil Release**

StainSmart®

**Antimicrobial**

AlphaSan® AF Built-In Protection†

**Dye Method**

Millitron®

**Tufted Face Weight**24 oz/yd<sup>2</sup> (814 g/m<sup>2</sup>)**Gauge**

1/8

**Stitches Per Inch**

8.8

**Tufts**70.4/in<sup>2</sup> (1,090/100 cm<sup>2</sup>)**Finished Pile Height**

0.11" (2.79 mm)

**Average Density (Finished)**

7,855

**Standard Backing**PVC-Free Comfort Plus® ES Cushion  
Available with TractionBack®**Recycled Content by Total Weight**ES Backing: 47.3% Pre-Consumer,  
0.0% Post-Consumer  
ESP Backing: 36.0% Pre-Consumer,  
11.3% Post-Consumer**Nominal Total Thickness**

0.35" (8.9 mm)

**Nominal Total Weight**112 oz/yd<sup>2</sup> (3,798 g/m<sup>2</sup>)**Flammability (Radiant Panel****ASTM-E-648)**

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or****ASTM-E-662)**

≤ 450

**Methenamine Pill Test (CPSC FF-1-70****or ASTM D 2859**

Self-Extinguishing

**Lightfastness (AATCC 16E)**

≥ 4.0 at 80 Hours

**Crocking (AATCC 165)**

≥ 4.0 Wet or Dry

**Static Electricity (AATCC-134) 20% R.H., 70° F.**

≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating (TARR)**

Severe Traffic End-Use Applications

**Recommended Maintenance**MilliCare® Textile and Carpet Care  
Service Network**Indoor Air Quality—CRI Green Label Plus™**

GLP0793, Carpet Category 5Y

**Recommended Installation Method(s)**

Monolithic

**WARRANTIES**

Lifetime Antimicrobial Protection (AlphaSan®)

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.