

CENTRO

Draft

Modular Tile

Construction

Tufted, Textured Loop

Tile Size

1 m x 1 m (39.4" x 39.4")

Yarn TypeMilliken-Certified WearOn® Nylon
Type 6,6**Stain Repel / Stain Resist / Soil Release**

StainSmart®

Antimicrobial

AlphaSan® AF Built-In Protection†

Dye Method

Millitron®

Gauge

1/10

Stitches Per Inch

14.4

Tufts144/in² (2,230/100 cm²)**Standard Backing**PVC-Free Underscore™ ES Cushion
Available with TractionBack®**Recycled Content by Total Weight**ES Backing: 40.9% Pre-Consumer,
0.0% Post-Consumer
ESP Backing: 30.0% Pre-Consumer,
11.0% Post-Consumer**Nominal Total Thickness**

0.31" (7.9 mm)

Nominal Total Weight87 oz./yd² (2,940 g/m²)**Flammability (Radiant Panel
ASTM-E-648)**

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or
ASTM-E-662)**

≤ 450

**Methenamine Pill Test (CPSC FF-1-70
or ASTM D 2859)**

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

**Static Electricity (AATCC-134) 20%
R.H., 70° F.**

≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating
(TARR)**

Severe Traffic End-Use Applications

Recommended MaintenanceMilliCare® Textile and Carpet Care
Service Network**Indoor Air Quality—CRI Green Label
Plus™**

GLP0793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic

WARRANTIESLifetime Antimicrobial Protection (AlphaSan®)
Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern PermanencyLifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Flammability

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.