

## Digital Dye Injected or Continuous Dyed Modular Carpet Tile Milliken & Company

Final Assembly: LaGrange, GA, USA

Life Expectancy: 15 Years

End of Life Options: Salvageable/Reusable In Its

Entirety

## Ingredients:

Face Fiber: Poly[Imino(1,6-Dioxo-1,6-Hexanediyl)Imino-1,6-Hexanediyl]; Backing: Aluminatesilicate, Calcium Carbonate, Polyurethane, Bitumens, Extracts of Steam-Refined and Air-Refined, Steam-Refined Bitumens, Polyethylene Terephthalate/Polybutylene Terephthalate, Polypropylene, Calcium Oxide, Styrene-Butadiene-Vinylidene Chloride Based Polymer, Styrene-Butadiene Copolymers, Dihydrogen Oxide, Fiberglass, Hydrocarbons, C6-20, Polymers, Hydrogenated, 2-Propenoic Acid, Polymer with 1-Propene, Potassium Oxide (K2O), Nylon 6, Quartz; Various Additives

## Living Building Challenge Criteria:

MKN-0014 VOC Content: N/A



EXP. 01 JAN 2019 VOC Emissions: CDPH Compliant

**Declaration Status:** 

LBC Red List Free

□ Declared

MANUFACTURER CLAIMS VERIFIED BY WAP Sustainability INTERNATIONAL **LIVING FUTURE** INSTITUTE™ declareproducts.com