

# SPORTS AND MULTI-FUNCTIONAL FLOORING

Training®

Product Specification

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** High performance recreational commercial sheet flooring; extreme durability combined with easy maintenance. Recommended areas for use:

- Education – Gymnasiums, Sports Halls
- Retail – Sports demonstration areas
- Healthcare – Physical therapy areas
- Hospitality – Work out rooms

### 1.2. **Manufacturer:**

Tarkett  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarketta.com](http://www.tarketta.com)  
E-mail: [info@johnsonite.com](mailto:info@johnsonite.com)

Phone: (800) 899-8916  
(440) 543-8916  
Tech: Ext 9297  
Samples: Ext 9299

### 1.3. **Proprietary Product Description:**

**Construction:** Johnsonite's Training flooring is composed of a urethane coated clear wearlayer comprised of 90% binder with a thickness of 0.028" (0.7 mm).

#### 1.3.1. **Styles:**

- Specify TRN-R (Training)

#### 1.3.2. **Physical Characteristics:**

- Overall thickness is 0.197" (5.0 mm)
- Packaging: Available in 6' 6" (2 m) wide and approximately 67 linear feet (20.5 m) per roll.

## 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Sheet material meets ASTM F 1303, Type I, Grade 1, Class C performance sheet vinyl floorcovering with backing
- Static coefficient of friction: ASTM D 2047 > 0.6
- Static Load Limit: ASTM F 970 – 175 psi
- Fire Performance: Flooring Radiant Panel: ASTM E 648 – Class 1

## 3. INSTALLATION

See Johnsonite Training installation instructions for complete details.

### 3.1. **Adhesives:**

- **Johnsonite #925** Adhesive for Resilient Flooring:  
Approximate Coverage:  
Porous & non-porous Substrate: 125-150 sq. ft.
- **Johnsonite #975** Two-Part Polyurethane Adhesive:  
Approximate Coverage:  
Porous & non-porous Substrate: 150-175 sq. ft.

## 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

## 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Training maintenance instructions for complete maintenance details.

## 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarketta.com](http://www.tarketta.com) or contact Tarkett at 1-800-899-8916.