



TILE + PLANK

## EVENT SERIES CLASSIC PLANK (ECK)

# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Frost (FR) (BB32 only) Third Grain (TG) (3321, OL03, OL05, OL07) Natural Grain (NG) (all except the above colors)
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	11
<b>Adhesive:</b>	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

### Installation Methods:



HERRINGBONE

UNIDIRECTIONAL



Product shown: ECK 3305

<b>SIZES</b>	4" x 36" (10.16 cm x 91.44 cm) 6" x 36" (15.24 cm x 91.44 cm)
--------------	--

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals; Non-Toluene Ink System
<b>Indoor Air Quality:</b>	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Manufacturing:</b>	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

### QUICKSHIP PROGRAM

 All colors in this style

LEED v4  
MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

**EVENT SERIES**  
**CLASSIC STONE (ECL)**

# Tandus Centiva

A Tarkett Company

## SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Frost (FR) (7101, 7102, 7112, 7126, 7127) Quarry (QU) (7106, 7107, 7133)
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	8
<b>Adhesive:</b>	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

### Installation Methods:

Product specific.  
Please see tandus-centiva.com for more information.



QUARTER TURN



VERTICAL  
ASHLAR



HORIZONTAL  
ASHLAR



Product shown: ECL 7133

<b>SIZES</b>	12"x18" (30.48 cm x 45.72 cm) 18"x18" (45.72 cm x 45.72 cm)
--------------	--

## TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

## ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals; Non-Toluene Ink System
<b>Indoor Air Quality:</b>	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Manufacturing:</b>	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

## QUICKSHIP PROGRAM

 All colors in this style

LEED v4  
MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



- For samples, warranties and more information, visit tandus-centiva.com or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



**EVENT SERIES**  
**CRAFTED PLANK (ECF )**

# Tandus Centiva

A Tarkett Company

## SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard <ul style="list-style-type: none"><li>• Natural Grain (NG) ECF 2115, ECF 2118, ECF 2122, ECF 2123, ECF 2124, ECF 2129, ECF 2131</li><li>• Third Grain (TG) ECF 2119, ECF 2120, ECF 2121, ECF 2126, ECF 2127, ECF 2130</li><li>• Weathered (WE) ECF 2128, ECF 2132</li><li>• Worn Grain (WG) ECF 2125, ECF 2133</li></ul>
<b>Urethane:</b>	Factory Applied
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	56



<b>SIZES</b>	6" x 48"
	7.2" x 48

## TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

## ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals
<b>Indoor Air Quality:</b>	FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

**Q QUICKSHIP PROGRAM**  
Contact your Tandus Centiva account executive for QuickShip availability.

LEED v4  
MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



ROLLSMART®



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

## EVENT SERIES HERITAGE PLANK (EHP)

# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Natural Grain (NG) (GW38 only) Rustic (RU) (3350, 3352, 3354) Third Grain (TG) (GW29 only) Weathered Grain (WE) (3208, 3209)
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	7
<b>Adhesive:</b>	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.
<b>Installation Methods:</b>	



HERRINGBONE



UNIDIRECTIONAL



Product shown: EHP 3350

<b>SIZES</b>	4"x36" (10.16 cm x 91.44 cm) 6"x36" (15.24 cm x 91.44 cm)
--------------	--

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals; Non-Toluene Ink System
<b>Indoor Air Quality:</b>	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Manufacturing:</b>	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

### QUICKSHIP PROGRAM

 All colors in this style

LEED v4  
MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

## EVENT SERIES QUARTZITE (EQZ)


# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Quarry (QU)
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	4
<b>Adhesive:</b>	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

### Installation Methods:



QUARTER TURN



VERTICAL  
ASHLAR



HORIZONTAL  
ASHLAR



Product shown: EQZ 7232

<b>SIZES</b>	12"x18" (30.48 cm x 45.72 cm) 18"x18" (45.72 cm x 45.72 cm)
--------------	--

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals; Non-Toluene Ink System
<b>Indoor Air Quality:</b>	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Manufacturing:</b>	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

### QUICKSHIP PROGRAM

 All colors in this style

LEED v4  
MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.





TILE + PLANK

## EVENT SERIES SLATE (ESL)


# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Rock (RK)
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	5
<b>Adhesive:</b>	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

### Installation Methods:



Product shown: ESL RR65

<b>SIZES</b>	12"x18" (30.48 cm x 45.72 cm) 18"x18" (45.72 cm x 45.72 cm)
--------------	--

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals; Non-Toluene Ink System
<b>Indoor Air Quality:</b>	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Manufacturing:</b>	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

### QUICKSHIP PROGRAM

 All colors in this style

LEED v4  
MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

## EVENT SERIES STRIATE (ESA)

# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Rock (RK)
<b>Urethane:</b>	Factory Applied
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	56



Product shown: ESA 2106

<b>SIZES</b>	18" x 18"
	12" x 36"
	18" x 36"

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals
<b>Indoor Air Quality:</b>	FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard



#### QUICKSHIP PROGRAM

Contact your Tandus Centiva account executive for QuickShip availability.

LEED v4  
MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



ROLLSMART®



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.



TILE + PLANK

## EVENT SERIES TRAVERTINE (ETR)


# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Quarry (QU)
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	4
<b>Adhesive:</b>	CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other Tandus Centiva LVT preferred adhesives.

### Installation Methods:



Product shown: ETR 7212

<b>SIZES</b>	12"x18" (30.48 cm x 45.72 cm) 18"x18" (45.72 cm x 45.72 cm)
--------------	--

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals; Non-Toluene Ink System
<b>Indoor Air Quality:</b>	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Manufacturing:</b>	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard

### QUICKSHIP PROGRAM

 All colors in this style

LEED v4  
MRc2 Building Product Disclosure and Optimization –  
Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization –  
Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.





TILE + PLANK

## EVENT SERIES URBAN STONE (EUS)

# Tandus Centiva

A Tarkett Company

### SPECIFICATIONS

<b>Classification:</b>	ASTM F1700 Class III Type B
<b>Total Thickness:</b>	0.120" (3.0 mm)
<b>Wear Layer Thickness:</b>	30 mil (0.76 mm)
<b>Edge Treatment:</b>	Square (SE), optional Slight Bevel (SB)
<b>Emboss:</b>	Standard Rock (RK)
<b>Urethane:</b>	Factory Applied
<b>Warranty:</b>	20-Year Limited Commercial Wear Warranty
<b>Colors:</b>	56

<b>SIZES</b>	18" x 18"	12" x 36"
	18" x 36"	36" x 36"



Product shown: EUS 2105

### TESTING

<b>Flexibility:</b>	ASTM F137	Passes
<b>Dimensional Stability:</b>	ASTM F2199	Passes
<b>Static Load:</b>	ASTM F970	Passes
<b>Residual Indentation:</b>	ASTM F1914	Excellent
<b>Flammability:</b>	ASTM E648	CRF $\geq$ 0.45 watts/cm <sup>2</sup> NFPA Class 1
<b>Slip Resistance:</b>	ASTM D2047	Passes >0.5 ADA Compliant
<b>Smoke Density:</b>	ASTM E662	Passes <450 D <sup>MC</sup>
<b>Resistance to Light:</b>	ASTM F1515	Excellent
<b>Chemical Resistance:</b>	ASTM F925	Excellent
<b>Resistance to Heat:</b>	ASTM F1514	Excellent

### ENVIRONMENTAL DATA

<b>Materials:</b>	No Heavy Metals
<b>Indoor Air Quality:</b>	FloorScore® Certification
<b>Recyclability:</b>	100% Recyclable through our ReStart® Program
<b>LEED Scoreboard:</b>	LEED 2009 MRc2 Construction Waste Management MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring
<b>Packaging:</b>	Packaged in recycled, corrugated cardboard



#### QUICKSHIP PROGRAM

Contact your Tandus Centiva account executive for QuickShip availability.

LEED v4  
MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations  
MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials  
MRc5 Construction and Demolition Waste Management  
IEQc2 Low-Emitting Materials



ROLLSMART®



- For samples, warranties and more information, visit [tandus-centiva.com](http://tandus-centiva.com) or call 800.248.2878.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.