

Style	ColorScape Tile	ColorSpec Tile
Construction	Thermoset Rubber Tile	Thermoset Rubber Tile
Classification	ASTM F1344 - Class 1, Type A	ASTM F1344 - Class 1, Type B
Finish	Matte	Matte
Total Thickness	1/8" (3.175 mm)	1/8" (3.175 mm)
Profile	Round, Square, Sculptured	Smooth, Square, Sculptured
Sizes	18.125" x 18.125" (460 mm x 460 mm) 36" x 36" (914.4 mm x 914.4 mm) 36.125" x 36.125" (917.7 mm x 917.7 mm) 36.25" x 36.25" (920.75 mm x 920.75 mm) Sizes are Profile Dependent	18" x 18" (457.2 mm x 457.2 mm) 18.125" x 18.125" (460 mm x 460 mm) 36" x 36" (914.4 mm x 914.4 mm) 36.125" x 36.125" (917.7 mm x 917.7 mm) 36.25" x 36.25" (920.75 mm x 920.75 mm) Sizes are Profile Dependent
Colors	36	36
Packaging	20 pieces per case; larger tiles sold by piece	20 pieces per case; larger tiles sold by piece
Weight Per Carton	44 lbs. (20 kg) per carton	44 lbs. (20 kg) per carton
Adhesive	Mannington MR-721 Epoxy Adhesive; M-725 Polyurethane Adhesive; MR-911 One Part Acrylic Adhesive for above-grade and stairwell applications	Mannington MR-721 Epoxy Adhesive; M-725 Polyurethane Adhesive; MR-911 One Part Acrylic Adhesive for above-grade and stairwell applications
Installation Method	Install flooring in strict accordance with the Mannington Rubber Tile Installation Instructions	Install flooring in strict accordance with the Mannington Rubber Tile Installation Instructions
Testing		
Static Load (ASTM F970)	500 PSI	
Smoke Density (ASTM E662)	Passes - < 450	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Slip Resistance (ASTM C1028)	Passes - ≥ 0.6	
Environmental Data		
Rapidly Renewable Content	Contains 4% Rapidly Renewable Resource Content by total product weight	
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
LEED Scoreboard	May contribute to LEED credits LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials	
Product Declarations	EPD	
mindful Materials	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA USA	
Warranty		
	Limited 10 Year Wear Warranty Limited 10 Year Commercial Warranty	

- ColorScape and ColorSpec formulations are made with our superior rubber so they retain their amazing color, resist indentations and cracking, and are quiet underfoot. Built-in waxes produce a natural luster that requires no finish or stripping, lowering maintenance costs.
- ColorScape and ColorSpec are not recommended in commercial areas that require static dissipation.
- In spaces that will receive rubber flooring and accessories, maintain a minimum temperature of 65° F (18° C) and a maximum temperature of 85° F (29° C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55° F (13° C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in product appearance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.

Crafted with purpose

For more information, contact your local Mannington representative or visit manningtoncommercial.com