












## SPECIFICATIONS

Wall Base		Optimum Edge®	Optimum Edge® 100	Premium Edge™	Mannington Edge™
	CONSTRUCTION	Thermoset Rubber, Type TS	Thermoset Rubber, Type TS	Thermoplastic Rubber, Type TP	Thermoplastic Vinyl, Type TV
	AVAILABLE HEIGHTS/SIZE	2 1/2" (64 mm) 4" (102 mm) 6" (152 mm) Coved or Toeless	4" (102 mm) Coved Available in ten colors**	2 1/2" (64 mm) 4" (102 mm) 4 1/2" (114 mm) 6" (152 mm) Coved or Toeless	2 1/2" (64 mm) 4" (102 mm) 4 1/2" (114 mm) 6" (152 mm) Coved or Toeless
	OVERALL THICKNESS	1/8" (3.2 mm)	1/8" (3.2 mm)	1/8" (3.2 mm)	.08" (2.0 mm) & 1/8" (3.2 mm)
	PACKAGE COUNT	25-4' pieces = 100' per carton	1-100' continuous roll	1-100' continuous roll or 25-4' pieces	1-100' continuous roll or 25-4' pieces
	AVERAGE WEIGHT PER CARTON 2 1/2"/4"/ 4 1/2"/6"	Coved = 27/39/53 lbs. Toeless = 24/39/50 lbs.	Coved = 38 lbs.	Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs.	Coved (.08") = 19/27/41/42 lbs. Toeless (.08") = 17/25/41/39 lbs. Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs.
	AVERAGE WEIGHT PER CARTON – CORNERS	Coved = 3/4/7 lbs. Toeless = 3/4/7 lbs.	N/A	Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs.	Coved (.08") = 3/3/8 lbs. Toeless (.08") = 2/3/7 lbs. Coved (1/8") = 3/4/9 lbs. Toeless (1/8") = 3/4/9 lbs.
	CORNERS	Factory molded, specify job site wrapped or molded	Specify job site made corners	Factory Pre-formed, specify job site wrapped or preformed	Factory Pre-formed, specify job site wrapped or preformed
	3RD PARTY CERTIFICATIONS	FloorScore			
	XPRESS	When you really need it now. Our innovative delivery program ensures that you get the carpet and hard surface products you need quickly and reliably. With product available to ship within 5 business days, Mannington's Xpress program leads the industry in service. Please refer to <a href="http://www.manningtoncommercial.com">www.manningtoncommercial.com</a> to view Xpress products.			

\*\* Optimum Edge® 100 is available in ten colors: 901 Night Black, 902 Deep Suede, 903 Dark Chocolate, 904 Bark, 905 Pewter, 907 Stone Gray, 911 Sable, 913 Mineral Gray, 918 Flax, 933 Sandrift

	Optimum Edge®	Optimum Edge® 100	Premium Edge™	Mannington Edge™
 WARRANTY	This product is backed by our Limited 5 Year Commercial Warranty			
 LEED	Mannington Commercial products may contribute to multiple LEED credits.			
FINISH	Smooth Satin Luster	Smooth Satin Luster	Smooth Matte	Matte
SPECIFICATIONS ASTM (F-1861)	Type TS, Group 1	Type TS, Group 1	Type TP, Group 1	Type TV, Group 1
FLOORING RADIANT PANEL TEST (ASM-E-648)	≥ 0.45 watts/cm <sup>2</sup> , Passes — Class 1			
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662)	< 450, Passes			
INSTALLATION ADHESIVE	Mannington MR-101 Acrylic Wall Base Adhesive			



Floor design copyrighted by Mannington Mills, Inc. 2014. For complete specifications, visit [www.manningtoncommercial.com](http://www.manningtoncommercial.com).



**MANNINGTON**  
COMMERCIAL